

## General Informationen

Offer Number	Order Number	Model Number	Model	Year Built
13109492	5205979	674887	SKO 24/L - 13.4 FP 60 COOL	15.01.19

## Size and Weight

Internal length	13410mm	Gross weight (Plated/Design)	42000/42000kg
Internal width	2460mm	Payload (Plated/Design)	0kg
Internal height	2650mm	Axle group load (Plated/Design)	27000/27000kg
Usable internal length	13315mm	King pin load (Plated/Design)	15000/15000kg
Usable internal height	2550mm	Total tare weight	8179kg
Total height at front (unladen)	4010mm	Coupling height	1139mm
Total height (unladen)	4010mm	Overall length	13550mm
Total height at rear (unladen)	4010mm	Overall trailer width	2600mm
Floor height at rear (unladen)	1280mm	Suspension ride height	405mm
Tyre size	385/65R22.5	Wheelbase	7600mm
		Door aperture height	2640mm
		Door aperture width	2460mm

## Equipment

### Special requests

X90292 vehicle conforms to EU-Type approval with Certificate of Conformity (CoC) X91012	1
Country of registration: "the Netherlands"	1

### **CARGOBULL \*\*\* HIGHLIGHTS \*\*\***

C00174 Production VREDEN	1
--------------------------	---

### **Registration/Certification**

P02123 2 reflective marker plates 565x200 ECE-R70 fitted vertically on rear doors	1
X90161 Provision of German ATP FRC certificate including sticker and ATP plate	1
X91500 Body certified to HACCP regulations , incl. HACCP cert. and decal on front bulkhead X90139	1
ECMT-certificate	1
X90094 Providing of export plate incl comprehensive urance with 1000EUR perc. excess for 4 weeks	1
X90122 International custom seal (TIR) for body with rear door, with TIR certificate	1
P02098 2 TIR plates, foldable, 1x at the front,1x at the rear	1

### **Chassis**

C00212 Galvanized and bolted "short chassis" for self-supporting body	1
C00332 Semi-trailer suitable for tractor unit to ISO 1726	1
C31032 Single bolted 2" king pin, position 1600mm, 1 Königsbolzenst. 1600mm	1
C00301 10 years warranty against rust breakthrough on galv. parts (as per terms & conditions)	1
C00306 Trailer wheelbase 7600 mm	1
C21013 Rear underrun bar bolted according to RL 70/221/EWG	1
C40120 Basket type spare wheel carrier for 2 wheels behind the axle group	1
X00140 side guard rails to RL 89/297/EWG in conjunction with pallet rack: SCHMITZ GRANITE	1

## Axles

<b>A00875</b>	<b>3x9t SAF-axles, drum brake</b>	<b>1</b>
A30051	SAUER axle, 9t, track 2040, Sp. ctr. 1300, 0-offset drum brake 420 mm	3
B99903	Brake size 420 x 180 for 3 axles	1
R00053	10 stud wheel spigot mounting according to DIN 74 361 (part 3)	1
<b>X90009</b>	<b>Wheel nut spanner</b>	<b>1</b>

## Suspension

<b>A00737</b>	<b>SCB-air susp. type: MRH-HO30</b>	<b>3</b>
---------------	-------------------------------------	----------

## Equipment

### Brake system

B99800	Dual line brake system according to RR EG 71/320 - Palm couplers	1
B12013	EBS 2S/2M, with roll stability program	1
B14045	EBS power supply by ISO 7638 socket + CAN-bus	1
A00914	Spring brake air chambers	1
B99893	Raise-lower valve with AUTO-RESET function	1
B99905	2 wheel chocks with holders	1

### Landing gear

C50025	Landing leg JOST, half-round foot with plate, single-side operation, low maintenance	1
--------	--	---

### Light system

E00250	lighting system 24V acc to ECE R48 with multi-chamber lights & LED rear marker lights	1
E00077	Premium distribution with 3 outlets 2x7poles DIN ISO3731+DIN ISO1185+1x15pol.DIN ISO12098	1
C24001	Rear lamp panel with "SCHMITZ" logo, colour: WHITE	1
E00107	LED side marker lights with reflectors	1
K75102	2 x red rear marker lights (top), 4 x white front marker lights/reflectors	1
E00128	1 pair of LED tracking lights	1
E10031	Without back-up warn. syst. / ramp appr. aid	1

### Wheels and tyres

<b>R30019</b>	<b>Regional traffic tyres (M + S)</b>	<b>1</b>
<b>R30003</b>	<b>Tyre make: SCB choice</b>	<b>1</b>
R40002	6x 385/65R22.5 (11.75x22.5)	1
<b>R40150</b>	<b>Steel rims</b>	<b>6</b>
R00078	Protective caps for wheel nuts	1

### Spray suppression

P00780	without additional mudguard	1
P00830	Vertical plastic mudguards	1
P00791	anti-spray acc. to regulation (EU) Nr. 109/2011 mudflaps with SCB logo	1
K11121	Splash protectors to the side of the axle group	1

## **Further chassis equipment**

C90302	Galvanised foldaway steel ladder with step at top, fitted to the rear	1
V00008	Without lashing rings	1
P02020	2 rear corner rubber block buffers	1
P02021	2 vertical rubber block buffers mounted on lamp panel	1
P02024	1 rear rubber buffer across rear width	1
<b>X10200</b>	<b>Pallet rack for 36 Euro/ 24 ISO pallets</b>	<b>1</b>
B99934	Coupling connectors and sockets mounted on front bulkhead	1

## **Body**

K00001	PU foam panel, free of thermal bridges, sealed against vapour diffusion	1
K09020	Covering skin internally galvanised, coil-coating fine-steel sheet, plastic coated	1

## **Front bulkhead/Roof/Side walls**

K21020	Insulated front bulkhead, NX17 foam, with reinforcement for fridge installation	1
K43010	EFP insulated sidewall, COOL 60, NX17 foam	1
<b>K29047</b>	<b>Circulation wall approx. 1800mm high, made of ALU hollow profiles, internal length -95 mm</b>	<b>1</b>
K63005	FP insulated roof, NX 17 foam	1
<b>K29091</b>	<b>Pallet stop fitted (4 x galvanised "hat" profiles at bottom of circulation wall)</b>	<b>1</b>

## **Rear closure**

<b>K31051</b>	<b>Insulated double rear doors (FP, NX17) foam with double s/steel lockrods</b>	<b>1</b>
K39013	Rear frame is stainless steel, sand blasted finish	1
K73311	300mm depth, anodized aluminium kick strip fitted at base of each rear door	1
P02040	Hinge protection rubber buffers fitted vertically to lower part of the rear frame	1
P02071	Without add. buffer protection to rear frame across bottom	1

## **Equipment**

### **Floor**

<b>K11007</b>	<b>Aluminium barley seed floor, low noise, rated at 5500kg</b>	<b>1</b>
K12001	300mm aluminium kick strip at front and both sides welded to floor	1

### **Further body equipment**

K72466	without multifunction clamping bars	1
K72440	Without tension belt for load securing rail	1
K75082	Box interior lighting with switch Powered from parking light	1

### **Refrigeration unit**

<b>K81444</b>	<b>THERMO KING SLXi 300 - 30 with BlueBox, OptiSet and modulation</b>	<b>1</b>
K80594	Provision for THERMO KING SLXi300	1
K80001	Fridge unit aperture cut out and bolt holes drilled in front bulkhead	1
<b>K80076</b>	<b>2 temperature sensors for CargoWatch</b>	<b>1</b>
<b>K80079</b>	<b>2 temperature sensors for temperature recording</b>	<b>1</b>
<b>K80126</b>	<b>Installation package for mono temp fridge,SKO</b>	<b>1</b>
K80223	Filler neck r.h.s.	1

<b>K80227</b>	<b>SCHMITZ black plastic fuel tank 245l 1 filling neck ; BIO-Diesel proof</b>	<b>1</b>
<b>K80429</b>	<b>Fridge Country Package 16</b>	<b>1</b>
<b>K91369</b>	<b>Euroscan TX3 temperature recorder with printer, according to EU-RL 12830</b>	<b>1</b>
<b>K91410</b>	<b>Provision for temperature recorder Euroscan TX3 (only for ATP application)</b>	<b>1</b>
<b>K77024</b>	<b>Tube type air chute under the roof (up to 13500 mm int. length)</b>	<b>1</b>

### ***Painting/Finishing***

<b>K99204</b>	<b>Roof painted in SCB 9010 white</b>	<b>1</b>
<b>C00135</b>	<b>Chassis: Hot dip galvanized</b>	<b>1</b>
<b>G00093</b>	<b>Hubs: Factory finished (KTL) black</b>	<b>6</b>
<b>C00087</b>	<b>Wheel rims: Factory finish (Silver)</b>	<b>1</b>
<b>K99050</b>	<b>Body finished in white SCB 9010</b>	<b>1</b>
<b>K99210</b>	<b>Landing legs: Factory finish - Jet Black</b>	<b>1</b>
<b>X90199</b>	<b>Without lettering</b>	<b>1</b>
<b>K99065</b>	<b>Colour of pallet box side cover as requested Standard colour category 1</b>	<b>1</b>
<b>X90340</b>	<b>Partial contour marking on side wall: white, all around on rear: red (S.KO)</b>	<b>1</b>

---