

## Mercedes-Benz Actros 3 3344 S 6X4

Model:	Mercedes-Benz Actros 3	Engine power:	320 kW (435 hp)
Vehicle type:	3344 S	Wheelbase:	3300 mm
Drivetrain:	6X4	Gross vehicle weight:	33000 kg
Baumuster:	93416112	Steering type:	left
Vehicle type:	Semitrailer tractor	Fifth wheel position:	1000 mm
Driver cabin:	L-Cab		

## Equipmentlist

### Paint

Cab paintwork:	MB 2549 pure orange <b>(RAL 2004)</b>
----------------	---------------------------------------

### Tyres

1st Axle:	2x 315/80 R 22,5 Continental	F18K27 10 (S+G) Highway cross country
2nd Axle:	4x 315/80 R 22,5 Continental	F18K29 10 (S+G) Highway cross country
3rd Axle:	4x 315/80 R 22,5 Continental	F18K29 10 (S+G) Highway cross country
Spare wheel:	1x 315/80 R 22,5 Continental	F18K29 10 (S+G) Highway cross country

### Standard equipment

A91	Front axle, straight version
AL3	Front axle 7.5 t
AM3	Rear axle H7, 13.0 t, crown wheel 300 Differential lock rear axle
BB5	Disc brakes on front and rear axle
BB8	Telligent braking system with ABS and ASR
BD3	Brake and electrical connections, high Dual-circuit full air brakes Automatic brake adjusting Trailer brakes 2-lines Flexible electric- and brake connections Compressed-air drier (single-chamber system) Roll back prevention
CL9	Steering LS 6/LS 8 Stabilizer front axle Steering column-rake and height adj. w. pneum lock

	Implement carrier, left
	multi-function steering wheel
DUP0	Basetype
EC6	Trailer socket, 15-pin
	Batteries 2x12V 165 AH
FE5	Power windows for driver's/co-driver's door
FN1	Distribution cockpit
FS2	Wide-angle mirror on driver's side, heated
	Cab rear wall without window
	Wide-angle exterior mirror on front passenger side
	Electrical adjustable, heated rearview mirrors
	Ramp mirror on co-driver's side
	Central locking system
	Air controlled heating/ventilation system
	Outside temperature gauge
	Telligent Maintenance System
KH8	Exhaust silencer, tailpipe downwards
KS4	Main tank, 400 l, steel
	Fuel consumption display
	6-part tail light cluster with reflector
	Headlamp unit, H7, with clear-lens look
	Indicator transmitter for extra indicator lamps
MA9	Engine mountings, for off-road use
MD4	Speed limiter, 90 km/h, EC
MD9	Cruise control
MG8	Top air intake rear, frame-mounted air cleaner
MS3	Engine version, Euro III
MV4	Engine, V6, LA, 320 kW (435 hp), 1800 rpm
	Single-cylinder air compressor, non-regulated
	Fuel preheating system
	Engine brake with constantly open throttle valve
	Radiator protection, bottom
N55	Transmission oil cooling
P44	Wing, for chassis transit
R38	15-degree tapered rims, 9.00 x 22.5
TR6	Weight variant 33.0 t (7.5/13.0/13.0)
XK3	Powertrain warranty, Gen.Terms/Con., 3 yrs/250000 km
XV6	Actros 3
	Steps and standing space behind cab
	Tools for export
Z01	Country-specific version
ZZ3	Vehicle, for right-side traffic

## Selected equipment

AQ3	Axle ratio i = 4.571 (HL7)
C63	Bumper, steel version
C69	Support bracket for fifth-wheel coupling, extended
DS3	Pop-up roof, electric
E84	Battery box, lockable
ES8	Additional socket, 24 V/15 A, firewall
ET2	Voltage transformer, 24 V/12 V, 15 A
EU1	CD-radio
EV2	Provision for fitting CB radio
F04	L-cab (w/o DD2)
F52	Sun visor, exterior, transparent
FE6	Cab steps, movable
FL3	Cab mountings, rear, reinforced
FL4	Comfort cab mountings, steel-sprung
FM2	Windows, tinted, with sun filter
FS4	Sunblind, side window in driver's door
FT0	Exterior rear-view mirror, grooved cover
FW2	Deletion, immobiliser (transponder)
FX7	Front mirror, aerodynamic
FZ9	Additional keys or remote-control transmitter Arching cab rear wall
G81	Clutch, reinforced
GC2	Transmission G 240-16/11.7-0.69
GS3	Gearshift, hydraulic
H03	Air conditioning system
H04	Heat insulation, additional
HF1	Construction-site filter
J10	Speedometer, km
J70	Air horn
JK3	Inst. cluster, graphics-capable display, eco-meter
JW0	Reversing warning device
K40	Tank-cap lock
K45	Screen, tank filler neck
K81	Fuel pre-filter, heated water separator
KI0	Protective plate under main tank
L16	Fog lamps, halogen
L28	Floodlights
L30	Protective grilles, headlamps
L54	Rotating beacon, yellow, left+right, front
L72	Electrics, for non-MB body
M45	Alternator 28 V/100 A
M60	Paper air cleaner, larger
M67	Cyclone pre-filter
M72	Protective plate under radiator and engine
M78	Engine number, stamped-in

---

MK9	Insect screen, in front of cooling system
MP2	Engine cooling power, increased
NH2	PTO, layshaft MB 131-2c
QF6	Rear spring, 16.0 t, hard
QJ7	5th-whl coupl,Jost 38-C1, 3.5-in, H=190mm,man. lubr.
QM8	Assembly plate, 40 mm, for 36t 5th-wheel coupling
QY1	Front spring, 9.0 t, hard
R04	Wheel nut cap
R60	Spare wheel carrier, provisional
R87	Spare wheel/spare wheel rim
SF1	Fold-up seat, velour, co-driver
SH1	Driver's comfort suspension seat, Grammer
SM5	Luxury bed, bottom
SV6	Seat backrest, release mechanism
X42	Labels/publications, English
XW9	Deletion, noise reduction measures
Y10	First aid kit
Y28	2 wheel chocks
Y34	Tyre inflating hose, 10 m
Y42	Telescopic jack, 12 t
Y44	Hazard warning triangle
YA8	Deletion, front apron

---

## Other facts

---

MP0	Engine Package for heavy-duty operation
-----	---

---

## Technical specifications

Fifth wheel position: 1000 mm

## Technical Data

Technical illustration

