



Mercedes-Benz



**SCHWING**

## Mercedes Benz Actros 5050 K 10x4/6/6500 Actros for Schwing S 58 SX

Model:	Mercedes-Benz Actros 3
Vehicle type:	5050 K
Drivetrain:	8X4
Baumuster:	93231512
Vehicle type:	Tipper chassis
Driver cabin:	M-Cab with low roof
Engine power:	370 kW (503 HP)
Wheelbase:	5600
Gross vehicle weight:	50000 kg
Steering type:	left

## Equipmentlist

### Paint

cabin:	MB 9147 arctic white
--------	----------------------

### Equipment

#### Chassis version

KCVX Extension of wheelbase by 1100 mm ( 1<sup>st</sup> axle to 3<sup>rd</sup> axle 5600 )

#### Axle load distribution

Z99 Weight variant 50.0 t (9.0 t / 9.0 t / 13.0 t / 13.0 t / 9.5 t)

#### Engine

MV6 Engine, V8, LA, 370 kW (503 hp), 1800 rpm

MS3 Engine version, Euro III

M49 Tandem air cleaner system ( to be modified )

>>> Fuel preheating system

K81 Fuel pre-filter, heated, water separator

>>> Radiator protection, bottom

ML3 High-speed fan, with belt drive

>>> Engine brake with constantly open throttle valve

>>> Single-cylinder air compressor, non-regulated

---

N53 Engine PTO, rear, for hydraulic pump

---

M72 Protective plate under radiator and engine

---

M78 Engine number, stamped-in

---

MA9 Engine mountings, for off-road use

---

## Clutch & transmission

---

GC2 Transmission G 240-16/11.7-0.69

---

N55 Transmission oil cooling

---

NG8 PTO flange, with cross serrations, D=120 mm

---

GS3 Gearshift, hydraulic

---

N56 PTO, live, MB, 1.4

---

N90 Deletion, tipper drive

---

NK7 Gearshift interlock, live PTO (NMV)

---

## Axles & suspension

---

A91 Front axle, straight version

---

>>> Front axle load compensating system

---

AL5 Front axle 9.0 t

---

AM3 Rear axle H7, 13.0 t, crown wheel 300

---

>>> Differential lock rear axle

---

AR1 Axle ratio  $i = 5.333$  (HL7)

---

QD1 Front spring, 9.0 t,

---

QF3 Rear spring, 15.0 t, hard

---

>>> Stabilizer front axle

---

C42 Stabiliser, rear axle, under frame

---

## Wheels & tyres

---

RA9 Tapered rims, 11,75 x 22,5 on front axle

---

R38 Tapered rims, 9,00 x 22,5

---

R04 Wheel nut cap

---

1.A. W48K16 10 2 x 385/65 R 22,5 TL Highway "K"

---

2.A. W48K16 10 2 x 385/65 R 22,5 TL Highway "K"

---

3.A. F18L76 13 4 x 315/80 R 22,5 TL Traction ( M+S ) "L"

---

4.A. F18L76 13 4 x 315/80 R 22,5 TL Traction ( M+S ) "L"

---

5.A. 2 x 385/65 R 22,5 TL Highway

---

## Frame and components attached to frame

---

CL9 Steering LS 6/LS 8

---

>>> Implement carrier, left

---

KU2 Main tank, 300 l, alloy

---

K40 Tank-cap lock

---

K45 Screen, tank filler neck

---

K68 Exhaust silencer(s), vertical, behind cab ( to be modified )

---

P44 Wing, for chassis transit

---

C63 Bumper, steel version

---

C95 Deletion, rear underride guard (EC)

---

Q18 End crossmember, bolted

---

## Brake system

- >>> Dual-circuit full air brakes
- >>> Automatic brake adjusting
- >>> Roll back prevention
- BB6 Drum brakes on front and rear axle
- BB0 Anti-lock braking system (ABS), disengageable
- BB8 Telligent braking system with ABS and ASR
- B65 Compressed air dryer, heated

## Cab exterior

- F05 M-cab
- DD1 Cab with low roof, standing room 1400 mm
- F24 Cab rear wall, straight
- F35 Cab rear wall with window
- FL6 Cab mountings, standard
- FC7 Windows, tinted, without sun filter
- D25 Roof hatch/vent, roof
- FE6 Cab steps, movable
- FS2 Wide-angle mirror on driver's side, heated
- FT0 Exterior rear-view mirror, grooved cover
- >>> Wide-angle exterior mirror on front passenger side
- >>> Electrical adjustable, heated rearview mirrors
- >>> Ramp mirror on co-driver's side
- FZ7 Immobiliser, with transponder
- >>> Central locking system

## Cab interior

- SH1 Driver's comfort suspension seat, Grammer
- SF1 Fold-up seat, velours, co-driver
- >>> Steering column-rake and height adj. w. pneum lock
- >>> multi-function steering wheel
- FN1 Distribution cockpit
- FE5 Power windows for driver's/co-driver's door
- JK2 Instrument cluster, graphics-capable display
- JN0 Tachograph, 1 day + 2 drivers, modular
- >>> Outside temperature gauge
- >>> Fuel consumption display
- JW0 Reversing warning device
- >>> Telligent Maintenance System
- EV6 Provision, 12-V radio, retrofit
- ET2 Voltage transformer, 24 V/12 V, 15 A
- HF1 Construction-site filter
- >>> Air controlled heating/ventilation system
- H03 Air conditioning system

## Electrics / electronics

- M45 Alternator 28 V/100 A
- EM8 PSM, body and trailer CAN, ISO 11992
- >>> Headlamp range adjuster
- >>> Headlamp unit, H7, with clear-lens look

- >>> 6-part tail light cluster with reflector
- >>> Indicator transmitter for extra indicator lamps
- MK6 Speed limiter, electronic, 85 km/h
- MD9 Cruise control

#### Additional scopes

- XW9 Deletion, noise reduction measures
- Y10 First aid kit
- Y44 Hazard warning triangle
- Y45 Warning lamp
- Y20 Tools for export
- Y34 Tyre inflating hose, 10 m
- YK4 Compressed-air gun, supplied loose
- Y28 2 wheel chocks
- XK3 Powertrain warranty, Gen. Terms/Con., 3 yrs/250000 km
- XV6 Actros 3
- X38 Model identification, acc. to weight variant
- X49 Labels/publications, Netherlands
- ZZ3 Vehicle, for right-side traffic

**plus all necessary modifications to mount the SCHWING S 58 SX concrete pump**