



1x **Daimler Demo Unit** MERCEDES-BENZ 4661/8X8/4800 "ACTROS"
with Rotzler double winch system 2x25t with extraction winch

General Information

MERCEDES-BENZ 4661/8X8/4800 "ACTROS"

Milage	5.525 Km
Mounting	Tractor head
Cab	L-Cab
Engine	Engine, V8, LA, 425 kW (578 HP), 1800 rpm, Euro 3
Wheel base	4.800 mm, 8x8/4
Steering	Left hand drive
Suspension	Front spring, 9.0 t hard, asymmetrical Rear spring, 18.0 t, for axle spacing 1450 mm
Gearshift	Powershift
Paintwork	7754 steel grey metallic
Tires	F18L16 10 x 2, 315/80 R 22,5# TL Highway "L" F18L16 10 x 2, 315/80 R 22,5# TL Highway "L" F18L16 10 x 2, 315/80 R 22,5# TL Highway "L" F18L16 10 x 2, 315/80 R 22,5# TL Highway "L"



Equipment

AL5	Front axle 9.0 t
AM6	Rear axle H7, 16.0 t, crown wheel 300
AR5	Axle ratio $i = 6.000$ (HL7)
A70	Differential lock, front axle
BB0	Anti-lock braking system (ABS), disengageable
BB1	Telligent braking system with ABS
BB6	Drum brakes on front and rear axle
BB9	Pipe fracture protection for brake system
BE4	Compressed air supply connection, front
B43	Trailer brake, 2-line
B62	Compr. air dryer, heated (twin-chamber system)
CL9	Steering LS 6/LS 8
CR5	Frame front end, reinforced, for special attachments
C42	Stabiliser, rear axle, under frame
C63	Bumper, steel version
C95	Deletion, rear underride guard (EC)
DD2	Cab with low roof, standing room 1560 mm
D25	Roof hatch/vent, roof
EB3	Batteries, 2 x 12V/220 Ah, low-maintenance
EC6	Trailer socket, 15-pin
EC8	Adapter, 15-pin to 2x7-pin socket
ED7	Socket under battery cover, for hand lamp
EM8	PSM, body and trailer CAN, ISO 11992
EM9	PSM, body CAN, ISO 11898 instead of 11992
EU1	CD-radio
E39	Automatic cutouts
E84	Battery box, lockable
FE5	Power windows for driver's/co-driver's door



Mercedes-Benz

FE6	Cab steps, movable
FJ4	Floor mat, rubber, driver's and co-driver's side
FL3	Cab mountings, rear, reinforced
FL6	Cab mountings, standard
FM2	Windows, tinted, with sun filter
FN1	Distribution cockpit
FS2	Wide-angle mirror on driver's side, heated
FS5	Sunblind, side window on both sides
FT0	Exterior rear-view mirror, grooved cover
FW2	Deletion, immobiliser (transponder)
F04	L-cab
F24	Cab rear wall, straight
F34	Cab rear wall without window
F52	Sun visor, exterior, transparent
GE3	Mercedes PowerShift
GH4	Mercedes PowerShift G 280-16/11.7-0.69
GK1	Oil cooler, for transfer case
GK8	Preinstallation turboclutch, only with CTT offer
GV8	Transfer case VG2400 - 3W, single-speed
GZ7	Clutch supplier F&S
HF1	Construction-site filter
H03	Air conditioning system
H04	Heat insulation, additional
JK2	Instrument cluster, graphics-capable display
J10	Speedometer, km
J58	Warning device for seat belts
J70	Air horn
KJ6	Exhaust silencer, vertical, central, behind cab
KS2	Main tank, 300 l, steel
K40	Tank-cap lock
L16	Fog lamps, halogen
L72	Electrics, for non-MB body
MA9	Engine mountings, for off-road use
MD9	Cruise control
MK9	Insect screen, in front of cooling system
ML3	High-speed fan, with belt drive
MP2	Engine cooling power, increased
MS3	Engine version, Euro III
MT0	Water circuit for turbo clutch
MT7	Speed limiter, electronic, 80 km/h
MV8	Engine, V8, LA, 425 kW (578 hp), 1800 rpm
M00	Omiss. of protect. plate under radiator and engine
M32	Air compressor, additional
M45	Alternator 28 V/100 A
M49	Tandem air cleaner system
M78	Engine number, stamped-in
NH2	PTO, layshaft MB 131-2c
NZ1	PTO, single
N52	Engine takeoff, rear, torque 600 Nm
N54	Coupling, flexible, for engine takeoff (loose)
N55	Transmission oil cooling
QD9	Front spring, 9.0 t hard, asymmetrical

QF8	Rear spring, 18.0 t, for axle spacing 1450 mm
Q18	End crossmember, bolted
RC0	Wide-base wheel, 10.00W-20, with tube
R04	Wheel nut cap
SH1	Driver's comfort suspension seat, Grammer
SH2	Co-driver's comfort suspension seat, Grammer
SL7	Provision for retrofitting seat/bunk combination
SV6	Seat backrest, release mechanism
TT9	Weight variant 48.0 t (9.0/9.0/16.0/16.0)
U88	Model plate, manual
XC2	Model plate, Gulf States
XQ3	VIN encoded complete vehicle data, Mercedes-Benz
XV6	Actros 3
XW9	Deletion, noise reduction measures
XY5	Model year 5
XZ1	Paint, additional control code
X38	Model identification, acc. to weight variant
X42	Labels/publications, English
X53	Publications, Arabic, additional
YK4	Compressed-air gun, supplied loose
Y16	Fire extinguisher
Y20	Tool kit, export
Y35	Tyre inflating hose, 25 m
Y44	Hazard warning triangle
Y45	Warning lamp
Y47	Hand lamp, 10 m cable
Y74	Jack, 25 t
ZA4	CTT vehicle, conversion at Molsheim plant
ZB0	Main contractor, Wörth Plant
ZS1	CTT vehicle, conversion preparations on assy. line
ZS2	CTT vehicle, conversion on assembly line
ZS3	CTT vehicle, conversion, external
ZS4	CTT vehicle, internal control code f. CTT projects
ZX1	Control unit, Common Powertrain Control (CPC)
ZX2	Braking system, EPB II
ZZ3	Vehicle, for right-side traffic
ZZ6	CTT vehicle
ZZ8	Feasibility request, order, special control code
ZZ9	Plausibility control code (internal)
Z01	Country-specific version
Z08	Internal control command, pre-production vehicle
Z57	Vehicle not to be transported on own axles
Z65	CTT vehicle, heavy-duty transport
Z99	Text order

V/AHT492

V/AKK40	Tank filter cap lockable
V/AKYRO	Wheel chock(s) non-foldable DIN 76051, NG 66 Fuel
V/KK81	pre-filter, heated water separator
W/AKKJ6	Upright exhaust muffler, position mid. Cab

W/KMT7	Electr. speed limiter (80 km/h)
W/KMV9	Engine, V8, LA, 450 kW (612 hp), 1800 rpm
W/KRVE	Vehicle preparation for single tyres X/AHM04
X/AKEAM	1-pin main battery switch, NATO
X/KMTE	Engine protective cover extended to bumper 1/AHT492-30
1/AKCGG	Frame behind cab
1/AKFFY	Widening of mirror by 250 mm
1/AK GK8	Turbo clutch
1/AKHKC	Roof-mounted air conditioning system, Waeco CA-0800-DC
1/AK KTA	Main fuel tank behind cab, 900 litres, aluminium
1/AK KYK7754	Main tank painted
1/AK K45	Fuel filter screen in filler neck
1/AK NBN	Hydraulic unit for semitrailer steering
1/AK PBP	Steel wing at 2nd front axle
1/AK ZAX	Conversion acc. to offer number
1/KBVJ	Doubling of trailer connections behind SLT cab incl. spiral hoses
1/KKYK	Main tank painted
1/KLSO	Two floodlights at top rear of cab
1/KMKL	Additional radiator
1/KYCH	Step behind cab and partial frame cover
1/KZST	Conversion "Titan"
2/AKFQE	Refrigerator box EZETIL EZC 35
2/AKSAI	Rear seats, 4 persons, 3-piece, folding 2/A36401-15
2/KZSK	Conversion 'S&G' 3/AHM04-30
3/AKCAK	Bumper, steel version, material thickness 5 mm
3/AKCCH	Chassis preparation for 16.00 R20 tyres
3/AKCRO	Mounting bracket and auxiliary frame for twin cable winch
3/AKCYO	Four shackle for towing lugs
3/AKC69	Attachment brackets for fifth-wheel coupling extended
3/AKECM	12-pin trailer power socket, VG 96 923
3/AKECN	7-pin trailer power socket, VG 95 234
3/AKKIA	Underbody protection and side protection for fuel tank
3/AK KYM7350	Add. tank painted, right
3/AKLH4	Tail lamps, construction, steel-mounted with grille
3/AKOCF	Rear wings, aluminium, walk-on
3/AKQYM	Towing lugs at front and rear (STANAG 4478)
3/AKRAB	Semi-tire pressure regulating device (PTG)
3/AKR BX	Tubeless tyres, "X" front axle
3/AKR CX	Tubeless tyres, "X" rear axle
3/AKR C2	Tapered rim, 10.00 W-20, single tyre w/o inner Tube
3/AKR FU	Steel rim 18.00 x 20,5 on rear axle
3/AKR PD	Tyres 16.00 R 20
3/AKR PE	Tyres 24.00 R 20,5 RA
3/AKR XD	Bead-Lock
3/AKR YC	Paintwork wheels and wheel hubs
3/AKR YC7350	Paintwork wheels and wheel hubs
3/AKR 60	Provisional spare wheel mounting

3/AKR87	Spare wheel/spare wheel rim
3/AKTFV	Weight variant 46,0t (9,0/9,0/14,0/14,0)
3/AKYML	Metallic paint
3/AKZYC	Painting of bright parts 3/A15038K014
3/A16038K025	
3/KCBX	Implement carrier moved back to dimension "X" mm
3/KCCW	Omission stabiliser on rear axle
3/KCRE	Pressure plate for semitrailer ram
3/KCRQ	Frame reinforcement for lifting device
3/KCWM	Chassis adapted on rear axles for heavy application
3/KEC7	Trailer socket 12V, 13-pin
3/KFC8	Rear side window, left and right
3/KGND	Protective grille on oil cooler for transfer case
3/KKHX	Moving of the main tank to the back to measure "X"mm
3/KKYM	Add. tank painted, right
3/KKYP	Fuel supply can be switched over
3/KLBT	Revolving beacons, yellow, tripod, behind cab, left and right
3/KLSG	Stone guard for head lamps
3/KQJN	Jost 5 wheel coupling JSK 38G-1-3,5' h=290 mm 36t
3/KQMA	Mounting plate Jost 40 mm for 5th wheel coup. 36t
3/KQSV	Calculation of 5th wheel lead after weighing

Superstructure: Rotzler double winch system 2x25t with extraction winch