



## 1x **Daimler Demo Unit** MERCEDES-BENZ ZETROS 3643 AS/6X6/4800 with Double-Winch

Mileage	23.490 Km
Mounting	Tractor head
Cab	M-Cab
Engine	Engine, R6, LA, 315 kW (428 HP), 1900/min, Euro 3
Wheel base	4.800 mm, 6x6
Steering	Left hand drive
Suspension	Leaf springs
Gearshift	Manual
Paintwork	7754 steel grey metallic
Tires	402G51 80 x 4 14.00 R 20# TT Cross country "G"
	402G51 80 x 4 14.00 R 20# TT Cross country "G"
	402G51 80 x 4 14.00 R 20# TT Cross country "G"

### Equipment

AL5	Front axle 9.0 t
AM6	Rear axle H7, 16.0 t, crown wheel 300
AR1	Axle ratio i = 5.333 (HL7)
A70	Differential lock, front axle
A71	Differential lock, rear axle
BA1	Voith retarder, performance optimised
BB0	Anti-lock braking system (ABS), disengageable
BB6	Drum brakes on front and rear axle
BB9	Pipe fracture protection for brake system
B02	Anti-lock braking system (ABS)
B22	Parking brake for GCW 44 t to 60 t
B43	Trailer brake, 2-line
B56	Coupling head, front, for topping up air



Mercedes-Benz

B62	Compr. air dryer, heated (twin-chamber system)
CM0	ZF steering gear
CR5	Frame front end, reinforced, for special attachments
C40	Stabiliser, front axle
C95	Deletion, rear underride guard (EC)
EB3	Batteries, 2 x 12V/220 Ah, low-maintenance
EC6	Trailer socket, 15-pin
EC8	Adapter, 15-pin to 2x7-pin socket
ED7	Socket under battery cover, for hand lamp
EM8	PSM, body and trailer CAN, ISO 11992
EU1	CD-radio
E30	Battery master switch, single-pin
E39	Automatic cutouts
E40	Trailer socket, 7-pin
E41	Trailer socket, 12-pin
E84	Battery box, lockable
E99	Terminal caps, batteries
FE5	Power windows for driver's/co-driver's door
FS2	Wide-angle mirror on driver's side, heated
FS3	Exterior mirror, electric, heated, co-driver's side
FS9	Mirror on driver's side, electrically adjustable
FW2	Deletion, immobiliser (transponder)
F05	M-cab
F34	Cab rear wall without window
F53	Uncoated parts, paintable
F63	Kerb mirror, co-driver's side
F89	Entry aid, driver's and co-driver's door
GC2	Transmission G 240-16/11.7-0.69
GS3	Gearshift, hydraulic
GV2	Transfer case VG2400 - 3W, 2-speed
G81	Clutch, reinforced
H03	Air conditioning system
H04	Heat insulation, additional
JK2	Instrument cluster, graphics-capable display
JW5	Telligent maintenance system
J10	Speedometer, km
J58	Warning device for seat belts
J70	Air horn
KH8	Exhaust silencer, tailpipe downwards
KI0	Protective plate under main tank
KL9	Fuel prefilter, additional



Mercedes-Benz

KT6	Main tank+second tank 500 l/500 l, steel
K40	Tank-cap lock
K45	Screen, tank filler neck
K81	Fuel pre-filter, heated water separator
LB2	Provision for fitting marker lights, side
LH6	Protective grille for tail lamps
LV1	Provision for fitting rotating beacons
L06	Daytime running lamp
L12	Headlamps, halogen Equipment
L16	Fog lamps, halogen
L30	Protective grilles, headlamps
L62	Reading light
L72	Electrics, for non-MB body
MA9	Engine mountings, for off-road use
MB1	Exhaust brake, with constantly-open throttle valve
MD4	Speed limiter, 90 km/h, EC
MD9	Cruise control
MG7	Air compressor, 2-cylinder, temperature-optimised
MM9	Engine, 6-cyl. in-line, LA, 315kW (428hp), 1900rpm
MP0	Engine package, for heavy-duty operation
MS3	Engine version, Euro III
M45	Alternator 28 V/100 A
M58	Fan, increased output
M67	Cyclone pre-filter
N55	Transmission oil cooling
P92	Deletion, mudguards for chassis transit
QD1	Front spring, 9.0 t
QF8	Rear spring, 18.0 t, for axle spacing 1450 mm
Q29	Trailer/tow-away coupling, Ringfeder
Q57	Tow-away coupling, rear
Q71	Tow-away lugs, front
RC0	Wide-base wheel, 10.00W-20, with tube
RD6	Two spare-wheel carriers, provisional
RD7	Two spare wheels/spare rims
R04	Wheel nut cap
SG2	Co-driver's standard suspension seat, Isringhausen
SG5	Driver's standard suspension seat, Isringhausen
SL4	Compact bunk, top, folding
S26	Centre seat,static,3-pt. seat belt,head restraint
T58	Weight variant 36.0 t (9.0/16.0/16.0)

XC2	Model plate, Gulf States
XX1	Model generation 1
X38	Model identification, acc. to weight variant
X42	Labels/publications, English
X53	Publications, Arabic, additional
YU4	Wheel chock, folding
Y10	First aid kit
Y16	Fire extinguisher
Y28	2 wheel chocks
Y34	Tyre inflating hose, 10 m
Y44	Hazard warning triangle
Y45	Warning lamp
Y47	Hand lamp, 10 m cable
Y74	Jack, 25 t
ZA4	CTT vehicle, conversion at Molsheim plant
ZB0	Main contractor, Wörth Plant
ZZ6	CTT vehicle
Z64	Customer-specific fittings
ZZ3	Vehicle, for right-side traffic
K/KYA5	Mercedes-Benz protective chassis sealing
W/AKCUX	Offer: Shortening of frame overhang to dimension "X" mm
W/AKCUX770	Offer: Shortening of frame overhang to dimension "X" mm
W/AKJ58	Offer: Warning system for safety belts
W/AKLBT	Offer: Revolving beacons, yellow, tripod, behind cab, left and right
W/AKL28	Offer: Service spotlight behind cab
W/AKMT7	Offer: Electr. speed limiter (80 km/h)
W/AKRVE	Offer: Vehicle preparation for single tyres
W/AKTEP	Offer: Weight variant 37,0t (9,0/14,0/14,0)
W/KCKC	Wheelbase shortened by 300 mm
W/KCPS	Conversion from chassis with platform into truck tractor
1/AKMTC	Offer: Radiator protection
1/KZSF	Conversion "F&B"
2/AKCRO	Offer: Mounting bracket and auxiliary frame for twin cable winch
2/AKCYN	Offer: Two shackle for towing lugs
2/AKC69	Offer: Attachment brackets for fifth-wheel coupling extended
2/AKQJ0	Offer: 5th-wheel coupling, Jost 38-G 1, 3.5inch,H=290mm, manually lubricated
2/AKQM8	Offer: Assembly plate, 40 mm, for 36t 5th-wheel coupling
2/AKQYX	Offer: fifth-wheel lead
W/AKCUX770	Offer: fifth-wheel lead
2/AKRAB	Offer: Semi-tire pressure regulating device > tyre valves <b>NOT</b> mounted.