



Mercedes-Benz



1x MERCEDES-BENZ ZETROS 3643 S/6X4/4500

MERCEDES-BENZ 3643 S/6X4/4500 "ZETROS"

Chassis for platform BM 94916712

Spare wheel not available >

**Vehicle Data**

Identification number	WDB9491671V247893
Milage	851 Km
Mounting	Tractor Head
Cab	M-Cab
Engine	Engine, R6, LA, 315 kW (428 HP), 1900/min, Euro 3
Wheel base	4.500 mm
Steering	Left hand drive
Suspension	Leaf suspension
Gearshift	Manual
Paintwork	7754 steel grey metallic
Tires	402G51 80 x 3, 14.00 R 20# TT Cross country "G"
	402G51 80 x 4, 14.00 R 20# TT Cross country "G"
	402G51 80 x 4, 14.00 R 20# TT Cross country "G"

**Equipment**

AL5	Front axle 9.0 t
AM6	Rear axle H7, 16.0 t, crown wheel 300
AR1	Axle ratio i = 5.333 (HL7)
A70	Differential lock, front axle
A71	Differential lock, rear axle
BB0	Anti-lock braking system (ABS), disengageable
BB6	Drum brakes on front and rear axle
BB9	Pipe fracture protection for brake system
B02	Anti-lock braking system (ABS)
B22	Parking brake for GCW 44 t to 60 t
B43	Trailer brake, 2-line
B65	Compressed air dryer, heated
CM0	ZF steering gear
CR5	Frame front end, reinforced, for special attachments



Mercedes-Benz

C40	C40 Stabiliser, front axle
C95	Deletion, rear underride guard (EC)
EB2	Batteries, 2 x 12 V/165 Ah, low-maintenance
EC6	Trailer socket, 15-pin
EC8	Adapter, 15-pin to 2x7-pin socket
EU1	CD-radio
E30	Battery master switch, single-pin
E39	Automatic cutouts
E84	Battery box, lockable
E99	Terminal caps, batteries
FE5	Power windows for driver's/co-driver's door
FS2	Wide-angle mirror on driver's side, heated
FS3	Exterior mirror, electric,heated, co-driver's side
FS9	Mirror on driver's side, electrically adjustable
FW2	Deletion, immobiliser (transponder)
F05	M-cab
F34	Cab rear wall without window
F63	Kerb mirror, co-driver's side
F89	Entry aid, driver's and co-driver's door
GC2	Transmission G 240-16/11.7-0.69
GS3	Gearshift, hydraulic
GV2	Transfer case VG2400 - 3W, 2-speed
G81	Clutch, reinforced
H03	Air conditioning system
H04	Heat insulation, additional
JK2	Instrument cluster, graphics-capable display
JN0	Tachograph, 1 day + 2 drivers, modular
JW0	Reversing warning device
JW5	Telligent maintenance system
J58	Warning device for seat belts
J70	Air horn
KH8	Exhaust silencer, tailpipe downwards
KI0	Protective plate under main tank
KS2	Main tank, 300 l, steel
K40	Tank-cap lock
K45	Screen, tank filler neck
K81	Fuel pre-filter, heated water separator
LB2	Provision for fitting marker lights, side
LH6	Protective grille for tail lamps
LJ9	Auxiliary main-beam headlamp, additional, on roof
L06	Daytime running lamp



Mercedes-Benz

L12	Headlamps, halogen
L30	Protective grilles, headlamps
L54	Rotating beacon, yellow, left+right, front
L72	Electrics, for non-MB body
MA9	Engine mountings, for off-road use
MB1	Exhaust brake, with constantly-open throttle valve
MD4	Speed limiter, 90 km/h, EC
MD9	Cruise control
MM9	Engine, 6-cyl. in-line, LA, 315kW (428hp), 1900 rpm
MP0	Engine package, for heavy-duty operation
MS3	Engine version, Euro III
MZ7	Air compressor, 1-cylinder, regulated
M45	Alternator 28 V/100 A
M58	Fan, increased output
M67	Cyclone pre-filter
M72	Protective plate under radiator and engine
M78	Engine number, stamped-in
NH2	PTO, layshaft MB 131-2c
N55	Transmission oil cooling
P92	Deletion, mudguards for chassis transit
QD1	Front spring, 9.0 t
QF8	Rear spring, 18.0 t, for axle spacing 1450 mm
Q29	Trailer/tow-away coupling, Ringfeder
Q57	Tow-away coupling, rear
RC0	Wide-base wheel, 10.00W-20, with tube
R04	Wheel nut cap
R60	Spare wheel carrier, provisional
R87	Spare wheel/spare wheel rim
SG0	Co-driver's seat, static, adjustable hat + inclin., ISRI
SG5	Driver's standard suspension seat, Isringhausen
T58	Weight variant 36.0 t (9.0/16.0/16.0)
XC2	Model plate, Gulf States
X38	Model identification, acc. to weight variant
X42	Labels/publications, English
X53	Publications, Arabic, additional
YU4	Wheel chock, folding
Y10	First aid kit
Y28	2 wheel chocks
Y30	Tyre pressure gauge
Y34	Tyre inflating hose, 10 m



Y44 Hazard warning triangle  
Y45 Warning lamp  
Y74 Jack, 25 t  
ZZ3 Vehicle, for right-side traffic  
S/AKQYX Offer: fifth-wheel lead  
S/KQJ0 5th-wheel coupling, Jost 38-G1, 3.5inch,H=290mm, manually lubricated  
S/KQM8 Assembly plate, 40 mm, for 36t 5th-wheel coupling  
W/AKA91 Offer: Front axle, straight  
W/AKCKF Offer: Wheelbase shortened by 600 mm  
W/AKCPS Offer: Conversion from chassis with platform into truck tractor  
W/AKC69 Offer: Attachment brackets for fifth-wheel coupling extended  
W/AKGWE Offer: Suppression boite de transfert  
W/AKKI0 Offer: Protective plate under main tank  
W/AKKS4 Offer: Main tank 400 liters, steel  
W/AKL28 Offer: Service spotlight behind cab  
W/AKZVP Offer: Chassis conversion to 6x4  
W/A16000G208