



Mercedes-Benz

1x Daimler Demo Unit MERCEDES-BENZ 1833 A/4X4/4800 "ZETROS"  
Chassis for platform BM 94901622

## Vehicle Data

Identification number	WDB9490162V224508
Milage	14.698 Km
Mounting	Chassis
Cab	M-Cab
Engine	R6, LA, 240 kW (326 HP), 2200/min, Euro 5
Wheel base	4.800 mm, 4x4
Steering	<b>Right hand drive</b>
Suspension	Leaf springs
Gearshift	Automatic transmission
Paintwork	Silver
Tires	402G57 80 x 3 14.00 R 20# TL Cross country "G" 402G57 80 x 2 14.00 R 20# TL Cross country "G"

## Equipment

- AL5 Front axle 9.0 t
- AM4 Rear axle H7, 13.0 t, crown wheel 233
- AS3 Axle ratio  $i = 7.733$  (HL7)
- A70 Differential lock, front axle
- A71 Differential lock, rear axle
- BB0 Anti-lock braking system (ABS), disengageable
- BB6 Drum brakes on front and rear axle
- BB9 Pipe fracture protection for brake system
- B02 Anti-lock braking system (ABS)
- B22 Parking brake for GCW 44 t to 60 t
- B43 Trailer brake, 2-line
- B56 Coupling head, front, for topping up air
- B62 Compr. air dryer, heated (twin-chamber system)
- CM0 ZF steering gear
- CR4 Mounting parts on frame/hole pattern
- CR5 Frame front end, reinforced, for special attachments
- C40 Stabiliser, front axle
- C42 Stabiliser, rear axle, under frame
- C95 Deletion, rear underride guard (EC)

- D15 Roof hatch, swivel type
- D17 Bogie
- EC6 Trailer socket, 15-pin
- ED7 Socket under battery cover, for hand lamp
- ED9 Provision for fitting electrical devices
- EK9 ADR/GGVS cat. A
- EM8 PSM, body and trailer CAN, ISO 11992
- ET2 Voltage transformer, 24 V/12 V, 15 A
- E22 Battery
- E28 Battery master switch, negative lead
- E31 Power socket
- E39 Automatic cutouts
- E40 Trailer socket, 7-pin
- E41 Trailer socket, 12-pin
- E55 Socket for 24 V maintenance charging
- E84 Battery box, lockable
- E99 Terminal caps, batteries
- FS2 Wide-angle mirror on driver's side, heated
- FS3 Exterior mirror, electric, heated, co-driver's side
- FS9 Mirror on driver's side, electrically adjustable
- FW2 Deletion, immobiliser (transponder)
- F05 M-cab
- F34 Cab rear wall without window
- F49 Windscreen, non-tinted, heated
- F53 Uncoated parts, paintable
- F63 Kerb mirror, co-driver's side
- F89 Entry aid, driver's and co-driver's door
- GC9 Auto. trans. 6/3.49-0.65, retard., Allison 3000SP PR
- GK1 Oil cooler, for transfer case
- GV9 Transfer case VG1700 - 3W 2-speed, Zetros
- G97 Provision for fitting cable winch
- H03 Air conditioning system
- H04 Heat insulation, additional
- H65 Auxiliary hot water heater, Webasto Thermo Top 90
- JK2 Instrument cluster, graphics-capable display
- JW5 Telligent maintenance system
- J10 Speedometer, km
- KH8 Exhaust silencer, tailpipe downwards

- KP2 AdBlue tank, 35 l
- KS2 Main tank, 300 l, steel
- K40 Tank-cap lock
- K45 Screen, tank filler neck
- K81 Fuel pre-filter, heated water separator
- LB2 Provision for fitting marker lights, side
- LH6 Protective grille for tail lamps
- L12 Headlamps, halogen
- L30 Protective grilles, headlamps
- L62 Reading light
- L72 Electrics, for non-MB body
- MB1 Exhaust brake, with constantly-open throttle valve
- MD4 Speed limiter, 90 km/h, EC
- MD9 Cruise control
- MG7 Air compressor, 2-cylinder, temperature-optimised
- MI4 Generator, dirt-proof
- MS5 BlueTec 5 (Euro V)
- MW5 Engine, 6-cyl. in-line, LA, 240kW(326hp), 2200rpm
- M90 Charge air preheater, electric
- NU4 PTO, autom. transm., 8 o'clock, low-speed, pump
- P44 Wing, for chassis transit
- QC4 Front spring, 7.5 t
- Q29 Trailer/tow-away coupling, Ringfeder
- Q60 Hook-type trailer coupling
- Q67 Tow-away lug, rear
- Q71 Tow-away lugs, front
- RC2 Wide-base rims, 10.00W-20, tubeless, single tyres
- RD9 Provision for install. tyre press. control system
- RM8 Tyre make, specially requested, Michelin
- R70 Spare wheel jack, side
- R87 Spare wheel/spare wheel rim
- SA0 Seat covers, man-made leather
- SG2 Co-driver's standard suspension seat, Isringhausen
- SG5 Driver's standard suspension seat, Isringhausen
- S27 Cent.seat, static, 3-pt.s.belt, head restr., fold.rest
- TM0 Weight variant 16.5 t (7.5/9.0)
- XZ7 Two-component paint
- X36 Label, fuse box, English
- X42 Labels/publications, English
- X57 Noise reduction measures, EC 96/20

Y10 First aid kit  
Y28 2 wheel chocks  
Y30 Tyre pressure gauge  
Y35 Tyre inflating hose, 25 m  
Y42 Telescopic jack, 12 t  
Y44 Hazard warning triangle  
Y45 Warning lamp  
ZB0 Main contractor, Wörth Plant  
ZD1 Vehicle with sovereign rights  
ZP1 Low-temperature package  
ZS3 CTT vehicle, conversion, external  
ZZ4 Vehicle, for left-side traffic  
ZZ6 CTT vehicle  
Z64 Customer-specific fittings  
Z81 Load-securing eyes  
Z90 Vehicle capable of fording up to 1.195 mm  
KRAG Pressure control system

### **Body Work**

Torsion free platform without side walls  
Hiab crane mounted behind cab  
Hydraulic Sepson winch with rope outlet front and rear