



1x Daimler **Demo Unit** MERCEDES-BENZ Actros MP3 3651 AK 8x8 Euro 5

MERCEDES-BENZ 3651 AK/8x8/4/4800 "ACTROS"

BM 93233612

Vehicle Data

Identification number	WDB932336-1L-814490
Milage	12.652 km
Mounting	Chassis with platform and tarpaulin
Cab	M-Cab
Engine	V8, LA, 375 kW (510 hp), 1800 rpm, Euro 5 Wheel base 4.800 mm, 8x8/4
Steering	Left hand drive
Suspension	Front spring, 9.0 t, asymmetric Rear spring, 13.0 t, for axle spacing 1450
Gearshift	Telligent automatic gearshift system II
Tires	"G" Y02G56 80 x 3, 395/85 R 20# TL Cross country "G" Y02G56 80 x 3, 395/85 R 20# TL Cross country "G" Y02G56 80 x 3, 395/85 R 20# TL Cross country "G" Y02G56 80 x 3, 395/85 R 20# TL Cross country

Equipment

AL5	Front axle 9.0 t
AM3	Rear axle H7, 13.0 t, crown wheel 300
AR1	Axle ratio i = 5.333 (HL7)
A70	Differential lock, front axle
BB0	Anti-lock braking system (ABS), disengageable
BB1	Telligent braking system with ABS
BB6	Drum brakes on front and rear axle
BB9	Pipe fracture protection for brake system
BE4	Compressed air supply connection, front
B43	Trailer brake, 2-line
CL9	Steering LS 6/LS 8
CR5	Frame front end, reinforced, for special attachments



Mercedes-Benz

C42	Stabiliser, rear axle, under frame
C63	Bumper, steel version
C71	Rear underride guard (EC)
D25	Roof hatch/vent, roof
EB3	Batteries, 2 x 12V/220 Ah, low-maintenance
EC6	Trailer socket, 15-pin
EK6	ADR provision, without chassis shielding
EM8	PSM, body and trailer CAN, ISO 11992
ES8	Additional socket, 24 V/15 A, firewall
E39	Automatic cutouts
FE5	Power windows for driver's/co-driver's door
FE6	Cab steps, movable
FL6	Cab mountings, standard
FM3	Windows, tinted, heated windscreen, sun filter
FN1	Distribution cockpit
FS2	Wide-angle mirror on driver's side, heated
FS5	Sunblind, side window on both sides
FT0	Exterior rear-view mirror, grooved cover
FW2	Deletion, immobiliser (transponder)
FX7	Front mirror, aerodynamic
F05	M-cab
F24	Cab rear wall, straight
F34	Cab rear wall without window
GC2	Transmission G 240-16/11.7-0.69
GE2	Telligent automatic gearshift system II
GK1	Oil cooler, for transfer case
GS7	Telligent gearshift system II
GV2	Transfer case VG2400 - 3W, 2-speed
GZ7	Clutch supplier F&S
HF1	Construction-site filter
H03	Air conditioning system
H04	Heat insulation, additional
H65	Auxiliary hot water heater, Webasto Thermo Top 90
IA9	Wheel arrangement 8x8/4
IF6	Actros series, production location Wörth
IL2	Export code
IZ2	Stock vehicle
JK2	Instrument cluster, graphics-capable display
J10	Speedometer, km
KE7	On-Board Diagnosis 1
KG0	Stainless-steel silencer with SCR cat. conv.



Mercedes-Benz

KJ6	Exhaust silencer, vertical, central, behind cab
KP6	AdBlue tank, 40 l
KS4	Main tank, 400 l, steel
K40	Tank-cap lock
K45	Screen, tank filler neck
L30	Protective grilles, headlamps
L42	Position lamps, top, yellow
L72	Electrics, for non-MB body
MA9	Engine mountings, for off-road use
MD4	Speed limiter, 90 km/h, EC
MD9	Cruise control
ML3	High-speed fan, with belt drive
MP2	Engine cooling power, increased
MS5	BlueTec 5 (Euro V)
MU6	Engine, V8, LA, 375 kW (510 hp), 1800 rpm
MZ3	Viscous coupling, electromagnetic, for fan
MZ8	Air compressor, 2-cylinder, regulated
M00	Omiss. of protect. plate under radiator and engine
M45	Alternator 28 V/100 A
M49	Tandem air cleaner system
M89	Flame system
NH2	PTO, layshaft MB 131-2c
N55	Transmission oil cooling
P44	Wing, for chassis transit
QD3	Front spring, 9.0 t, asymmetric
QF1	Rear spring, 13.0 t, for axle spacing 1450
QS2	Crossmember, f.trail.coupl.G250/centre-axle trailer
Q15	End crossmember, lower, without trailer coupling
Q18	End crossmember, bolted
R04	Wheel nut cap
R60	Spare wheel carrier, provisional
R82	Tapered rims, 10.00-20, single tyres
R83	Tyre pressure control system
R87	Spare wheel/spare wheel rim
SF0	Fold-up seat, co-driver
SG5	Driver's standard suspension seat, Isringhausen
S28	Centre seat, with seat belt
TU5	Weight variant 36.0 t (9.0/9.0/9.0/9.0)
XV6	Actros 3
X38	Model identification, acc. to weight variant



Mercedes-Benz

X42	Labels/publications, English
X57	Noise reduction measures, EC 96/20
YK4	Compressed-air gun, supplied loose
Y10	First aid kit
Y30	Tyre pressure gauge
Y34	Tyre inflating hose, 10 m
Y44	Hazard warning triangle
ZA4	CTT vehicle, conversion at Molsheim plant
ZB0	Main contractor, Wörth Plant
ZS1	CTT vehicle, conversion preparations on assy. line
ZS2	CTT vehicle, conversion on assembly line
ZS4	CTT vehicle, internal control code f. CTT projects
ZZ3	Vehicle, for right-side traffic
ZZ6	CTT vehicle
ZZ8	Feasibility request, order, special control code
Z01	Country-specific version
Z99	Text order
KBFB	front brake connections for towing (yellow)
KB62	Heated air drier (twin-chamber system)
KCLX	Overhang extended to 'X' mm
KCRQ	Frame reinforcement for lifting device
KCVC	Extension of wheelbase by 300 mm
KCYO	Four shackle for towing lugs
KEOB	Battery master isolating switch, single-pole, 1500A (removable handle)
KESP	Power socket type MS 52 131 (AUS)
KGEC	Transmission oil temperature gauge in cab
KJBB	Voltmeter
KKIA	Underbody protection and side protection for fuel tank
KK81	Fuel pre-filter, heated water separator
KLMY	Reading light, gooseneck
KLSH	Stone guard for rear lights
KMTE	Engine protective cover extended to bumper
KPBP	Steel wing at 2nd front axle
KQ29	Trailer or tow-away coupling, manufacturer RINGFEDER
KRGC	5-degree tapered rim 10.00-20V,tubeless,for tyre pressure control system
KRYC	Paintwork wheels and wheel hubs
KSG2	Passenger suspension seat as standard,Isringhausen
KYRO	Wheel chock(s) non-foldable DIN 7605 1, NG 66

Body work

Empl platform

- AKQUB Automatic hook coupling; size: KA3; Type
- AKCQJ Crossmember, reinforced
- AKEC7 Trailer socket 12V, 13-pin
- AKEDJ 12-pin trailer power socket, NATO, STANAG
- AKEDL Electrical connection for vehicle being
- AKQYM Towing lugs at front and rear (STANAG)
- AKRAG Pressure control system
- AKRXD Bead-Lock
- AKZWJ Fording ability 750 mm (STANAG 2805)
- AKZDI Additional work
- KRGC Schrägschulterf. 10.00-20V,schlauchlos,für
- KRYC Lackierung Räder und Naben