



Mercedes-Benz

## Technics

Baumuster	96440112	Plant	0600 (Wörth)
Type	2042 S 4X2 FG13	Production no.	12931449
Type-serie	Actros 5	Object ident	
National type		FIN	
Vehicle group		VIN	
Sub category	23A	Engine no.	
Country of operation	607	Order No. Canter	
5th wheel lead in mm		Order No. Brazil	
Customs special case	00 (Kein Zoll-Sonderfall	FU code	CB (Completely Built Up)
Export licence obligation	No	PU, Sending no.	
Special process code		Delta weight FO +/-	
No check code		Limit CO2 value: total	
ZMA/BBA no.			

## Equipment Code

Pos.	Paint	Description	Add. paint	Description
1	9147	arctic white		

Pos.	Tyres	Description
A1	F18K29 75 x 2	315/80 R 22,5# TL (S+G) Highway cross country "K"
A2	F18L88 75 x 4	315/80 R 22,5# TL Regio (Traction/M+S) "L"

Code	Description	Code	Description
A1C	Front axle 7.5 t	J1K	Tachograph, 1 day + 2 drivers, modular
A1Y	Front axle, straight version	J2E	Radio with USB connector
A2G	Rear axle, crown wheel 300, planetary, 13.4 t	J2I	Standard loudspeaker
A5P	Axle ratio i = 3.714	J6A	Classic Cockpit
B1B	Electronic braking system with ABS and ASR	K0T	Main tank, left
B1H	Electr. compressed air supply and control, centre	K1L	Tank, 430 l, left, 650 x 700 x 1100 mm, aluminium
B2A	Disc brakes on front and rear axle	K5M	Tanks, lockable
B2D	Cover plate for brake discs	K5Q	Fuel screen, tank filler neck
B2X	Parking brake, electronic	K7D	Exhaust system, tailpipe to right and outwards
B4A	Condensation monitoring, for compressed air sys.	L1H	Foglamps, halogen
B4M	Air reservoir, steel	L2L	Rotating beacon, yellow
B5J	Brake and electrical connections, low	L3A	Floodlight, bottom
C0F	Frame overhang 1000 mm	M0A	Engine mounts, reinforced
C1Z	Wheelbase 3900 mm	M0C	Bottom shell to prevent swirling-up of dust
C5B	Step plate above frame, partial cover	M0Z	Noise regulation acc. to UN-R 51.03, phase 1
C5D	Step, behind cab, left	M3J	Eng. OM460, inline 6, 12.8 l, 310kW (421hp), 2100 Nm
C6C	Steering, single-circuit	M5U	Exhaust brake, standard system

C6J	Power steering pump, uncontrolled	M5W	Engine version, Euro III
C6Q	Stabiliser, front axle	M6L	Air compressor, 2-cylinder
C6Y	Stabiliser, under frame, rear axle	M7I	Insect screen in front of cooling system
C7F	Front underride guard (ECE), aluminium	M7V	Cooling output for very hot regions
C7I	Battery carrier cover, lockable	M8B	Air intake behind cab, mounted
C7J	Battery carrier, batteries side by side	M8L	Cyclone filter for coarse dust
C8B	Rear wing, 2550 mm vehicle width	M8Y	Fuel pre-filter, chassis-mounted, additional
C8H	Wing, 3-piece, with EC splash guard	M9V	Deletion, guard plate, bumper
C8I	Splash guard (EC), front	N2E	PTO MB 131-2c, pump
D0L	Smoker package	N6Z	Transmission oil cooling
D0S	Compressed-air connection, in cab	O0A	Coolant service interval, long for non-SWR
D1B	Driver's suspension seat, standard	O1T	Interior colour greige/anthracite
D1N	Fold-up co-driver's seat	O1Y	Steering, direct
D2N	Driver's seat backrest, release mechanism	O2D	Control code, steering oil cooling
D2Y	Seat belt monitor	P0S	Space f.control unit betw. driv.seat & door pocket
D3B	Luxury bed, bottom	P9A	Tip control, in cab
D3X	Seat cover, flat-weave fabric	P9B	Trailer operation switchover
D4Y	Sunblind, side, driver's side	Q0W	Fifth-wheel coupling ex factory
D6F	Air conditioning system	Q1M	Front spring, 7.5 t, 3-leaf
D6Z	Construction-site filter	Q2V	Rear spring, 13.0 t, hard
D7G	Stowage compartment lid, driver and co-driver side	Q4K	Fifth wheel coupling height = 185 mm
D8A	Roof hatch/vent, roof	Q4X	Fifth wheel coupling, manually lubricated
E1B	Batteries 2 x 12 V/170 Ah, low-maintenance	Q5Q	Fifth wheel coupling, standard, Jost JSK 37C
E1M	Alternator, 28 V/150 A	Q6D	Mounting plate, 40 mm, 20 t
E2J	Automatic cutouts	Q6Z	Fifth-wheel coupling with hole pattern
E3E	Additional socket, 12 V/15 A, co-driver footwell	Q8E	Tow-away coupling, rear, Rockinger
E3L	Socket, 24 V/15 A, co-driver footwell	R0Z	Wheel-nut cap
E6A	Trailer socket, 24 V, 15-pin	R1Q	15-degree tapered rims, 9.00 x 22.5
E6Z	Reversing buzzer	S5A	Speed limiter, 90 km/h (56 mph), ECE
F0F	Side module, N3 vehicle	S5Z	Cruise control
F0X	Mirror cover, on-road vehicle	S8B	Fire extinguisher, 2 kg
F1D	L-cab ClassicSpace, 2.30 m, tunnel 170 mm	S8C	Hazard warning triangle
F1R	L-cab	U2I	Control code EBS, 4th generation
F2E	Floor var. tunnel 170mm, for stowage compart. left	U2P	New cooling module, 2nd generation
F2G	Cab width 2.30 m	U3D	Control code, CAN star points, classic
F2N	Cab, 600 mm attachment height	V0S	Vehicle class N3
F2U	ClassicSpace	V0V	Overhang angle, rear, minimum 25 degrees
F3A	Cab mountings, standard, steel-sprung	V0X	Ground clearance under front axle, minimum 250 mm
F3W	Cab tilting mechanism, mechanical-hydraulic	V0Y	Ground clearance under rear axle, minimum 250 mm
F4H	Cab rear wall, without window	V1I	Actros BM964
F4X	Stowage compartment exterior flap, left	V1Z	Grounder
F4Y	Stowage compartment exterior flap, right	V3L	Actros BM964 model generation 5
F5L	Sun visor, exterior, transparent	V8A	Chassis number FIN
F5Y	A-pillar trim	W1E	Weight variant 20.5 t (7.5/13.0)
F6C	Windscreen, tinted	X1J	Instrument/labels/documentation, Arabic
F6Q	Air horn	X2E	Model plate, EU

F7B	Bumper, with steel corners	X3W	Powertrain warranty as per T and Cs 3yrs/450,000km
F7C	Bumper centre section with towing eyes	Y4A	Telescopic jack, 12 t/19 t
F7X	Cab entrance, left/right, rigid	Y4I	1 wheel chock
F8B	2 remote control keys	Y4Y	Tyre inflating hose
F8E	Locking system, with central locking	Y4Z	Compressed-air gun, with hose
G0K	Drive program, economy/power	Y6A	Country-specific version
G0R	Transmission support arms, optimised for removal	Z2H	Try-out vehicle
G2C	Transmission G 230-12/11.7-0.78	Z3Z	Export code
G5A	Single-disc clutch	Z4O	Tank cross-section, narrow
G5G	Mercedes PowerShift 3	Z4R	Tank cross-section, high
H1Z	Fifth-wheel lead +450 mm	Z5L	OM 460
I4A	Wheel arrangement 4x2	Z5M	PTO, single
I5C	20.0-tonner	Z5P	Clutch supplier F&S
I6D	Semitrailer tractor	Z5S	Power take-off, pump, under top edge of frame
I6I	Vehicle production plant Wörth	Z5X	Left-hand drive
I6K	Heavy-duty model series, new generation from 18 t	Z5Y	Vehicle, for right-side traffic
I6M	Heavy-duty vehicles from 18 t, off-road	Z7N	Text order
I6W	Leaf suspension, rear axle	Z8D	Internal control command, sample release
J1A	Instrument cluster, 10.4 cm		