



Mercedes-Benz
Trucks you can trust

1 x Mercedes-Benz Actros 5 BM 964 3348 S 6x4

Model:	Mercedes-Benz Actros 5 BM 964	Engine power:	350 kW (475 PS)
Vehicle type:	3348 S	Wheelbase:	3600 mm
Drivetrain:	6x4	Gross vehicle weight:	33000 kg
Baumuster:	96441612	Steering type:	left
Vehicle type:	Semitrailer tractor	Fifth wheel position:	1000 mm
Driver cabin:	StreamSpace 2,3 - 170		

Equipmentlist

Paint

Cab:	MB 9147 arctic white
------	----------------------

Tyres

1st Axle:	2x 385/55 R 22,5 Goodyear	W68KKA 90 Regio steer
2nd Axle:	4x 315/70 R 22,5 Goodyear	F38LLA 90 Regio drive
3rd Axle:	4x 315/70 R 22,5 Goodyear	F38LLA 90 Regio drive
Spare wheel:	1x 315/70 R 22,5 Goodyear	F38LLA 90 Regio drive

Standard equipment

A1C	Front axle 7.5 t
A2G	Rear axle, crown wheel 300, planetary, 13.4 t
A5Y	Axle ratio i = 4.333 Differential lock, rear axle
B1B	Electronic braking system with ABS and ASR
B1H	Electr. compressed air supply and control, centre
B1Z	ABS, disengageable
B2A	Disc brakes on front and rear axle



Mercedes-Benz

B2X	Parking brake, electronic
B4M	Air reservoir, steel
B5I	Brake and electrical connections, high
	Flashing brake lights during emergency braking
	Parking brake, acoustic warning
	Compressed air supply connection, front
C0A	Frame overhang 750 mm
C5B	Step plate above frame, partial cover
C5D	Step, behind cab, left
C6C	Steering, single-circuit
C6J	Power steering pump, uncontrolled
C6Q	Stabiliser, front axle
C8F	Wing, for chassis transit
CLW	Steering oil cooling
	Hole matrix on frame, continuous
D0S	Compressed-air connection, in cab
D1B	Driver's suspension seat, standard
D1N	Fold-up co-driver's seat
D3X	Seat cover, flat-weave fabric
D6F	Air conditioning system
	Multifunction steering wheel
	Bottle holder
	Power windows, all-round
	Entrance lamps, in door panel
	Document stowage space, A4 size
DUPO	Basetype
E1M	Alternator, 28 V/150 A
E3L	Socket, 24 V/15 A, co-driver footwell
E6A	Trailer socket, 24 V, 15-pin
F0G	Side module, N3G vehicle
F0X	Mirror cover, on-road vehicle
F2G	Cab width 2.30 m
F2N	Cab, 600 mm attachment height
F3A	Cab mountings, standard, steel-sprung
F3W	Cab tilting mechanism, mechanical-hydraulic
F4H	Cab rear wall, without window
F5Y	A-pillar trim
F6C	Windscreen, tinted
F7B	Bumper, with steel corners
F7C	Bumper centre section with towing eyes
F7Y	Cab entrance, left/right, movable
F8E	Locking system, with central locking
F8V	Light sensor
F8W	Rain sensor
	Cab, reinforced
	Air deflectors, corner panels
	Kerb mirror
G0K	Drive program, economy/power
G0R	Transmission support arms, optimised for removal



Mercedes-Benz

G2F	Transmission G 330-12/11.63-0.77
G5G	Mercedes PowerShift 3
J1A	Instrument cluster, 10.4 cm
J2I	Standard loudspeaker
J6A	Classic Cockpit
	On-Board Diagnosis
	Travel computer
	Maintenance system
K0T	Main tank, left
K7D	Exhaust system, tailpipe to right and outwards
	Side marker lights
	Ambient lighting
	LED end-outline marker lamp
M0A	Engine mounts, reinforced
M0C	Bottom shell to prevent swirling-up of dust
M0Z	Noise regulation acc. to UN-R 51.03, phase 1
M3L	Eng. OM460, inline 6, 12.8 l, 350kW (476hp), 2300 Nm
M5U	Exhaust brake, standard system
M5W	Engine version, Euro III
M6L	Air compressor, 2-cylinder
M7I	Insect screen in front of cooling system
M7J	Guard plate, bumper
M7U	Cooling output for hot regions
M8B	Air intake behind cab, mounted
N6Z	Transmission oil cooling
Q6W	Fifth wheel angle, extended, h = 50 mm
	End cross member, neutral position
R1Q	15-degree tapered rims, 9.00 x 22.5
S5Z	Cruise control
V0T	Vehicle class N3G, off-road vehicle
V0V	Overhang angle, rear, minimum 25 degrees
V0W	Breakover angle, minimum 25 degrees
V0X	Ground clearance under front axle, minimum 250 mm
V0Y	Ground clearance under rear axle, minimum 250 mm
V0Z	Ground clearance between axles, minimum 300 mm
V1I	Actros BM964
V1Z	Grounder
V3L	Actros BM964 model generation 5
V8A	Chassis number FIN
W5W	Weight variant 33.0 t (7.5/13.0/13.0)
X2I	Model plate, export
X3Z	Powertrain warranty as per T and Cs 3yrs/250,000km
Y4Z	Compressed-air gun, with hose
Y6A	Country-specific version
Z4O	Tank cross-section, narrow
Z4Q	Tank cross-section, low
Z5L	OM 460
Z5X	Left-hand drive
Z5Y	Vehicle, for right-side traffic

Selected equipment

A1X	<i>Straight front axle, increased ground clearance</i>
B4A	Condensation monitoring, for compressed air sys.
C1R	Wheelbase 3600 mm
C5P	Bolted frame
C7I	Battery carrier cover, lockable
C7J	Battery carrier, batteries side by side
D2N	Driver's seat backrest, release mechanism
D3A	Luxury bed, top, wide, with levelling control
D3B	Luxury bed, bottom
D6Z	Construction-site filter
D8N	Tilting sunroof, electric
E1C	Batteries 2 x 12 V/220 Ah, low-maintenance
E2J	Automatic cutouts
E3B	Connection point 12V/15A, for auxiliary consumers
E5A	No. 1 switch, for non-MB body electrics
E6Y	Reverse warning, comb. with hazard warning lights
F1E	L-cab StreamSpace, 2.30 m, tunnel 170 mm
F1R	L-cab
F2E	Floor var. tunnel 170mm, for stowage compart. left
F2W	StreamSpace
F3E	Cab mountings, rear, reinforced
F4X	Stowage compartment exterior flap, left
F4Y	Stowage compartment exterior flap, right
F5L	Sun visor, exterior, transparent
F6I	Front mirror, heated
F6Q	Air horn
F8G	2 mechanical vehicle keys, additional
F9Y	Vehicle key, without transponder
G5B	Double-disc clutch
H2K	Fifth-wheel lead +1000 mm
J1Y	Speedometer, km/h and mph
J1Z	Speedometer, deletion, tachograph
J5S	Radio, with USB connection and Bluetooth
K0W	Second tank, right
K1C	Tank, 290 l, left, 650 x 565 x 950 mm, aluminium
K5M	Tanks, lockable
K5Q	Fuel screen, tank filler neck
K6C	Second tank, 290 l, right, 650 x 565 x 950 mm, aluminium
L2U	1 LED beacon, visibility possibly less than 360°
L3A	Floodlight, bottom
L4Z	Protective grille, metal, for headlamps
M8L	Cyclone filter for coarse dust
Q0W	Fifth-wheel coupling ex factory
Q1L	Front spring, 7.5 t, 4-leaf
Q3D	Rear spring, 2 x 16.0 t



Q4L	Fifth wheel coupling height = 190 mm
Q4X	Fifth wheel coupling, manually lubricated
Q6E	Mounting plate, 40 mm, 36 t
Q6Q	Fifth-wheel coupl., heavy-duty, 3.5", Jost JSK 38C
Q6Y	Semi-tr. bracket w. hole pattern, extended, reinf.
R0Z	Wheel-nut cap
R1T	15-degree tapered rims, 11.75 x 22.5, front axle
R8F	Spare wheel carrier, provisional
R8P	Spare wheel/spare wheel rim
S5E	Speed limiter, 80 km/h
S8A	First aid kit
S8C	Hazard warning triangle
X1A	Instrument/labels/documentation, English
X4L	Literature in French, additional
Y4A	Telescopic jack, 12 t/19 t
Y4I	1 wheel chock
Y4Y	Tyre inflating hose
JMVA	Fuel pre-filter, chassis-mounted, add., unheated