

Mercedes-Benz Arocs 4 2033 A

Vehicle description:

Model:	Mercedes-Benz Arocs 4
Vehicle type:	2033 A
Drivetrain:	4x4
Baumuster:	96400812
Subcategory:	26a
Chassis variant:	All-wheel chassis
Cab:	M-Cab
Engine power:	240kW (326 HP)
Wheelbase:	4.500 mm
Gross vehicle weight:	- kg
Steering type:	Left

Paint:

LZ 1: Cab/null	MB 9147	arctic white
----------------	---------	--------------

Tyres:

1st Axle:	2 x 14.00 R 20 Michelin	402G51 80 Cross country
2nd Axle:	2 x 14.00 R 20 Michelin	402G51 80 Cross country
Spare wheel:	1 x 14.00 R 20 Michelin	402G51 80 Cross country

Vehicle equipment:

Standard equipment:

A1Y	Front axle, straight version
A2G	Rear axle, crown wheel 300, planetary, 13.4 t Differential lock, rear axle
B1D	Electronic air-processing unit, medium
B1Z	ABS, disengageable
B2B	Drum brakes on front and rear axle
B4M	Air reservoir, steel Flashing brake lights during emergency braking Parking brake, acoustic warning Compressed air supply connection, front

Mercedes-Benz Arocs 4 2033 A

C6C	Steering, single-circuit
C6J	Powersteering pump, uncontrolled
C6Q	Stabiliser, front axle
C6Y	Stabiliser, under frame, rear axle
C7J	Battery carrier, batteries side by side
C8F	Wing, for chassis transit
CLW	Steering oil cooling Hole matrix on frame, continuous
D0S	Compressed-air connection, in cab
D1B	Driver's suspension seat, standard
D1N	Fold-up co-driver's seat
D3X	Seat cover, flat-weave fabric
D6Z	Construction-site filter
D8A	Roof hatch/vent, roof Multifunction steering wheel Bottle holder Power windows, all-round Entrance lamps, in door panel Document stowage space, A4 size
DUPO	Basetype
E1N	Alternator 28 V / 100 A
E3L	Socket, 24 V / 15 A, co-driver footwell
F0G	Side module, N3G vehicle
F0Y	Mirror cover, construction vehicle
F2C	Floor variant, tunnel 320 mm
F2G	Cab width 2.30 m
F2N	Cab, 600 mm attachment height
F2U	ClassicSpace
F3A	Cab mountings, standard, steel-sprung
F3W	Cab tilting mechanism, mechanical-hydraulic
F4H	Cab rear wall, without window
F5Y	A-pillar trim
F6C	Windscreen, tinted
F7B	Bumper, with steel corners
F7D	Bumper centre section w. towing eyes, coupling jaw
F7Y	Cab entrance, left/right, movable
F8A	2 vehicle keys
F8E	Locking system, with central locking Cab, reinforced Air deflectors, corner panels Kerb mirror
G0R	Transmission support arms, optimised for removal
G0W	Drive program offroad
G2C	Transmission G 230-12/ 11.7-0.78
G5A	Single-disc clutch
G5G	Mercedes PowerShift 3
J1A	Instrument cluster, 10.4 cm

Mercedes-Benz Arocs 4 2033 A

J1K	Tachograph, 1 day + 2 drivers, modular On-Board Diagnosis Travel computer Display, trailer data, in instrument panel FleetBoard Eco Support Maintenance system
K0T	Main tank, left
K3V	AdBlue tank, 60 l, left
K7P	Exhaust system, bracket two-piece Side marker lights Ambient lighting LED end-outline marker lamp
M0C	Bottom shell to prevent swirling-up of dust
M2N	Eng. OM470, inline 6, 10.7 l, 240kW (326hp), 1700 Nm
M5A	2. Engine generation OM470
M5U	Exhaust brake, standard system
M6L	Air compressor, 2-cylinder
M7I	Insect screen in front of cooling system
M7J	Guard plate, bumper
M7V	Cooling output for very hot regions
M8B	Air intake behind cab, mounted
N6Z	Transmission oil cooling
Q2V	Rear spring, 13.0 t, hard
Q8M	End crossmember lower, reinforced End cross member, neutral position
S5Z	Cruise control
V0T	Vehicle class N3G, off-road vehicle
V1B	Arocs
V1Z	Grounder
V2I	Arocs model generation 1
V8A	Chassis number FIN
X2I	Model plate, export
X3Z	Powertrain warranty as per T and Cs 3yrs/250,000km
Y4Z	Compressed-air gun, with hose
Y6A	Country-specific version
Z4O	Tank cross-section, narrow
Z4Q	Tank cross-section, low
Z5D	OM 470
Z5X	Left-hand drive
Z5Y	Vehicle, for right-side traffic

Mercedes-Benz Arocs 4 2033 A

Special equipment:

A1E	Front axle 9 .0 t
A1W	Differential lock, front axle
A6C	Axle ratio i = 4.833
B1A	Electronic braking system with ABS
B1F	Heating, electronic air-processing unit
B4A	Condensation monitoring, for compressed air sys.
C2N	Wheelbase 4.500 mm
C4C	Frame overhang 2100 mm
C5P	Bolted frame
C6L	Power-assisted steering, reinforced, / from 9 t
C7I	Battery carrier cover, lockable
C9S	Deletion mounting parts, on frame
C9Y	Deletion, rear underride guard (ECE)
D0L	Smoker package
D0U	Smoke detector, in cab
D2N	Driver's seat backrest, release mechanism
D2Y	Seat belt monitor
D3I	Bunk, bottom
D6F	Air conditioning system
D6I	Residual engine heat utilisation
D6N	Hot-water auxiliary heater, cab and engine
D7A	Heat insulation, additional
D7G	Stowage compartment lid, driver and co-driver side
E1C	Batteries 2 x 12 V /220 Ah, low-maintenance
E2J	Automatic cutouts
E3E	Additional socket, 12 V / 15 A, co-driver footwell
E3Y	PSM, body and trailer CAN, ISO 11992
E3Z	PSM, body CAN, ISO 11898 instead of 11992
E5G	Battery disconnect switch outside, on frame
E6Z	Reversing buzzer
E9E	Provision, ADR, without chassis shielding
F1O	M-cab ClassicSpace, 2.30 m, tunnel 320 mm
F1Q	M-cab
F3E	Cab mountings, rear, reinforced
F3Z	Hydraulic tilting mechanism oil, below -25 degrees
F4X	Stowage compartment exterior flap, left
F5L	Sun visor, exterior, transparent
F6I	Front mirror, heated
F6R	Air horns, cab roof
G4D	Transfer case VG 2800-3W / 1.45· 1.04, permanent
J2E	Radio with USB connector
J2I	Standard loudspeaker
K1C	Tank, 290 l, left, 650 x 565 x 950 mm, aluminium
K5M	Tanks, lockable
K5Q	Fuel screen, tank filler neck

Mercedes-Benz Arocs 4 2033 A

K5S	Protective cap for AdBlue metering system
K7A	Exhaust system, tailpipe vertical
K7F	Exhaust system, offset, for large tyres
L0Y	Tail lamps wiring harness, extended
L1H	Fog lamps, halogen
L4Z	Protective grille, metal, for headlamps
M0U	Noise encapsulation, special package
M5C	Engine version Euro VI, D
M8L	Cyclone filter for coarse dust
M8Y	Fuel pre-filter, chassis-mounted, additional
M9A	Pre-installation, pre-heating, engine coolant
Q1Y	Front spring, 9.0 t, 4-leaf
Q8E	Tow-away coupling, rear, Rockinger
R0V	Vehicle adaptation, large tyres
R4Z	Wide-base rims, 10.00W-20, tube, single tyres
R8F	Spare wheel carrier, provisional
R8P	Spare wheel/spare wheel rim
S5C	Speed limiter, 85 km/h
S8A	First aid kit
S8B	Fire extinguisher, 2 kg
S8C	Hazard warning triangle
S8D	Warning lamp
S8E	Reflective safety jacket
W9S	Weight variant 18.0 t (9.0/9.0)
X1K	Instrument / labels / documentation, Russian
Y4A	Telescopic jack, 12 t / 19 t
Y4J	2 wheel checks
Y4P	Tyre pressure gauge, digital
Y4S	Spare bulbs, in box
Y4W	Tool kit, extended
Y4Y	Tyre inflating hose
Z9K	Cold Climate Pack Classic

Mercedes-Benz Arocs 4 2033 A

Equipment overview:

Standard equipment:

A1Y; A2G; B 10; B1Z; B2B; B4M; C6C; C6J; C6O; C6Y; C7J; C8F; CLW; D0S; D1B; D1N; D3X; D6Z; D8A; DUPO; E1N; E3L; F0G; F0Y; F2C; FZG; F2N; F2U; F3A; F3W; F4H; F5Y; F6C; F7B; F7D; F7Y; F8A; F8E; G0R; G0W; G2C; GSA; GSG; J1A; J1K; K0T; K3V; K7P; M0C; M2N; M5A; M5U; M6I; M7I; M7J; M7V; M8B; N6Z; Q2V; Q8M; S5Z; V0T; V1B; V1Z; V2I; V8A; X21; X3Z; Y4Z; Y6A; Z4O; Z4Q; Z5D; Z5X; Z5Y;

Special equipment:

A1E; A1W; A6C; B1A; B1F; B4A; C2N; C4C; C5P; C6L; C71; C9S; C9Y; D0L; D0U; D2N; D2Y; D3I; D6F; D6I; D6N; D7A; D7G; E1C; E2J; E3E; E3Y; E3Z; E5G; E6Z; E9E; F1O; F1Q; F3E; F3Z; F4X; F5L; F6I; F6R; G4D; J2E; J2I; K1C; K5M; K5Q; K5S; K7A; K7F; L0Y; L1H; L4Z; M0U; M5C; M8L; MSY; M9A; QIY; Q8E; R0V; R4Z; R8F; R8P; S5C; S8A; S8B; S5C; S8D; S8E; W9S; X1K; Y4A; Y4J; Y4P; Y4S; Y4W; Y4Y; Z9K;

Additional equipment: