





Truck-mounted concrete pump

SY38 Z5-200



Note: Standard version. Dimensions and weights depend on truck, pump model and equipment. For illustration only.

Technical data		
Boom	Folding system	5-arm Z
	Vertical reach	38.0 m
	Horizontal reach	34.0 m
	Reach depth	21.5 m
	Unfolding height	11.3 m
	End hose length	3 m
Support	Outrigger spread front	6.2 m
	Outrigger spread rear	7.1 m
Dimensions	Overall length	11.7 m
	Width	2.5 m
	Height	3.9 m
Core pump	Output	160 m³/h
	Pressure	85 bar
	Strokes/min	26
	Delivery cylinder Ø	260 mm
	Stroke length	1900 mm



Standard Equipment SY38 Z5-200		
Chassis	Transfer Gear Box	
	Towing eye	
Cleaning	Water tank 600 I	
	Water pump 150 I/min 20 bar	
Delivery line	2-layer delivery line – DN 125, 5.5"	
	End hose 3 m DN 125, 5.5"	
Hopper	Concrete hopper with agitator	
	Central lubrication hopper, hydraulically	
	Hard metal wear parts kit	
	Switchover cylinder diameter = 100 mm	
	Agitator safety switch off, lever switch	
Lighting	Working light for illuminating hopper	
	Side marker lamps	
Pump	Core pump with 1900 mm stroke	
	Delivery cylinder with 260 mm diameter	
	Core pump with 160 m³/h delivery rate	
	Delivery cylinder chrome-plated	
	Delivery piston standard	
Control System	SANY SYLD user interface display	
	SANY SYMC control system	
	Radio remote control propotional	
	2nd radio remote control incl. 40 m cable	

Support	Boom pedestal (X-type outrigger and swing out legs)	
	OSS one side support (assistance device)	
	Support plates (4x) in magazine (2x) open	
	Swivel support plates	
Safety	Chassis horn via remote control on hopper	
	Handrail on rearsteps	
	Horn at the boom, button on rear controlbox	
	Warning device boom not in cradle	
Addi- tional features	User manual and spare part list	
	Stowage Box	
	Painting: Pedestal, hopper, arm assembly and delivery line in RAL 6016 Traffic white	
	Road approval KIT (markers & underrun protection)	
	Platform aluminum	
	Rear steps, left & right side	
	Plastic hopper cover, foldable	