

## MAN TGM 18.240 4X2 BB

Code	Designation
000AA	Non-variable parts
001AC	steering arrangement, right
005BJ	Wheelbase 3575 mm
006EV	rear frame overhang 1125 mm
018MK	D0836LFL40 engine - 240 hp/176 kW EURO 3 - 925 Nm Common Rail
02AAB	instrument panel kmh 'Base-Line'
022SF	gearbox ZF 12 AS 1210 OD MAN TipMatic
023FT	fuel tank 150l right
025MU	front axle VOK-07 dropped
026EA	front springs parabolic 7.1 t
027AC	radiator and intercooler
028EB	rear springs parabolic, 11.5 t
03KAA	fuel tank fitted
030AC	hydraulic steering
030EE	steering wheel with height and inclination adjustment
032AB	MAN BrakeMatic (electronic brake system)
034NH	hypoid rear axle HY-1133
035FE	Hypoid axle ratio $i = 5.29$
037AC	with differential lock in rear axle
038GC	disc wheels 10 hole 8.25-22.5 on 1stFA TL
038PC	disc wheels 10-hole 8.25-22.5 on 1stRA TL
038TC	disc wheel 10-hole 8.25-22.5 as spare wheel TL
042XY	without electronic tachograph
050NK	C cab 2240mm wide, 1620mm long
052XA	without stowage boxes
058BA	seat coverings in standard quality
058NH	driver's seat, high-comfort, with air suspension
059HC	Static co-driver's seat with storagebox
064AC	two additional vehicle keys
080AE	door interior panelling washable
116AE	visco fan
118MA	EDC engine regulation
121EH	neutral pos. switch
123CC	strainer for fuel tank
123CE	chain for tank cap
124AL	fuel filter
124AR	additional fuel filter heated with water trap, make SEPAR
124EA	fuel filter heating
142AF	calibrate tachograph
153KC	air conditioning system AC R134A with automatic temperature control without CFHC
172EP	red-and-white warning stripes on doors and air deflectors
201HL	Air-intake half-height behind cab. With dry air filter/pre-separator
205AP	1-cyl. compressor 238 cc
206AR	exhaust upswept left
206TA	elbow for upswept or raised exhaust
208AB	engine brake with additional actuation via brake pedal

208XD	without exhaust valve brake (EVB)
210AA	flame starting system
211AD	clutch with 395 mm diameter
219AF	steering oil reservoir with dipstick
230AC	with underride guard at rear
230ER	front underride guard
230YX	without lateral underride guard
232HC	synthetic bumper
236CS	rear cross member for trailer coupling 160X100
241AE	body mounting brackets on frame
245XX	without spare wheel holder
256AA	steering wheel lock
258HA	anti-lock braking system (ABS)
259CA	disc brake for front axle
259CB	disc brake for rear axle
262XX	without brake connection on frame end
278AE	Air filler connection at front
283FR	Cab mounts on coil springs for 'C' cab
303AX	Lockable tank fastener - 1 u. ventilated for master key system
309AA	Beam throw regulator
310EE	Halogen twin headlights H7 for right-hand traffic
318AA	marker lamps
318AK	lateral marker lights
319YX	without reading light
321EC	central locking
324AA	Single-tone horn, electric
325AA	MAN Tronic (on-board computer)
326FZ	Socket in cab 12V 2-pole and 24V 2-pole
326XY	Without 12/24 V socket on end of frame
327AF	battery main switch, mechanical
329CT	Two 12-V 175-Ah batteries
329ED	Battery box lockable (without lock)
329HC	Maintenance sign for batteries - 'maintenance-free'
33VAC	engine capsule
331CY	28V three-phase alternator 120A 3360W Longlife Eco
339FP	Display on the dashboard for operating data
343AZ	Warning buzzer in seven-chamber light when reverse gear engaged
345AU	Maximum electronic speed limitation 89 km/h
345EA	cruise control
348AA	Coolant level indicator in cab
350LK	CB radio antenna on cab roof
350NK	Radio MAN CD 24V
351AF	preparation for radiotelephone
352CF	2 halogen revolving beacons on cab roof left and right
352WS	Revolving beacon, yellow
362AA	Stabiliser for rear axle
363AA	Stabiliser for front axle
370CR	air dryer, heated
373AE	antifreeze effective down to -35 degrees
376XH	Without Mattress for lower bunk

376XK	Without Mattress for upper bunk
376XL	No bunks for 'M' , 'C' , 'DK' cabs
380AC	windscreen of laminated glass tinted
380CA	door windows tinted
381AA	cab rear wall without windows
381XC	Without curtain before bunks
381YA	Without all-roand curtain for C/M cab
384CD	Safety belt display, driver's side
386AS	Mechanical sliding roof
387AF	Electric door window lifters for driver and co-driver
388AB	Folding sunshade for driver and co-driver
389AC	handles left and right (on B-post)
389AD	handles left and right (on A-post)
390AX	storage compartment above windscreen
390XB	without pigeon hole on rear wall
390XX	without oddment box
392AK	rear-view mirror(s) heatable and electrically adjustable
392AR	kerb mirror, right, heated and electrically adjustable
392AS	Wide-angle mirror, right, heatable and electrically adjustable
392AW	kerb mirror, left, heatable and electrically adjustable
392AX	wide-angle mirror, left, heated and electrically adjustable
392CL	EU front mirror on co-driver's side
392HA	Mirror brackets for body width 2500-2600 mm width 2500 mm
394FM	1 Fire extinguisher, 2 kg, multilingual (English/German/Dutch)
396CC	windscreen washer electric
400AH	mudflap front
401AF	temporary transport mudguards
401CW	deletion of plastic mudguards
404AP	spray reducer
405AC	Bonding set, separate
405AK	hazard-warning sign
405AR	hazard-warning lamp
405CP	20 m tyre inflator hose with pressure gauge
407AN	Jack, 10 t
411AG	chock with bracket, loose
434ES	dashboard in standard version
524IB	Load variant 16000 kg
538AE	plastic floor and engine tunnel covering
542DM	Supplier declaration
542FC	anti-noise package 80 dB (92/97EEC)
542IZ	confirmation for international registration
542NC	Registration as N3 vehicle, (GVW > 12t)
600AC	Fittings for right-hand traffic
LQW01	chassis in water-based paint
LVS01	chassis graphite black RAL 9011 matt
LVS02	wheels White aluminium acrylic RAL 9006
LVS03	cab DEEP ORANGE 2011
80001	2 wahlweise 295/80R22,5 LENK-S+G TL
90001	4 wahlweise 295/80R22,5 ANTR-S+G TL
90004	1 wahlweise 295/80R22,5 LENK-S+G TL

Weights:
Gross weight: 16000
1st front axle: 7100
2nd front axle: 0
3rd front axle: 0
Leading axle: 0
1st rear axle: 11500
2nd rear axle: 0
Trailing axle: 0