

## MAN TGS 33.440 6X4 BBS-WW

Code	Designation
001AA	steering arrangement, left
005NK	Wheelbase 3600+1400 mm
006BO	rear frame overhang 700 mm
018KS	Engine D2676LF04 - 440 HP / 324 KW EURO2 - 2,100 Nm common rail
02AAG	Instrument panel km/h 'High-Line in colour'
022WO	Gearbox ZF 16 S 253 OD
023P8	Fuel tank aluminium 590l right
025MK	front axle VO-09 straight
026EF	front springs parabolic 9,5 t
027AX	extended radiator and intercooler over 35 degrees ambient temperature
028FP	rear springs parabolic 16 t
028PA	Fit tandem axles
029GC	Propshafts for high load profile
03KAA	fuel tank fitted
030EE	steering wheel with height and inclination adjustment
032AB	MAN BrakeMatic (electronic brake system)
034EC	brake shoe width for rear axle 220 mm
034MH	hub-reduction rear axle HPD-1382/ HP-1352
035KK	Planetary axle ratio $i = 3.63$
037AC	with differential lock in rear axle
038GG	disc wheels 10 hole 9.00-22.5 on 1stFA TL
038PG	disc wheels 10-hole 9.00-22.5 on 1stRA TL
038RG	disc wheels 10-hole 9.00-22.5 on 2ndRA TL
038TG	disc wheel 10-hole 9.00-22.5 as spare wheel TL
04WAH	Two electrical spiral cables 24-V 7-pin to 7-pin to semitrailer
042CY	EC tachograph electronic, automatic, 2 drivers
05NAE	front panel unlockable from inside
050NF	L cab 2240mm wide, 2280mm long
052AC	Storage box accessible from inside and outside - flap unlocked from inside
058BA	seat coverings in standard quality
058NH	driver's seat, high-comfort, with air suspension
059NA	co-driver's seat static, with longitudinal + seat back adjustment
080AE	door interior panelling washable
116AP	Visco fan with high cooling output
116AZ	Fan control for use in hot countries
118AC	air deflector to stop dust swirling
118EK	Short mounting base (engine only)

118MA	EDC engine regulation
119EH	General PTO parameterisation
119KA	Idle shutdown
119KK	Coolant engine-protection function
119NB	Emergency brake signal (ESS)
123CC	strainer for fuel tank
124AL	fuel filter
124AZ	Auxiliary fuel filter with water separator
150WR	Brushed aluminium insert on instrument panel
153KA	air conditioning system AC R134A without CFHC
159XS	without cab insulation NORDIC (against cold) for M, L and LX cab
194AC	operator's manual in French
201AR	air intake upswept with dry air filter / precleaner
201EM	Air filter cartridge with safety insert for heavy-duty deployment
201FA	fine dust and pollen filter
203EK	connection for external engine speedcontrol (ZDR)
205AN	air compressor 1-cylinder, 360 ccm
206ET	exhaust on lh side with tail pipe towards rear
208AK	exhaust valve brake
210XX	Without flame-start/jump-start system
211FQ	Single-disc clutch DTE 430, reinforced
227AC	rear axle breather upswept
230XW	Without front underride guard
233EM	3-part steel bumper
234AX	towing coupling ROCKINGER SK5
236AF	cross member for trailer coupling
245AE	spare-wheel holder on left side
256AA	steering wheel lock
258AC	antijackknife brake
258HA	anti-lock braking system (ABS)
259CC	drum brake for front axle
259CE	drum brake for rear axle
262AZ	2-line brake connection behind cab
272FA	Entry lighting for driver and co-driver
276AC	Armrests for driver's seat
280BA	Equipment for hazardous goods to ADR, type AT
280EU	stoneguard grille in front of radiator
280FB	Working platform with step and grab handle
281AB	medium-height design
283FG	Air sprung cab mounts for 'L,LX,XL,XLX,XXL'
303AX	Lockable tank fastener - 1 u. ventilated for master key system
308CB	Electrical preparation for retrofitting a PTO
308ER	brake lining wear display for front axle drum brake and rear axle drum brake
310EE	Halogen twin headlights H7 for right-hand traffic

310FA	2 spotlights on cab roof
311AA	protective grille for headlights headlights
318AA	marker lamps
318AK	lateral marker lights
319AR	reading lamp for driver
321EC	central locking
324AC	Two-tone horn,electric
325AA	MAN Tronic (on-board computer)
325EE	Language 1 'French' for display in instrument panel
325FC	Language 2 'English' for display in instrument panel
326CR	trailer socket for ABS behind cab
326ET	trailer socket, 24 V, 7+7-pole, behind cab
327AF	battery main switch, mechanical
329CS	Two 12-V 155-Ah batteries
329ER	Battery box up to 175 Ah
329HC	Maintenance sign for batteries - 'maintenance-free'
331AB	Basic alternator
339FP	Display on the dashboard for operating data
343AN	Acoustic warning system at end of frame for engaged reverse gear
345CV	Maximum electronic speed limitation 85 km/h
345EA	cruise control
346CA	charging pressure indicator
350NN	MAN Media Truck radio, 12 V with five-inch colour display
350XO	Without navigation SD
352FD	Preparation for installation of flashing beacons
358AA	ETA electric cutout
362AH	Stabiliser on both rear axles
363AA	Stabiliser for front axle
370CM	air dryer
373AE	antifreeze effective down to -35 degrees
376FA	1 bunk with storage space (with aluminium frame).
376HA	Mattress for lower bunk
376KA	Bunk cover for bottom bunk
376XK	Without Mattress for upper bunk
380AC	windscreen of laminated glass tinted
380CA	door windows tinted
381AA	cab rear wall without windows
381CE	All-roand curtain
381CM	diagonal curtain
384CD	Safety belt display, driver's side
385AT	Side windows tinted behind B-post
386AS	Mechanical sliding roof
387AF	Electric door window lifters for driver and co-driver
388AH	Roller blind for windscreen, mechanical

388AK	sun shade in front of windscreen
389AC	handles left and right (on B-post)
389AD	handles left and right (on A-post)
390CT	cup holder in dashboard
390XB	without pigeon hole on rear wall
390XX	without oddment box
392AH	kerb mirror, right
392CZ	Electrically heated and adjustable rear view mirror, heated wide-angle mirror
392HA	Mirror brackets for body width 2500-2600 mm width 2500 mm
392XJ	Without front mirror on co-driver's side/at centre
400AH	mudflap front
401EZ	Plastic mudguard three-part with flap (without spray reduction)
404AP	spray reducer
405AC	Bonding set, separate
405AK	hazard-warning sign
405AR	hazard-warning lamp
407AH	jack 12 t
411AA	1 chock
417AC	wheel bolt covers front
434CH	Smoking package
434DA	Interior design in Sand
491LE	fifth-wheel coupling JOST JSK 38 C-1 3.5", height 190 mm, without connection for central lubrication
493MP	Kingpin to rear axle centre 1075 mm
493YT	JOST fifth-wheel base plate 40 mm (fifth-wheel loads up to 36t)
523AE	signs in French
523AM	signs additionally in Arabic
538AE	plastic floor and engine tunnel covering
542BT	ADR inspection and certificate
542DM	Supplier declaration
542FC	anti-noise package 80 dB (92/97EEC)
542NC	Registration as N3 vehicle, (GVW > 12t)
600AC	Fittings for right-hand traffic
798LF	Height over cab, unloaded up to 4000mm
798WK	vehicle can be registered only as off-road vehicle to directive 70/156/EEC; note body
LQW01	chassis in water-based paint
LVS01	chassis graphite black RAL 9011 matt
LVS02	wheels White aluminium acrylic RAL 9006
LVS03	cab Pure white RAL 9010
80001	2 wahlweise 315/80R22,5 LENK-NAH TL
90001	4 wahlweise 315/80R22,5 ANTR-NAH TL
90002	4 wahlweise 315/80R22,5 ANTR-NAH TL
90004	1 wahlweise 315/80R22,5 LENK-NAH TL

**Weights:**

Gross weight: 33000

1st front axle: 7500

2nd front axle: 0

3rd front axle: 0

Leading axle: 0

1st rear axle: 13000

2nd rear axle: 13000

Trailing axle: 0