

MAN TGS 41.400 8X4 BB-WW TipMatic



Weights:

Gross weight:	44000
1st front axle:	9000
2nd front axle:	9000
3rd front axle:	0
Leading axle:	0
1st rear axle:	13000
2nd rear axle:	13000
Trailing axle:	0

Technical extent of delivery

Code	Designation
001AA	steering arrangement, left
005UK	wheelbase 1795+2980+1400 mm
006CI	rear frame overhang 800 mm
018SI	engine D2066LF06 - 400 hp / 294 KW EURO2 - 1900 Nm Common-Rail
02AAE	instrument panel km/h 'High-Line'
021GG	Transmission software for off-road use
022GW	gearbox ZF 12 AS 2330 OD MAN TipMatic
023EH	fuel tank 400l right
025ML	front axle VO-09/VO-09 straight
026EF	front springs parabolic 9,5 t
027AX	extended radiator and intercooler over 35 degrees ambient temperature
028ED	rear springs trapezoidal 16 t
028PA	Anbau Doppelachse
029GC	propshafts for increased load profile
03KAA	fuel tank fitted
030EE	steering wheel with height and inclination adjustment
032AB	MAN BrakeMatic (electronic brake system)
034EC	brake shoe width for rear axle 220 mm
034MH	hub-reduction rear axle HPD-1382/ HP-1352
035LF	planetary axle ratio $i = 4.33$
037AC	with differential lock in rear axle
038GH	disc wheels 10 hole 11.75-22.5 on 1st FA TL
038JH	disc wheels 10-hole 11.75-22.5 on 2nd front axle TL
038PG	disc wheels 10-hole 9.00-22.5 on 1st RA TL
038RG	disc wheels 10-hole 9.00-22.5 on 2nd RA TL
038TH	disc wheel 10-hole 11.75-22.5 as spare wheel TL
042DF	Digital tachograph, manufactured by CONTI
05NAE	front panel unlockable from inside
050NN	M cab 2240mm wide, 1880mm long
052XA	without stowage boxes
058BC	seat coverings in high-comfort quality
058NH	driver's seat, high-comfort, with air suspension
059NA	co-driver's seat static, with longitudinal + seat back adjustment
064AC	two additional vehicle keys
080AE	door interior panelling washable



116AE	visco fan
118AC	air deflector to stop dust swirling
118EK	short mounting base (only engine)
118MA	EDC engine regulation
119EH	general parameterisation for power take-offs
122CZ	PTO NH/4C without flange f=1.22 right side, horizontal
123AC	guard plate for 1 tank
123CC	strainer for fuel tank
124AL	fuel filter
124AZ	additional fuel filter with water trap
133MA	actuating system for tipper body
153KC	air conditioning system AC R134A with automatic temperature control without CFHC
159XS	without cab insulation NORDIC (against cold) for M, L and LX cab
194AB	operator's manual in English
201AR	air intake upswept with dry air filter / precleaner
201EM	air filter element with safety element for heavy-duty operation
201FA	fine dust and pollen filter
203EK	connection for external engine speed control (ZDR)
205AN	air compressor 1-cylinder, 360 ccm
206EY	exhaust on rh side with tail pipe to rear
208AK	exhaust valve brake
210XX	without flame starting system/ additional starting aid device
211FT	single-disc clutch MFZ 430 reinforced
227AC	rear axle breather upswept
230AH	rear underride guard, round
230XW	without front underride guard
230YX	without lateral underride guard
233EM	3-part steel bumper
236AF	cross member for trailer coupling
241AH	body attachment brackets bolted
245AE	spare-wheel holder on left side
256AA	steering wheel lock
256EA	emergency steering pump
258HA	anti-lock braking system (ABS)
259CA	disc brake for front axle
259CE	drum brake for rear axle
262XX	without brake connection on frame end
272FA	entry lighting for driver and co-driver
276AC	armrests for driver's seat
280EU	stoneguard grille in front of radiator
281AB	medium-height design
283FM	air sprung cab mounts for 'M' cab
284LE	Important: poorer ride comfort due to trapezoidal rear springs
303AM	tank cap lockable - 1 cap with vent (not licensable according to ECE-R34)
310CL	additional headlights and foglights
310EE	halogen twin headlights H7 for right-hand traffic
310HB	Daytime running lights (in conformance with ECE R87)
311AA	protective grille for headlights headlights
311AE	protective grille for taillamps
318AA	marker lamps
318AK	side marker lights
319AR	reading lamp for driver
321EC	central locking



324AC	two-tone horn,electric
324CA	2 air horns on cab roof/roof spoiler
325AA	MAN Tronic (on-board computer)
325EC	language 1 'English' for display in instrument panel
325FE	language 2 'French' for display in instrument panel
326XY	without 12/24 V socket at frame end
327AF	battery main switch, mechanical
329CS	batteries 12V 155Ah, 2 pcs
329ER	battery box up to 175Ah
329HC	service note for batteries "maintenance-free"
331AB	alternator Basic
339FP	Display on the dashboard for operating data
343AN	acoustic warning system for engaged reverse gear at frame end
345AU	Speed limiter, electronic 89 km/h + 1 km/h tolerance
345EA	cruise control
346CA	charging pressure indicator
350NN	Radio MAN Media Truck 12V with 5" display
350XO	without navigation SD
352CF	2 Halogen priority lights on cab roof
352WS	colour of revolving beacon yellow
358AA	ETA electric cutout
362AH	stabilizer on both rear axles
363AA	stabilizer for front axle
363AE	stabilizer on 2nd front axle
370CM	air dryer
373AE	Antifreeze effective down to -37 degrees
376XH	without mattress for lower bunk
376XK	without mattress for upper bunk
376XL	No bunks for 'M', 'C', 'DK' cabs
380AC	windscreen of laminated glass tinted
380CA	door windows tinted
381AA	cab rear wall without windows
381XC	without curtain before bunks
381YX	without all-round curtain
384AS	automatic seat belt, red
384CD	safety belt display, driver's side
385AT	side windows tinted behind B-post
386AS	mechanical sliding roof
387AF	electric door window lifters for driver and co-driver
388AH	roller blind for windscreen, mechanical
388AK	sun shade in front of windscreen
389AC	handles left and right (on B-post)
389AD	handles left and right (on A-post)
390XN	without waste paper bins between theseats
390XX	without oddment box
392AR	kerb mirror, right, heated and electrically adjustable
392AW	kerb mirror, left, heatable and electrically adjustable
392CL	EU front mirror on co-driver's side
392CW	Electrically heated and adjustable rear and wide-angle mirrors, wide angle mirror with el. manoeuvring
392HA	mirror arms for body width 2500-2600 mm width 2500 mm
394FM	1 Fire extinguisher 2 kg multilingual (English/German/Dutch)
400AH	mudflap front



401AS	mudguard cover for transfer
401CQ	Plastic mudguard, rear (half shell; without rain spray inhibitor)
401EL	3-part synthetic mudguards for 2nd front axle
404AP	spray reducer
405AC	first-aid kit
405AU	2 breakdown warning signs loose
405CP	20 m tyre inflator hose with pressure gauge
405FL	2 warning flashers loose for TW
406ED	lock for battery box
406FB	lock for spare wheel carrier
407AA	jack 25 t
411AA	1 chock
411AC	2nd chock
434CH	smoker-package
523AC	signs in English
538AE	plastic floor and engine tunnel covering
542DM	supplier's declaration
542FX	anti-noise measures are not in accordance with EU standard
542HS	aprons in wheel houses to prevent soiling of the engine
600AC	Fittings for right-hand traffic
796AB	Body ordered by central Sales Department
798LF	Height across cab unloaded up to 4000 mm
798RA	Aufbau/Umbau gemäß Truck Request Anfrage. TR-Nummer: R1.15013.8148
798WK	vehicle can be registered only as off-road vehicle to directive 70/156/EEC; note body
LQW01	chassis in water-based paint
LVS01	chassis graphite black RAL 9011 matt
LVS02	wheels White aluminium acrylic RAL 9006
LVS03	cab Pure white RAL 9010
80001	2 x 385/65R22,5 LENK-S+G TL CONTINENTAL
80002	2 x 385/65R22,5 LENK-S+G TL CONTINENTAL
90001	4 x 315/80R22,5 ANTR-S+G TL CONTINENTAL
90002	4 x 315/80R22,5 ANTR-S+G TL CONTINENTAL
90004	1 x 385/65R22,5 LENK-S+G TL CONTINENTAL