

Model : TGS 33.400 6X4 BBS-WW

Place of production:	MÜNCHEN
Vehicle model:	TGS 33.400 6X4 BBS-WW
Basic vehicle	L 26W AE 33

Technical extent of delivery

Code	Customer Special Request	Designation
001AA		steering arrangement, left
005NW		wheelbase 3900+1400 mm
006BO		rear frame overhang 700 mm
018SI		engine D2066LF06 - 400 hp / 294 KW EURO2 - 1900 Nm Common-Rail
02AAG		Instrument panel km/h 'High-Line in colour'
021GG		Gearbox software MAN TipMatic Offroad (off-road deployment)
022QE		MAN TipMatic 12 28 OD gearbox
023P8		Fuel tank aluminium 590l right
025MK		front axle VO-09 straight
026EC		front springs parabolic 8.0 t
027AX		extended radiator and intercooler over 35 degrees ambient temperature
028FP		rear springs parabolic 16 t
028PA		Fit tandem axles
029GC		Propshafts for high load profile
03KAA		fuel tank fitted
030EE		steering wheel with height and inclination adjustment
032AB		MAN BrakeMatic (electronic brake system)
034EC		brake shoe width for rear axle 220 mm
034MH		hub-reduction rear axle HPD-1382/ HP-1352
035LF		Planetary axle ratio $i = 4.33$
037AC		with differential lock in rear axle
038GG		disc wheels 10 hole 9.00-22.5 on 1stFA TL
038PG		disc wheels 10-hole 9.00-22.5 on 1stRA TL
038RG		disc wheels 10-hole 9.00-22.5 on 2ndRA TL
038TG		disc wheel 10-hole 9.00-22.5 as spare wheel TL
04WAE		Electrical spiral Y-cable 24-V 15-pin to 2x7-pin to semitrailer
042CY		EC tachograph electronic, automatic, 2 drivers
045CA		MAN EasyStart for TipMatic
05NAE		front panel unlockable from inside
050NF		L cab 2240mm wide, 2280mm long
052AE		Storage box accessible from outside - flap unlocked from inside
058BA		seat coverings in standard quality
058NH		driver's seat, high-comfort, with air suspension
059NA		co-driver's seat static, with longitudinal + seat back adjustment

080AE	door interior panelling washable
116AE	visco fan
116AZ	Fan control for use in hot countries
118AC	air deflector to stop dust swirling
118EK	Short mounting base (engine only)
118MA	EDC engine regulation
119EH	General PTO parameterisation
119KK	Coolant engine-protection function
122S4	PTO NH/4C without horizontal flange f=1.14 on right
123CC	strainer for fuel tank
124AL	fuel filter
124AZ	Auxiliary fuel filter with water separator
150WR	Brushed aluminium insert on instrument panel
153KA	air conditioning system AC R134A without CFHC
159XS	without cab insulation NORDIC (against cold) for M, L and LX cab
194AC	operator's manual in French
201AR	air intake upswept with dry air filter / precleaner
201EM	Air filter cartridge with safety insert for heavy-duty deployment
201FA	fine dust and pollen filter
203EK	connection for external engine speedcontrol (ZDR)
203ES	Control module for external data exchange (customer-specific control module) with fleet management system in
205AN	air compressor 1-cylinder, 360 ccm
206ET	exhaust on lh side with tail pipe towards rear
208AK	exhaust valve brake
210XX	Without flame-start/jump-start system
211FB	Single-disc clutch DBE 430, reinforced
227AC	rear axle breather upswept
230XW	Without front underride guard
233EM	3-part steel bumper
234AX	towing coupling ROCKINGER SK5
236AF	cross member for trailer coupling
245XX	without spare wheel holder
256AA	steering wheel lock
258HA	anti-lock braking system (ABS)
259CC	drum brake for front axle
259CE	drum brake for rear axle
262AZ	2-line brake connection behind cab
272FA	Entry lighting for driver and co-driver
278EA	Air connection in cab
278EF	Air lines and air gun
280AC	wiring for tank truck to ADR
280BA	Equipment for hazardous goods to ADR, type AT
280EU	stoneguard grille in front of radiator

280FB		Working platform with step and grab handle
281AB		medium-height design
283FS		Cab mounts on coil springs for 'L,LX,XL,XLX,XXL' cab
303AX		Lockable tank fastener - 1 u. ventilated for master key system
310EE		Halogen twin headlights H7 for right-hand traffic
310FA		2 spotlights on cab roof
310HB		Daytime driving lights (ECE R87-compliant)
310LH		Red/white interior lighting in cab roof
311AA		protective grille for headlights headlights
318AA		marker lamps
318AK		lateral marker lights
319AR		reading lamp for driver
321EC		central locking
324AC		Two-tone horn,electric
325AA		MAN Tronic (on-board computer)
325EE		Language 1 'French' for display in instrument panel
325FE		Language 2 'French' for display in instrument panel
326CP		15-pin 24 V trailer socket behind cab
326CR		trailer socket for ABS behind cab
327AF		battery main switch, mechanical
329CS		Two 12-V 155-Ah batteries
329ER		Battery box up to 175 Ah
329HC		Maintenance sign for batteries - 'maintenance-free'
331AB		Basic alternator
339FP		Display on the dashboard for operating data
343AN		Acoustic warning system at end of frame for engaged reverse gear
345CV		Maximum electronic speed limitation 85 km/h
345EA		cruise control
346CA		charging pressure indicator
350NN		MAN Media Truck radio, 12 V with five-inch colour display
350XO		Without navigation SD
351US		AUX-IN/USB in the instrument panel
352FD		Preparation for installation of flashing beacons
362AF		Stabiliser on 2nd rear axle only
363AA		Stabiliser for front axle
370CM		air dryer
373AE		antifreeze effective down to -35 degrees
373GD		Fully synthetic high-performance oilfor driven axles
376FA		1 bunk with storage space (with aluminium frame).
376HA		Mattress for lower bunk
376KA		Bunk cover for bottom bunk
376XK		Without Mattress for upper bunk
380AC		windscreen of laminated glass tinted
380CA		door windows tinted

381AA		cab rear wall without windows
381XC		Without curtain before bunks
381YX		Without all-roand curtain
384CD		Safety belt display, driver's side
385AT		Side windows tinted behind B-post
386AS		Mechanical lifting roof
387AF		Electric door window lifters for driver and co-driver
388AH		Roller blind for windscreen, mechanical
388AK		sun shade in front of windscreen
389AC		handles left and right (on B-post)
389AD		handles left and right (on A-post)
390CT		cup holder in dashboard
390XB		without pigeon hole on rear wall
390XX		without oddment box
392AH		kerb mirror, right
392CZ		Electrically heated and adjustable rear view mirror, heated wide-angle mirror
392HA		Mirror brackets for body width 2500-2600 mm width 2500 mm
392XJ		Without front mirror on co-driver's side/at centre
394ED		1 Fire extinguisher, Belgian, 3 kg
400AH		mudflap front
401EZ		Plastic mudguard three-part with flap (without spray reduction)
404AP		spray reducer
405AC		Bonding set, separate
405AK		hazard-warning sign
405AR		hazard-warning lamp
407AA		jack 25 t
411AA		1 chock
434DA		Interior design in Sand
44VCA		Crankcase ventilation closed
491LE		JOST JSK 38 C-1 3.5" fifth-wheel coupling, installation height 190 mm (without central lubrication connectio
493HL		Kingpin to rear axle centre 1125 mm
493YT		JOST fifth-wheel base plate 40 mm (fifth-wheel loads up to 36t)
523AE		signs in French
538AE		plastic floor and engine tunnel covering
542FX		anti-noise measures are not in accordance with EU standard
542HS		aprons in wheel houses to prevent soiling of the engine
542NC		Registration as N3 vehicle, (GVW > 12t)
600AC		Fittings for right-hand traffic
798LF		Height over cab, unloaded up to 4000mm
798WF		vehicle cannot be registered to directive 2000/40/EC. Exceptions possible under cert. circumstances.
LQW01		chassis in water-based paint
LVS01		chassis graphite black RAL 9011 matt

LVS02		wheels White aluminium acrylic RAL 9006
LVS03		cab Pure white RAL 9010
80001		2 wahlweise 13R22,5 LENK-S+G TL
90001		4 wahlweise 13R22,5 ANTR-S+G TL
90002		4 wahlweise 13R22,5 ANTR-S+G TL
90004		1 wahlweise 13R22,5 LENK-S+G TL

Weights:

Gross weight: 33000

1st front axle: 8000

2nd front axle: 0

3rd front axle: 0

Leading axle: 0

1st rear axle: 13000

2nd rear axle: 13000

Trailing axle: 0