

Model : TGM 15.240 4X2 BB

Place of production: STEYR

Vehicle model: TGM 15.240 4X2 BB

Basic vehicle : L N08 HG 06

Technical extent of delivery

Code	Designation
001AA	steering arrangement, left
005CR	wheelbase 4425 mm
006OB	rear frame overhang 2325 mm
018IC	Engine D0836LFL53 - 240 HP / 176 KW EURO4 - 925 Nm C-R OBD+NOx-S.
02AAB	instrument panel kmh 'Base-Line'
021GS	With/without gearbox software
022IE	Transmission ZF 9S-1310 OD
023FT	fuel tank 150l right
025MU	front axle VOK-07 dropped
026EA	front springs parabolic 7.1 t
027AC	radiator and intercooler
028EB	rear springs parabolic, 11.5 t
03KAA	fuel tank fitted
030AC	hydraulic steering
030EE	steering wheel with height and inclination adjustment
032AB	MAN BrakeMatic (electronic brake system)
034NH	hypoid rear axle HY-1133
035EV	Hypoid axle ratio i = 4.11
037AC	with differential lock in rear axle
038GC	disc wheels 10 hole 8.25-22.5 on 1stFA TL
038PC	disc wheels 10-hole 8.25-22.5 on 1stRA TL
038TC	disc wheel 10-hole 8.25-22.5 as spare wheel TL
042XY	without electronic tachograph
050NK	C cab 2240mm wide, 1620mm long
052XA	without stowage boxes
058BA	seat coverings in standard quality
058NA	driver's seat static, longitudinal adjustment and seat back adjustment
059HC	Static co-driver's seat with storagebox
080AE	door interior panelling washable
116AE	visco fan
118MA	EDC engine regulation
121EH	neutral pos. switch
123CE	chain for tank cap

124AL		fuel filter
124AM		additional fuel filter with water trap, make SEPAR
124EA		fuel filter heating
142AF		calibrate tachograph
153KC		air conditioning system AC R134A with automatic temperature control without CFHC
194AB		operator's manual in English
201HE		raised air intake with dry air filter at bottom right
205AP		1-cyl. compressor 238 cc
206ES		exhaust on rh side with tail pipe towards frame centre
208AB		engine brake with additional actuation via brake pedal
208XD		without exhaust valve brake (EVB)
210XX		Without flame-start/jump-start system
211AD		clutch with 395 mm diameter
219AF		steering oil reservoir with dipstick
230AC		with underride guard at rear
230ER		front underride guard
230YX		without lateral underride guard
232HC		synthetic bumper
234AX		towing coupling ROCKINGER SK5
236CS		rear cross member for trailer coupling 160X100
241AC		without platform mounting brackets
245AX		spare-wheel holder on left side behind rear axle
256AA		steering wheel lock
258HA		anti-lock braking system (ABS)
259CA		disc brake for front axle
259CB		disc brake for rear axle
262XX		without brake connection on frame end
278AE		Air filler connection at front
283FR		Cab mounts on coil springs for 'C' cab
303AX		Lockable tank fastener - 1 u. ventilated for master key system
309AA		Beam throw regulator
310EE		Halogen twin headlights H7 for right-hand traffic
318AA		marker lamps
318AK		lateral marker lights
319YX		without reading light
324AA		Single-tone horn, electric
325AA		MAN Tronic (on-board computer)
325EC		Language 1 'English' for display in instrument panel
326XY		Without 12/24 V socket on end of frame
327AF		battery main switch, mechanical
329AC		2 batteries 12 V 88 Ah
329ED		Battery box lockable (without lock)
329HC		Maintenance sign for batteries - 'maintenance-free'
33VAC		engine capsule

331AB		Basic alternator
339FP		Display on the dashboard for operating data
345AU		Maximum electronic speed limitation 89 km/h
345XA		Without cruise control
348AA		Coolant level indicator in cab
350CB		Preparation for radio 24V
362AA		Stabiliser for rear axle
363AA		Stabiliser for front axle
370CM		air dryer
376XH		Without Mattress for lower bunk
376XK		Without Mattress for upper bunk
376XL		No bunks for 'M' , 'C' , 'DK' cabs
380AC		windscreen of laminated glass tinted
380CA		door windows tinted
381AA		cab rear wall without windows
381XC		Without curtain before bunks
381YX		Without all-roand curtain
384CD		Safety belt display, driver's side
386XA		Without lifting roof
387AG		Mechanical door window lifters for driver and co-driver
388AB		Folding sunshade for driver and co-driver
389AC		handles left and right (on B-post)
389AD		handles left and right (on A-post)
390AX		storage compartment above windscreen
390XB		without pigeon hole on rear wall
390XX		without oddment box
392AH		kerb mirror, right
392AL		mechanical wide-angle mirror, right
392AT		mech. wide-angle mirror, left
392AY		rear view mirror, mech. adjustable
392CL		EU front mirror on co-driver's side
392HA		Mirror brackets for body width 2500-2600 mm width 2500 mm
396CC		windscreen washer electric
400AH		mudflap front
401AF		temporary transport mudguards
401CW		deletion of plastic mudguards
404AP		spray reducer
405AC		Bonding set, separate
405AP		deletion hazard-warning plate
405CK		Omission of hazard warning lights
407AN		Jack, 10 t
411AA		1 chock
434ES		dashboard in standard version
44VCA		Crankcase ventilation closed

523AC		signs in English
538AE		plastic floor and engine tunnel covering
542FC		anti-noise package 80 dB (92/97EEC)
542NC		Registration as N3 vehicle, (GVW > 12t)
600AC		Fittings for right-hand traffic
LQW01		chassis in water-based paint
LVS01		chassis graphite black RAL 9011 matt
LVS02		wheels White aluminium acrylic RAL 9006
LVS03		cab Pure white RAL 9010
80001		2 wahlweise 295/80R22,5 LENK-NAH TL
90001		4 wahlweise 295/80R22,5 ANTR-NAH TL
90004		1 wahlweise 295/80R22,5 LENK-NAH TL

Weights:

Gross weight: 15000

1st front axle: 7100

2nd front axle: 0

3rd front axle: 0

Leading axle: 0

1st rear axle: 11500

2nd rear axle: 0

Trailing axle: 0