

## Model : TGS 33.360 6X4 BB-WW

Place of production: MÜNCHEN

Vehicle model: TGS 33.360 6X4 BB-WW

Basic vehicle L 26W AE 05

### Technical extent of delivery

Code	Designation
001AA	steering arrangement, left
005NK	Wheelbase 3600+1400 mm
006CI	rear frame overhang 800 mm
018SJ	engine D2066LF07 - 360 hp / 265 kW EURO2 - 1800 Nm Common-Rail
02AAG	Instrument panel km/h 'High-Line in colour'
021GG	Gearbox software MAN TipMatic Offroad (off-road deployment)
022QE	MAN TipMatic 12 28 OD gearbox
023EH	fuel tank 400l right
023VA	smaller ground clearance because of fuel tank
025MK	front axle VO-09 straight
026EC	front springs parabolic 8.0 t
027AX	extended radiator and intercooler over 35 degrees ambient temperature
028EC	rear springs parabolic 13 t
028PA	Fit tandem axles
029GC	Propshafts for high load profile
03KAA	fuel tank fitted
030EE	steering wheel with height and inclination adjustment
032AB	MAN BrakeMatic (electronic brake system)
034EC	brake shoe width for rear axle 220 mm
034MH	hub-reduction rear axle HPD-1382/ HP-1352
035FA	Planetary axle ratio $i = 4.83$
037AC	with differential lock in rear axle
038GG	disc wheels 10 hole 9.00-22.5 on 1stFA TL
038PG	disc wheels 10-hole 9.00-22.5 on 1stRA TL
038RG	disc wheels 10-hole 9.00-22.5 on 2ndRA TL
038TG	disc wheel 10-hole 9.00-22.5 as spare wheel TL
042XY	without electronic tachograph
05NAE	front panel unlockable from inside
050NN	M cab 2240mm wide, 1880mm long
052XA	without stowage boxes
058BA	seat coverings in standard quality
058NH	driver's seat, high-comfort, with air suspension
059NA	co-driver's seat static, with longitudinal + seat back adjustment

064AC		two additional vehicle keys
080AE		door interior panelling washable
116AE		visco fan
116AZ		Fan control for use in hot countries
118AC		air deflector to stop dust swirling
118AP		Engine number also on crankcase
118EK		Short mounting base (engine only)
118LK		Intercooler suitable for fording, noneed for automatic dewatering
118MA		EDC engine regulation
119EH		General PTO parameterisation
119KK		Coolant engine-protection function
122S4		PTO NH/4C without horizontal flange f=1.14 on right
123AC		guard plate for 1 tank
123CC		strainer for fuel tank
124AL		fuel filter
124AZ		Auxiliary fuel filter with water separator
150MC		Window cleaning set
150WR		Brushed aluminium insert on instrument panel
153KC		air conditioning system AC R134A with automatic temperature control without CFHC
159XS		without cab insulation NORDIC (against cold) for M, L and LX cab
194AB		operator's manual in English
201AR		air intake upswept with dry air filter / precleaner
201EM		Air filter cartridge with safety insert for heavy-duty deployment
201FA		fine dust and pollen filter
203EK		connection for external engine speedcontrol (ZDR)
203ER		Control module for external data exchange (customer-specific control module) with body functionality
205AN		air compressor 1-cylinder, 360 ccm
206ET		exhaust on lh side with tail pipe towards rear
208AL		regulated rocker arm brake (EVBeC)
210XX		Without flame-start/jump-start system
211FB		Single-disc clutch DBE 430, reinforced
227AC		rear axle breather upswept
230AH		rear underride guard, round
230EM		underride guard at rear roand 'medium' for chassis without body from factory
230XW		Without front underride guard
230YX		without lateral underride guard
233EM		3-part steel bumper
236AF		cross member for trailer coupling
241AC		without platform mounting brackets
245AE		spare-wheel holder on left side
256AA		steering wheel lock
258HA		anti-lock braking system (ABS)
258HB		anti-spin regulator (ASR)

258TA		Electronic stability program (ESP)
259CC		drum brake for front axle
259CE		drum brake for rear axle
262XX		without brake connection on frame end
272FA		Entry lighting for driver and co-driver
280EU		stoneguard grille in front of radiator
281AB		medium-height design
283FB		Cab mounts on coil springs for 'M' cab
303AM		Lockable tank cap - one unit, ventilated (cannot be approved/registered in accordance with ECE-R34)
309AA		Beam throw regulator
310CL		Additional high-beam headlights and fog lights
310EE		Halogen twin headlights H7 for right-hand traffic
311AA		protective grille for headlights headlights
311AE		protective grille for taillamps
318AA		marker lamps
318AK		lateral marker lights
319AR		reading lamp for driver
321EC		central locking
324AC		Two-tone horn,electric
325AA		MAN Tronic (on-board computer)
325EC		Language 1 'English' for display in instrument panel
325FL		Language 2 'Portuguese' for display in instrument panel
326CK		trailer socket for anti-skid system on frame end
326XY		Without 12/24 V socket on end of frame
327AF		battery main switch, mechanical
329CT		Two 12-V 175-Ah batteries
329ER		Battery box up to 175 Ah
329HC		Maintenance sign for batteries - 'maintenance-free'
331AB		Basic alternator
339FP		Display on the dashboard for operating data
343AN		Acoustic warning system at end of frame for engaged reverse gear
345AS		Maximum electronic speed limitation 90 km/h
345EA		cruise control
346CA		charging pressure indicator
350NN		MAN Media Truck radio, 12 V with five-inch colour display
350TJ		Hands-free functionality for one mobile phone (multi-function steering wheel and Bluetooth -capable)
350XO		Without navigation SD
351US		AUX-IN/USB in the instrument panel
352CF		2 halogen revolving beacons on cab roof left and right
352WS		Revolving beacon, yellow
362AH		Stabiliser on both rear axles
363AA		Stabiliser for front axle

370CM	air dryer
373AE	antifreeze effective down to -35 degrees
376XH	Without Mattress for lower bunk
376XK	Without Mattress for upper bunk
376XL	No bunks for 'M' , 'C' , 'DK' cabs
380AC	windscreen of laminated glass tinted
380CA	door windows tinted
381AA	cab rear wall without windows
381XC	Without curtain before bunks
381YX	Without all-roand curtain
384CD	Safety belt display, driver's side
385AT	Side windows tinted behind B-post
386AS	Mechanical lifting roof
387AF	Electric door window lifters for driver and co-driver
388AH	Roller blind for windscreen, mechanical
388AK	sun shade in front of windscreen
388CA	Roller sunblinds on both doors
389AC	handles left and right (on B-post)
389AD	handles left and right (on A-post)
390CT	cup holder in dashboard
390XX	without oddment box
392AH	kerb mirror, right
392CZ	Electrically heated and adjustable rear view mirror, heated wide-angle mirror
392HA	Mirror brackets for body width 2500-2600 mm width 2500 mm
392XJ	Without front mirror on co-driver's side/at centre
400AH	mudflap front
401EZ	Plastic mudguard three-part with flap (without spray reduction)
404AP	spray reducer
405AC	Bonding set, separate
405AK	hazard-warning sign
405AR	hazard-warning lamp
407AH	jack 12 t
411AA	1 chock
417AC	wheel bolt covers front
434CH	Smoking package
434DA	Interior design in Sand
523AC	signs in English
538AE	plastic floor and engine tunnel covering
542FX	anti-noise measures are not in accordance with EU standard
542NC	Registration as N3 vehicle, (GVW > 12t)
600AC	Fittings for right-hand traffic
798LF	Height over cab, unloaded up to 4000mm
798WK	vehicle can be registered only as off-road vehicle to directive 70/156/EEC; note body
LQW01	chassis in water-based paint

LVS01		chassis graphite black RAL 9011 matt
LVS02		wheels White aluminium acrylic RAL 9006
LVS03		cab Traffic white RAL 9016
80001		2 Goodyear 315/80R22,5 MSSII TL 156/
90001		4 Goodyear 315/80R22,5 MSDII TL 156/
90002		4 Goodyear 315/80R22,5 MSDII TL 156/
90004		1 Goodyear 315/80R22,5 MSSII TL 156/

**Weights:**

Gross weight: 33000

1st front axle: 8000

2nd front axle: 0

3rd front axle: 0

Leading axle: 0

1st rear axle: 13000

2nd rear axle: 13000

Trailing axle: 0