

Vehicle Data

Model : TGS 26.360 6X2-4 BL-WW

Place of production: MÜNCHEN

Vehicle model: TGS 26.360 6X2-4 BL-WW

Basic vehicle L 18W DU 06

Technical extent of delivery

Code	Customer Special Request	Designation
001AA		steering arrangement, left
005KS		wheelbase 5100+1350 mm
006RS		rear frame overhang 2800 mm
018IZ		Engine D2066LF48 - 360 HP / 265 KW EURO3 - 1800 Nm common rail
02AAG		Instrument panel km/h 'High-Line in colour'
022H1		Gearbox ZF 16 S 223 DD
023EH		fuel tank 400l right
025MH		front axle VOK-09 dropped
026EC		front springs parabolic 8.0 t
027AN		radiator and intercooler for up to 35 degrees ambient temperature
028AM		air suspension rear
03KAA		fuel tank fitted
030EE		steering wheel with height and inclination adjustment
032AB		MAN BrakeMatic (electronic brake system)
034NK		hypoid rear axle HY-1350
035EV		Hypoid axle ratio i = 4.11
037XX		without differential lock in rear axle
038DG		disc wheels 10-hole 9.00-22.5 on trailing axle
038GG		disc wheels 10 hole 9.00-22.5 on 1stFA TL
038PG		disc wheels 10-hole 9.00-22.5 on 1stRA TL
038TG		disc wheel 10-hole 9.00-22.5 as spare wheel TL
041AD		trailing axle NOL-08 steered, lifting
042DM		Digital tachograph made by MAN
05NAE		front panel unlockable from inside
050NN		M cab 2240mm wide, 1880mm long
052XA		without stowage boxes
058BA		seat coverings in standard quality
058NH		driver's seat, high-comfort, with air suspension
059NA		co-driver's seat static, with longitudinal + seat back adjustment
080AE		door interior panelling washable
116AE		visco fan
118EK		Short mounting base (engine only)
118MA		EDC engine regulation

123CC		strainer for fuel tank
124AL		fuel filter
124AZ		Auxiliary fuel filter with water separator
150WR		Brushed aluminium insert on instrument panel
153YD		without air-conditioner
159XS		without cab insulation NORDIC (against cold) for M, L and LX cab
194AN		operator's manual in SPANISH
201AS		air intake raised with dry air filter
201EM		Air filter cartridge with safety insert for heavy-duty deployment
201FA		fine dust and pollen filter
205AN		air compressor 1-cylinder, 360 ccm
206ET		exhaust on lh side with tail pipe towards rear
208XD		without exhaust valve brake (EVB)
210XX		Without flame-start/jump-start system
211FJ		Single-disc clutch DTE 430
227AC		rear axle breather upswept
230AH		rear underride guard, round
230ER		front underride guard
230YX		without lateral underride guard
232HA		synthetic bumper with integrated airdam
236AF		cross member for trailer coupling
241AC		without platform mounting brackets
245AE		spare-wheel holder on left side
256AA		steering wheel lock
258HA		anti-lock braking system (ABS)
258HB		anti-spin regulator (ASR)
258NA		ECAS air suspension
259CA		disc brake for front axle
259CB		disc brake for rear axle
262AC		brake connection 2-line
272FA		Entry lighting for driver and co-driver
280EC		Fly mesh guard before radiator
283FB		Cab mounts on coil springs for 'M' cab
284WS		End of service life 16527 München 16.11.2020
303AX		Lockable tank fastener - 1 u. ventilated for master key system
310EE		Halogen twin headlights H7 for right-hand traffic
318AA		marker lamps
318AK		lateral marker lights
319AR		reading lamp for driver
321EC		central locking
324AC		Two-tone horn,electric
325AA		MAN Tronic (on-board computer)
325EH		Language 1 'Spanish' for display in instrument panel
325FL		Language 2 'Portuguese' for display in instrument panel
326CK		trailer socket for anti-skid system on frame end
326CN		15-pin 24 V trailer socket on end offrame
327AF		battery main switch, mechanical

329CT		Two 12-V 175-Ah batteries
329ER		Battery box up to 175 Ah
329HC		Maintenance sign for batteries - 'maintenance-free'
331AB		Basic alternator
339FP		Display on the dashboard for operating data
343CK		Acoustic warning system for engaged reverse gear, can be deactivated
345AS		Maximum electronic speed limitation 90 km/h
345EA		cruise control
346CA		charging pressure indicator
350NN		MAN Media Truck radio, 12 V with five-inch colour display
350XO		Without navigation SD
362AA		Stabiliser for rear axle
363AA		Stabiliser for front axle
365AA		starting-off aid
370CM		air dryer
373AE		antifreeze effective down to -35 degrees
376XH		Without Mattress for lower bunk
376XK		Without Mattress for upper bunk
376XL		No bunks for 'M' , 'C', 'DK' cabs
380AC		windscreen of laminated glass tinted
380CA		door windows tinted
381AA		cab rear wall without windows
381XC		Without curtain before bunks
381YX		Without all-roand curtain
384CD		Safety belt display, driver's side
385AT		Side windows tinted behind B-post
386XA		Without lifting roof
387AF		Electric door window lifters for driver and co-driver
388AH		Roller blind for windscreen, mechanical
388AK		sun shade in front of windscreen
389AC		handles left and right (on B-post)
389AD		handles left and right (on A-post)
390CT		cup holder in dashboard
390XX		without oddment box
392AH		kerb mirror, right
392CZ		Electrically heated and adjustable rear view mirror, heated wide-angle mirror
392HA		Mirror brackets for body width 2500-2600 mm width 2500 mm
392XJ		Without front mirror on co-driver's side/at centre
400AH		mudflap front
401EZ		Plastic mudguard three-part with flap (without spray reduction)
404AP		spray reducer
405AC		Bonding set, separate
405AK		hazard-warning sign
405AR		hazard-warning lamp
407AA		jack 25 t
411AA		1 chock
434CH		Smoking package

434DA		Interior design in Sand
44VCA		Crankcase ventilation closed
523AF		signs in Spanish
538AE		plastic floor and engine tunnel covering
542BC		COP document
542BK		exhaust gas certificate Euronorm
542FX		anti-noise measures are not in accordance with EU standard
542IZ		confirmation for international registration
542NC		Registration as N3 vehicle, (GVW > 12t)
600AC		Fittings for right-hand traffic
798LF		Height over cab, unloaded up to 4000mm
LQW01		chassis in water-based paint
LVS01		chassis graphite black RAL 9011 matt
LVS02		wheels White aluminium acrylic RAL 9006
LVS03		cab Traffic white RAL 9016
80001		2 wahlweise 315/70R22,5 LENK-NAH TL
90001		4 wahlweise 315/70R22,5 ANTR-NAH TL
90003		2 wahlweise 315/70R22,5 LENK-NAH TL
90004		1 wahlweise 315/70R22,5 LENK-NAH TL

Weights:

Gross weight: 26000

1st front axle: 8000

2nd front axle: 0

3rd front axle: 0

Leading axle: 0

1st rear axle: 11500

2nd rear axle: 0

Trailing axle: 7500