

Model : TGM 18.240 4X4 BB

Vehicle model: TGM 18.240 4X4 BB
 Basic vehicle : L N38 EG 06

Technical extent of delivery

Code	Customer Special Request	Designation
001AA		steering arrangement, left
005CU		wheelbase 4500 mm
006OB		rear frame overhang 2325 mm
018MK		engine D0836LFL40 - 240 hp / 176 kW EURO3 - 925 Nm Common Rail
02AAB		instrument panel kmh 'Base-Line'
021GG		Gearbox software MAN TipMatic Offroad (off-road deployment)
022SF		MAN TipMatic 12 12 OD gearbox
023CT		fuel tank 300l right
025MS		front axle VP-09 driven
026AV		front springs parabolic 7.5 t
026ZA		Caution: Front springs uprated to maximum
027AC		radiator and intercooler
028EB		rear springs parabolic, 11.5 t
03KAA		fuel tank fitted
030AC		hydraulic steering
030EE		steering wheel with height and inclination adjustment
032AB		MAN BrakeMatic (electronic brake system)
034EA		brake shoe width 180 mm for rear axle
034MF		hub-reduction rear axle HP-1333 single tyred
035KM		Planetary axle ratio $i = 5.33$
037AC		with differential lock in rear axle
037CB		differential lock in front axle with buzzer
037CM		restricted steering control when FA diff. lock is engaged
038EW		disc wheels 10-hole 10.00-20 on 1st FA TL
038FQ		disc wheel 10-hole 10.00-20 as sparewheel TL
038FX		disc wheels 10-hole 10.00-20 on 1st RA TL for single tyres
042XY		without electronic tachograph
050NK		C cab 2240mm wide, 1620mm long
052XA		without stowage boxes
058BA		seat coverings in standard quality
058NA		driver's seat static, longitudinal adjustment and seat back adjustment
059CD		co-drivers' bench for 2 persons (single seats)
080AE		door interior panelling washable

116AE		visco fan
118MA		EDC engine regulation
119EH		General PTO parameterisation
120EK		deep oil pan for gradeability up to 60%, oil quantity 16/20L
121EH		neutral pos. switch
123CC		strainer for fuel tank
123CE		chain for tank cap
124AL		fuel filter
124EA		fuel filter heating
142AF		calibrate tachograph
146AB		transfer case G 102
146AF		front wheel drive (dis)engageable
146CD		Transfer box management (VSM)
153KC		air conditioning system AC R134A with automatic temperature control without CFHC
194AC		operator's manual in French
201HF		raised air intake with dry air filter at bottom right/pre-separator
205AP		1-cyl. compressor 238 cc
206ES		exhaust on rh side with tail pipe towards frame centre
208AB		engine brake with additional actuation via brake pedal
208AK		exhaust valve brake
210XX		Without flame-start/jump-start system
211AD		clutch with 395 mm diameter
219AF		steering oil reservoir with dipstick
227EA		transfer case breather raised
230AC		with underride guard at rear
230YX		without lateral underride guard
233EK		steel bumper
234AX		towing coupling ROCKINGER SK5
234HC		2 shackles at front end of frame
236CS		rear cross member for trailer coupling 160X100
241AC		without platform mounting brackets
245XX		without spare wheel holder
256AA		steering wheel lock
258HA		anti-lock braking system (ABS)
258HB		anti-spin regulator (ASR)
258RA		hill-climbing brake
259CC		drum brake for front axle
259CE		drum brake for rear axle
262XX		without brake connection on frame end
278AE		Air filler connection at front
280BA		Equipment for hazardous goods to ADR, type AT
280TK		Deployment as fire fighter
281AA		high design
283FR		Cab mounts on coil springs for 'C' cab

303AX		Lockable tank fastener - 1 u. ventilated for master key system
308CB		Electrical preparation for retrofitting a PTO
309AA		Beam throw regulator
310EE		Halogen twin headlights H7 for right-hand traffic
310FA		2 spotlights on cab roof
311AA		protective grille for headlights headlights
311CH		off-road logic for ABS
318AA		marker lamps
318AK		lateral marker lights
319YX		without reading light
320AC		switches and wiring for cargo space lighting
322EA		protective roof for tail light
324AA		Single-tone horn, electric
325AA		MAN Tronic (on-board computer)
325EC		Language 1 'English' for display in instrument panel
325FE		Language 2 'French' for display in instrument panel
326CW		7+7-pin 24 V trailer socket at end of frame
327AF		battery main switch, mechanical
329CT		Two 12-V 175-Ah batteries
329ED		Battery box lockable (without lock)
329HC		Maintenance sign for batteries - 'maintenance-free'
33VAC		engine capsule
331AB		Basic alternator
339FP		Display on the dashboard for operating data
345AU		Maximum electronic speed limitation 89 km/h
345EA		cruise control
348AA		Coolant level indicator in cab
350AA		Preparation for Radio 12V
352CF		2 halogen revolving beacons on cab roof left and right
352WS		Revolving beacon, yellow
358AA		ETA electric cutout
362AA		Stabiliser for rear axle
363AA		Stabiliser for front axle
370CM		air dryer
376XH		Without Mattress for lower bunk
376XK		Without Mattress for upper bunk
376XL		No bunks for 'M' , 'C' , 'DK' cabs
380AC		windscreen of laminated glass tinted
380CA		door windows tinted
381AA		cab rear wall without windows
381XC		Without curtain before bunks
381YX		Without all-roand curtain
384CD		Safety belt display, driver's side
386XA		Without lifting roof

387AG		Mechanical door window lifters for driver and co-driver
388AB		Folding sunshade for driver and co-driver
388AK		sun shade in front of windscreen
389AC		handles left and right (on B-post)
389AD		handles left and right (on A-post)
390AX		storage compartment above windscreen
390XB		without pigeon hole on rear wall
390XX		without oddment box
392AG		Kerb mirror, left
392AH		kerb mirror, right
392AL		mechanical wide-angle mirror, right
392AT		mech. wide-angle mirror, left
392AY		rear view mirror, mech. adjustable
392CL		EU front mirror on co-driver's side
392HA		Mirror brackets for body width 2500-2600 mm width 2500 mm
396CC		windscreen washer electric
400AH		mudflap front
401AF		temporary transport mudguards
401CW		deletion of plastic mudguards
401EG		Mudguard cover panel widening in accordance with EU Directive 91/226/EEC
404AP		spray reducer
405AC		Bonding set, separate
405AK		hazard-warning sign
405AR		hazard-warning lamp
406ED		lock for battery box
407AN		Jack, 10 t
411AA		1 chock
434ES		dashboard in standard version
44VCA		Crankcase ventilation closed
523AC		signs in English
523CL		ABS/all-wheel drive sign in English
538AE		plastic floor and engine tunnel covering
542FB		Anti-noise package 82 dB (92/97EEC) off-road
542NG		Registration as an N3G vehicle, (GW >12 t)
600AC		Fittings for right-hand traffic
LQW01		chassis in water-based paint
LVS01		chassis graphite black RAL 9011 matt
LVS02		wheels White aluminium acrylic RAL 9006
LVS03		cab LIGHT IVORY RAL 1014
80001		2 wahlweise 365/85R20 GELAENDE TL
90001		2 wahlweise 365/85R20 GELAENDE TL
90004		1 wahlweise 365/85R20 GELAENDE TL

Weights:

Gross weight: 17500

1st front axle: 7500

2nd front axle: 0

3rd front axle: 0

Leading axle: 0

1st rear axle: 10000

2nd rear axle: 0

Trailing axle: 0