

## Model : TGS 26.440 6X4 BB

Place of production: WIEN

Vehicle model: TGS 26.440 6X4 BB

Basic vehicle L 26S KG 11

### Technical extent of delivery

Code	Customer Special Request	Designation
001AA		steering arrangement, left
005OI	X	Wheelbase 4200+1400 mm
006NC	X	rear frame overhang 2200 mm
018JA		Engine D2066LF40 - 440 hp / 324 KW EURO5 SCR - 2100 Nm C-R OBD2
02AAE		instrument panel km/h 'High-Line'
021GG		Gearbox software MAN TipMatic Offroad (off-road deployment)
022GW		MAN TipMatic 12 23 OD gearbox
023JD		Fuel tank 400l right and 35l AdBlue
025MK	X	front axle VO-09 straight
026EF		front springs parabolic 9,5 t
027AX	X	extended radiator and intercooler over 35 degrees ambient temperature
028MK	X	slide shackle springs for rear axle 13 t
028PA	X	Fit tandem axles
03KAA	X	fuel tank fitted
030EE		steering wheel with height and inclination adjustment
032AB		MAN BrakeMatic (electronic brake system)
034EC		brake shoe width for rear axle 220 mm
034MM	X	hub-reduction rear axle HPD-1353/ HP-1333
035KL		Planetary axle ratio $i = 4.00$
037AC		with differential lock in rear axle
038GH		disc wheels 10 hole 11.75-22.5 on 1st FA TL
038PG		disc wheels 10-hole 9.00-22.5 on 1stRA TL
038RG		disc wheels 10-hole 9.00-22.5 on 2ndRA TL
038TG		disc wheel 10-hole 9.00-22.5 as spare wheel TL
042XY		without electronic tachograph
05NAE	X	front panel unlockable from inside
050ND	X	double cab 'DK' 4 doors 'DK' 2240mm wide, 2785mm long
052XA		without stowage boxes
058BA	X	seat coverings in standard quality
058NH	X	driver's seat, high-comfort, with air suspension
059NA	X	co-driver's seat static, with longitudinal + seat back adjustment
080AE	X	door interior panelling washable

116AE		visco fan
118EK	X	Short mounting base (engine only)
118MA		EDC engine regulation
119EH		General PTO parameterisation
120KE		preparation for PTO at flywheel end with f=1.233
122JS		2 PTOs NAS/10 w/o flange f=1.03 top and with flange f=1.40 bottom
124AL		fuel filter
124AZ		Auxiliary fuel filter with water separator
124EA		fuel filter heating
142AF		calibrate tachograph
150MC	X	Window cleaning set
150WR		Brushed aluminium insert on instrument panel
153KC	X	air conditioning system AC R134A with automatic temperature control without CFHC
159XS	X	without cab insulation NORDIC (against cold) for M, L and LX cab
194AB		operator's manual in English
201AR	X	air intake upswept with dry air filter / precleaner
201FA		fine dust and pollen filter
203EK		connection for external engine speedcontrol (ZDR)
203ER		Control module for external data exchange (customer-specific control module) with body functionality
205AN		air compressor 1-cylinder, 360 ccm
206KA	X	exhaust at right-hand side
208AK		exhaust valve brake
210AA		flame starting system
211FF		single-plate clutch MFZ 430
227AC		rear axle breather upswept
230XW		Without front underride guard
230XX		Without rear underride guard
230YX		without lateral underride guard
233EM	X	3-part steel bumper
234HC		2 shackles at front end of frame
234HO		Trailer coupling RINGFEDER 4040 G 150B
236AF		cross member for trailer coupling
241AC		without platform mounting brackets
245XX		without spare wheel holder
256AF		steering wheel lock with immobiliser
258HA		anti-lock braking system (ABS)
258HB		anti-spin regulator (ASR)
258TA		Electronic stability program (ESP)
259CC	X	drum brake for front axle
259CE	X	drum brake for rear axle
262AC		brake connection 2-line
272FA		Entry lighting for driver and co-driver
272FF	X	step lighting at rear for double cab

280EU	X	stoneguard grille in front of radiator
280HD	X	Engine start/stop device under frontpanel
281AB	X	medium-height design
283FM	X	Air sprung cab mounts for 'M' cab
303AT		Non-lockable tank cap 1 u. non-ventilated (not eligible for approval/registration according to ECE-R34)
303CA		AdBlue filler cap 1 pc.
309AA		Beam throw regulator
310CL		Additional high-beam headlights and fog lights
310EE		Halogen twin headlights H7 for right-hand traffic
318AA		marker lamps
318AK	X	lateral marker lights
319AA	X	reading lamps for driver and co-driver
321EC		central locking
324AC		Two-tone horn,electric
325AA		MAN Tronic (on-board computer)
325EA		Language 1 'German' for display in instrument panel
326CK		trailer socket for anti-skid system on frame end
326CN		15-pin 24 V trailer socket on end offrame
326FZ		Socket in cab 12V 2-pole and 24V 2-pole
327AC	X	battery main switch, electric
329CT	X	Two 12-V 175-Ah batteries
329ER		Battery box up to 175 Ah
329HC		Maintenance sign for batteries - 'maintenance-free'
331CY		28V three-phase alternator 120A 3360W Longlife Eco
339FP		Display on the dashboard for operating data
345AZ		Speed limiter, electronic 100 km/h
345EA		cruise control
346CA		charging pressure indicator
350NN		MAN Media Truck radio, 12 V with five-inch colour display
350XO		Without navigation SD
358AA		ETA electric cutout
362AH		Stabiliser on both rear axles
363AA		Stabiliser for front axle
370CR		air dryer, heated
373AE		antifreeze effective down to -35 degrees
376XH		Without Mattress for lower bunk
376XK		Without Mattress for upper bunk
376XL	X	No bunks for 'M' , 'C' , 'DK' cabs
380AC	X	windscreen of laminated glass tinted
380CA	X	door windows tinted
381AA		cab rear wall without windows
381XC		Without curtain before bunks
381YX		Without all-roand curtain

384CD		Safety belt display, driver's side
385AT		Side windows tinted behind B-post
386AS	X	Mechanical lifting roof
387AF		Electric door window lifters for driver and co-driver
388AH		Roller blind for windscreen, mechanical
389AC	X	handles left and right (on B-post)
389AD		handles left and right (on A-post)
390XB	X	without pigeon hole on rear wall
390XN		without waste paper bins between theseats
390XX		without oddment box
392AH		kerb mirror, right
392CL	X	EU front mirror on co-driver's side
392CZ	X	Electrically heated and adjustable rear view mirror, heated wide-angle mirror
392HA		Mirror brackets for body width 2500-2600 mm width 2500 mm
400AH	X	mudflap front
401CY	X	synthetic mudguards, 3-part, with mud flaps
404AP	X	spray reducer
405AC	X	Bonding set, separate
405AK	X	hazard-warning sign
405AR	X	hazard-warning lamp
407AH	X	jack 12 t
411AF		2 chocks
538AE	X	plastic floor and engine tunnel covering
542DC		International data confirmation
542DM		Supplier declaration
542FC		anti-noise package 80 dB (92/97EEC)
542IZ		confirmation for international registration
542NC		Registration as N3 vehicle, (GVW > 12t)
600AC		Fittings for right-hand traffic
798LF	X	Height over cab, unloaded up to 4000mm
798WF		vehicle cannot be registered to directive 2000/40/EC. Exceptions possible under cert. circumstances.
799RK		Tyre load rating increased by 10% municipal allowance
LQA03		cab acryl
LQW01		chassis in water-based paint
LVS01		chassis graphite black RAL 9011 matt
LVS02		wheels White aluminium acrylic RAL 9006
LVS03		cab Pure white RAL 9010
80001		2 wahlweise 385/65R22,5 LENK-S+G TL
90001		4 wahlweise 315/80R22,5 ANTR-S+G TL
90002		4 wahlweise 315/80R22,5 ANTR-S+G TL
90004		1 wahlweise 315/80R22,5 LENK-S+G TL

**Weights:**

Gross weight: 28000

1st front axle: 9000

2nd front axle: 0

3rd front axle: 0

Leading axle: 0

1st rear axle: 13000

2nd rear axle: 13000