

Model : TGS 18.360 4X4 BB-WW

Vehicle model: TGS 18.360 4X4 BB-WW
 Basic vehicle L 52W DU 05

Technical extent of delivery

Code	Customer Special Request	Designation
001AA		steering arrangement, left
005CU		wheelbase 4500 mm
006OG		rear frame overhang 2350 mm
018IZ		Engine D2066LF48 - 360 HP / 265 KW EURO3 - 1800 Nm common rail
02AAG		Instrument panel km/h 'High-Line in colour'
022WO		Gearbox ZF 16 S 253 OD
023CH		fuel tank 220l right
025MS		front axle VP-09 driven
026EC		front springs parabolic 8.0 t
027AP		radiator and intercooler for over 35degrees ambient temperature
028EC		rear springs parabolic 13 t
03KAA		fuel tank fitted
030EE		steering wheel with height and inclination adjustment
032AB		MAN BrakeMatic (electronic brake system)
034MG		hub-reduction rear axle HP-1352
035FA		Planetary axle ratio i = 4.83
037AC		with differential lock in rear axle
038GZ		disc wheels, 10-hole 8.5-20 on 1st FA TT
038PZ		disc wheels, 10-hole 8.5-20 on 1st rear axle TT
038TZ		disc wheel, 10-hole 8.5-20.0 as spare wheel TT
042XY		without electronic tachograph
05NAE		front panel unlockable from inside
050NN		M cab 2240mm wide, 1880mm long
052XA		without stowage boxes
058BA		seat coverings in standard quality
058NH		driver's seat, high-comfort, with air suspension
059NA		co-driver's seat static, with longitudinal + seat back adjustment
080AE		door interior panelling washable
116AE		visco fan
116AZ		Fan control for use in hot countries
118AC		air deflector to stop dust swirling
118EK		Short mounting base (engine only)
118MA		EDC engine regulation
119EH		General PTO parameterisation

119KK		Coolant engine-protection function
123AC		guard plate for 1 tank
123CC		strainer for fuel tank
124AL		fuel filter
124AT		Heated additional fuel filter / water trap
124EA		fuel filter heating
142AF		calibrate tachograph
146AF		front wheel drive (dis)engageable
146KA		transfer case G172
150MC		Window cleaning set
150WR		Brushed aluminium insert on instrument panel
153KA		air conditioning system AC R134A without CFHC
159XS		without cab insulation NORDIC (against cold) for M, L and LX cab
194AB		operator's manual in English
195AG		preservation for transport overseas
201AR		air intake upswept with dry air filter / precleaner
201EM		Air filter cartridge with safety insert for heavy-duty deployment
201EY		Cyclone filter on front panel for cab fresh air mode
201FA		fine dust and pollen filter
203EK		connection for external engine speedcontrol (ZDR)
203ER		Control module for external data exchange (customer-specific control module) with body functionality
205AN		air compressor 1-cylinder, 360 ccm
206ET		exhaust on lh side with tail pipe towards rear
208AK		exhaust valve brake
210XX		Without flame-start/jump-start system
211FJ		Single-disc clutch DTE 430
227AA		front axle breather upswept
227AC		rear axle breather upswept
230AH		rear underride guard, round
230XW		Without front underride guard
230YX		without lateral underride guard
233EM		3-part steel bumper
236AF		cross member for trailer coupling
241AH		body attachment brackets bolted
245AE		spare-wheel holder on left side
256AF		steering wheel lock with immobiliser
258HA		anti-lock braking system (ABS)
259CC		drum brake for front axle
259CE		drum brake for rear axle
262XX		without brake connection on frame end
272FA		Entry lighting for driver and co-driver
280EC		Fly mesh guard before radiator
281AA		high design

283FB		Cab mounts on coil springs for 'M' cab
303AX		Lockable tank fastener - 1 u. ventilated for master key system
308CB		Electrical preparation for retrofitting a PTO
309AA		Beam throw regulator
310EE		Halogen twin headlights H7 for right-hand traffic
311AA		protective grille for headlights headlights
318AA		marker lamps
318AK		lateral marker lights
319AR		reading lamp for driver
321EC		central locking
324AC		Two-tone horn,electric
325AA		MAN Tronic (on-board computer)
325EC		Language 1 'English' for display in instrument panel
326CK		trailer socket for anti-skid system on frame end
326XY		Without 12/24 V socket on end of frame
327AF		battery main switch, mechanical
329CT		Two 12-V 175-Ah batteries
329ER		Battery box up to 175 Ah
329HC		Maintenance sign for batteries - 'maintenance-free'
331CY		28V three-phase alternator 120A 3360W Longlife Eco
339FP		Display on the dashboard for operating data
343AN		Acoustic warning system at end of frame for engaged reverse gear
345AS		Maximum electronic speed limitation 90 km/h
345EA		cruise control
346CA		charging pressure indicator
350NN		MAN Media Truck radio, 12 V with five-inch colour display
350XO		Without navigation SD
352FD		Preparation for installation of flashing beacons
358AA		ETA electric cutout
362AA		Stabiliser for rear axle
363AA		Stabiliser for front axle
370CM		air dryer
373AE		antifreeze effective down to -35 degrees
376XH		Without Mattress for lower bunk
376XK		Without Mattress for upper bunk
376XL		No bunks for 'M' , 'C' , 'DK' cabs
380AC		windscreen of laminated glass tinted
380CA		door windows tinted
381AA		cab rear wall without windows
381XC		Without curtain before bunks
381YX		Without all-roand curtain
384CD		Safety belt display, driver's side
385AT		Side windows tinted behind B-post
386AS		Mechanical lifting roof

387AF		Electric door window lifters for driver and co-driver
388AH		Roller blind for windscreen, mechanical
389AC		handles left and right (on B-post)
389AD		handles left and right (on A-post)
390CT		cup holder in dashboard
390XX		without oddment box
392AH		kerb mirror, right
392CL		EU front mirror on co-driver's side
392CZ		Electrically heated and adjustable rear view mirror, heated wide-angle mirror
392HA		Mirror brackets for body width 2500-2600 mm width 2500 mm
394FM		1 Fire extinguisher, 2 kg, multilingual (English/German/Dutch)
400AH		mudflap front
401EZ		Plastic mudguard three-part with flap (without spray reduction)
404AP		spray reducer
405AC		Bonding set, separate
405AK		hazard-warning sign
405AR		hazard-warning lamp
405CP		20 m tyre inflator hose with pressure gauge
406ED		lock for battery box
407AH		jack 12 t
411AA		1 chock
434DA		Interior design in Sand
44VCA		Crankcase ventilation closed
523AC		signs in English
538AE		plastic floor and engine tunnel covering
542FX		anti-noise measures are not in accordance with EU standard
542NG		Registration as an N3G vehicle, (GW >12 t)
600AC		Fittings for right-hand traffic
798LF		Height over cab, unloaded up to 4000mm
LQW01		chassis in water-based paint
LVS01		chassis graphite black RAL 9011 matt
LVS02		wheels White aluminium acrylic RAL 9006
LVS03		cab FLAME RED RAL 3000
80001		2 wahlweise 12,00R20 LENK S+G
90001		4 wahlweise 12,00R20 ANTR S+G
90004		1 wahlweise 12,00R20 LENK S+G

Weights:

Gross weight: 20500
1st front axle: 7500
2nd front axle: 0
3rd front axle: 0
Leading axle: 0
1st rear axle: 13000