

## MAN TGM 18.240 4X2 BB

| Code  | Designation  |
|-------|--|
| 000AA | Non-variable parts   |
| 001AC | steering arrangement, right  |
| 005BJ | Wheelbase 3575 mm  |
| 006EV | rear frame overhang 1125 mm  |
| 018MK | D0836LFL40 engine - 240 hp/176 kW EURO 3 - 925 Nm Common Rail                    |
| 02AAB | instrument panel kmh 'Base-Line'   |
| 022SF | gearbox ZF 12 AS 1210 OD MAN TipMatic  |
| 023FT | fuel tank 150l right   |
| 025MU | front axle VOK-07 dropped  |
| 026EA | front springs parabolic 7.1 t  |
| 027AC | radiator and intercooler   |
| 028EB | rear springs parabolic, 11.5 t   |
| 03KAA | fuel tank fitted   |
| 030AC | hydraulic steering   |
| 030EE | steering wheel with height and inclination adjustment                            |
| 032AB | MAN BrakeMatic (electronic brake system)   |
| 034NH | hypoid rear axle HY-1133   |
| 035FE | Hypoid axle ratio $i = 5.29$   |
| 037AC | with differential lock in rear axle  |
| 038GC | disc wheels 10 hole 8.25-22.5 on 1stFA TL  |
| 038PC | disc wheels 10-hole 8.25-22.5 on 1stRA TL  |
| 038TC | disc wheel 10-hole 8.25-22.5 as spare wheel TL                                   |
| 042XY | without electronic tachograph  |
| 050NK | C cab 2240mm wide, 1620mm long   |
| 052XA | without stowage boxes  |
| 058BA | seat coverings in standard quality   |
| 058NH | driver's seat, high-comfort, with air suspension                                 |
| 059HC | Static co-driver's seat with storagebox  |
| 064AC | two additional vehicle keys  |
| 080AE | door interior panelling washable   |
| 116AE | visco fan  |
| 118MA | EDC engine regulation  |
| 121EH | neutral pos. switch  |
| 123CC | strainer for fuel tank   |
| 123CE | chain for tank cap   |
| 124AL | fuel filter  |
| 124AR | additional fuel filter heated with water trap, make SEPAR                        |
| 124EA | fuel filter heating  |
| 142AF | calibrate tachograph   |
| 153KC | air conditioning system AC R134A with automatic temperature control without CFHC |
| 172EP | red-and-white warning stripes on doors and air deflectors                        |
| 201HL | Air-intake half-height behind cab. With dry air filter/pre-separator             |
| 205AP | 1-cyl. compressor 238 cc   |
| 206AR | exhaust upswept left   |
| 206TA | elbow for upswept or raised exhaust  |
| 208AB | engine brake with additional actuation via brake pedal                           |

|       |   |
|-------|---|
| 208XD | without exhaust valve brake (EVB)                               |
| 210AA | flame starting system   |
| 211AD | clutch with 395 mm diameter                                     |
| 219AF | steering oil reservoir with dipstick                            |
| 230AC | with underride guard at rear                                    |
| 230ER | front underride guard   |
| 230YX | without lateral underride guard                                 |
| 232HC | synthetic bumper  |
| 236CS | rear cross member for trailer coupling 160X100                  |
| 241AE | body mounting brackets on frame                                 |
| 245XX | without spare wheel holder                                      |
| 256AA | steering wheel lock   |
| 258HA | anti-lock braking system (ABS)                                  |
| 259CA | disc brake for front axle                                       |
| 259CB | disc brake for rear axle  |
| 262XX | without brake connection on frame end                           |
| 278AE | Air filler connection at front                                  |
| 283FR | Cab mounts on coil springs for 'C' cab                          |
| 303AX | Lockable tank fastener - 1 u. ventilated for master key system  |
| 309AA | Beam throw regulator  |
| 310EE | Halogen twin headlights H7 for right-hand traffic               |
| 318AA | marker lamps  |
| 318AK | lateral marker lights   |
| 319YX | without reading light   |
| 321EC | central locking   |
| 324AA | Single-tone horn, electric                                      |
| 325AA | MAN Tronic (on-board computer)                                  |
| 326FZ | Socket in cab 12V 2-pole and 24V 2-pole                         |
| 326XY | Without 12/24 V socket on end of frame                          |
| 327AF | battery main switch, mechanical                                 |
| 329CT | Two 12-V 175-Ah batteries                                       |
| 329ED | Battery box lockable (without lock)                             |
| 329HC | Maintenance sign for batteries - 'maintenance-free'             |
| 33VAC | engine capsule  |
| 331CY | 28V three-phase alternator 120A 3360W Longlife Eco              |
| 339FP | Display on the dashboard for operating data                     |
| 343AZ | Warning buzzer in seven-chamber light when reverse gear engaged |
| 345AU | Maximum electronic speed limitation 89 km/h                     |
| 345EA | cruise control  |
| 348AA | Coolant level indicator in cab                                  |
| 350LK | CB radio antenna on cab roof                                    |
| 350NK | Radio MAN CD 24V  |
| 351AF | preparation for radiotelephone                                  |
| 352CF | 2 halogen revolving beacons on cab roof left and right          |
| 352WS | Revolving beacon, yellow  |
| 362AA | Stabiliser for rear axle  |
| 363AA | Stabiliser for front axle                                       |
| 370CR | air dryer, heated   |
| 373AE | antifreeze effective down to -35 degrees                        |
| 376XH | Without Mattress for lower bunk                                 |

|       |  |
|-------|--|
| 376XK | Without Mattress for upper bunk                                |
| 376XL | No bunks for 'M' , 'C' , 'DK' cabs                             |
| 380AC | windscreen of laminated glass tinted                           |
| 380CA | door windows tinted  |
| 381AA | cab rear wall without windows                                  |
| 381XC | Without curtain before bunks                                   |
| 381YA | Without all-roand curtain for C/M cab                          |
| 384CD | Safety belt display, driver's side                             |
| 386AS | Mechanical sliding roof  |
| 387AF | Electric door window lifters for driver and co-driver          |
| 388AB | Folding sunshade for driver and co-driver                      |
| 389AC | handles left and right (on B-post)                             |
| 389AD | handles left and right (on A-post)                             |
| 390AX | storage compartment above windscreen                           |
| 390XB | without pigeon hole on rear wall                               |
| 390XX | without oddment box  |
| 392AK | rear-view mirror(s) heatable and electrically adjustable       |
| 392AR | kerb mirror, right, heated and electrically adjustable         |
| 392AS | Wide-angle mirror, right, heatable and electrically adjustable |
| 392AW | kerb mirror, left, heatable and electrically adjustable        |
| 392AX | wide-angle mirror, left, heated and electrically adjustable    |
| 392CL | EU front mirror on co-driver's side                            |
| 392HA | Mirror brackets for body width 2500-2600 mm width 2500 mm      |
| 394FM | 1 Fire extinguisher, 2 kg, multilingual (English/German/Dutch) |
| 396CC | windscreen washer electric                                     |
| 400AH | mudflap front  |
| 401AF | temporary transport mudguards                                  |
| 401CW | deletion of plastic mudguards                                  |
| 404AP | spray reducer  |
| 405AC | Bonding set, separate  |
| 405AK | hazard-warning sign  |
| 405AR | hazard-warning lamp  |
| 405CP | 20 m tyre inflator hose with pressure gauge                    |
| 407AN | Jack, 10 t   |
| 411AG | chock with bracket, loose                                      |
| 434ES | dashboard in standard version                                  |
| 524IB | Load variant 16000 kg  |
| 538AE | plastic floor and engine tunnel covering                       |
| 542DM | Supplier declaration   |
| 542FC | anti-noise package 80 dB (92/97EEC)                            |
| 542IZ | confirmation for international registration                    |
| 542NC | Registration as N3 vehicle, (GVW > 12t)                        |
| 600AC | Fittings for right-hand traffic                                |
| LQW01 | chassis in water-based paint                                   |
| LVS01 | chassis graphite black RAL 9011 matt                           |
| LVS02 | wheels White aluminium acrylic RAL 9006                        |
| LVS03 | cab DEEP ORANGE 2011   |
| 80001 | 2 wahlweise 295/80R22,5 LENK-S+G TL                            |
| 90001 | 4 wahlweise 295/80R22,5 ANTR-S+G TL                            |
| 90004 | 1 wahlweise 295/80R22,5 LENK-S+G TL                            |

|                      |
|----------------------|
| Weights:             |
| Gross weight: 16000  |
| 1st front axle: 7100 |
| 2nd front axle: 0    |
| 3rd front axle: 0    |
| Leading axle: 0      |
| 1st rear axle: 11500 |
| 2nd rear axle: 0     |
| Trailing axle: 0     |