

Model : TGL 8.160 4X2 BB

Place of production: STEYR
 Vehicle model: TGL 8.160 4X2 BB

Technical extent of delivery

Code	Customer Special Request	Designation
001AA		steering arrangement, left
005AO		wheelbase 3050 mm
006EL		rear frame overhang 1075 mm
018R3		Engine D0834LFL92 - 160 hp / 118 kW Euro 4 SCR - 600 Nm C-R without torque reduction
02AAG		Instrument panel km/h 'High-Line in colour'
021GS		With/without gearbox software
022ID		Transmission ZF 6S-800 OD
023AZ		plastic fuel tank, 100l, right
023Y3		Fuel tank, 35 l AdBlue
025LT		front axle VOK-05, dropped
026FX		front springs parabolic 3.4 t
027AC		radiator and intercooler
028FS		rear springs parabolic 5.6 t
028ZA		Caution: Rear springs uprated to maximum
03KAA		fuel tank fitted
030AC		hydraulic steering
030EE		steering wheel with height and inclination adjustment
032AB		MAN BrakeMatic (electronic brake system)
034ND		hypoid rear axle HY-0718
035HA		Hypoid axle ratio $i = 3.36$
037AC		with differential lock in rear axle
038IV		disc wheels 6-hole 6.00-17.5 on 1st FA TL
038OV		disc wheels 6-hole 6.00-17.5 on 1st rear axle TL
038UV		disc wheel 6-hole 6.00-17.5 as sparewheel TL
042XY		without electronic tachograph
050NK		C cab 2240mm wide, 1620mm long
052XA		without stowage boxes
058BA		seat coverings in standard quality

058NH		driver's seat, high-comfort, with air suspension
059CD		co-drivers' bench for 2 persons (single seats)
080AE		door interior panelling washable
116AE		visco fan
118AP		Engine number also on crankcase
118MA		EDC engine regulation
119EH		General PTO parameterisation
121EH		neutral pos. switch
122HD		PTO NH/1C without flange $f=0.53$
123CC		strainer for fuel tank
123CE		chain for tank cap
124AL		fuel filter
124AZ		Auxiliary fuel filter with water separator
124EA		fuel filter heating
133EL		MEILLER axial pump 254/1
133MA		actuating system for tipper body
142AF		calibrate tachograph
150WR		Brushed aluminium insert on instrument panel
153KA		air conditioning system AC R134A without CFHC
194CC		operator's manual in ARABIC
195AG		preservation for transport overseas
196KF		Reflective contour marking for cab, white
201CR		air intake upswept with dry air filter behind cab / precleaner
203EK		connection for external engine speedcontrol (ZDR)
203ER		Control module for external data exchange (customer-specific control module) with body functionality
205AP		1-cyl. compressor 238 cc
206ES		exhaust on rh side with tail pipe towards frame centre
208AA		exhaust brake
208AK		exhaust valve brake
210AA		flame starting system
211AD		clutch with 395 mm diameter
219AF		steering oil reservoir with dipstick
230ER		front underride guard
230XX		Without rear underride guard
230YX		without lateral underride guard
233EK		steel bumper
234EB		tow coupling RINGFEDER 6441
236CR		rear cross member for trailer coupling 140X80
241AE		body mounting brackets on frame
241CA		radiator guard
245AE		spare-wheel holder on left side
256AA		steering wheel lock
258HA		anti-lock braking system (ABS)

259CA		disc brake for front axle
259CB		disc brake for rear axle
262XX		without brake connection on frame end
278AE		Air filler connection at front
283FR		Cab mounts on coil springs for 'C' cab
303AX		Lockable tank fastener - 1 u. ventilated for master key system
303CA		AdBlue filler cap 1 pc.
309AA		Beam throw regulator
310EE		Halogen twin headlights H7 for right-hand traffic
318AA		marker lamps
318AK		lateral marker lights
319YX		without reading light
320AC		switches and wiring for cargo space lighting
321EC		central locking
324AA		Single-tone horn, electric
325AA		MAN Tronic (on-board computer)
325EC		Language 1 'English' for display in instrument panel
325KU		Language 2 'Arabic' for instrument panel display
326XY		Without 12/24 V socket on end of frame
327AF		battery main switch, mechanical
329AC		2 batteries 12 V 88 Ah
329ED		Battery box lockable (without lock)
329HC		Maintenance sign for batteries - 'maintenance-free'
331AB		Basic alternator
339FP		Display on the dashboard for operating data
343CK		Acoustic warning system for engaged reverse gear, can be deactivated
345AS		Maximum electronic speed limitation 90 km/h
345EA		cruise control
348AL		Indicator in cab for coolant and engine oil
350NN		MAN Media Truck radio, 12 V with five-inch colour display
350XO		Without navigation SD
352CF		2 halogen revolving beacons on cab roof left and right
352WS		Revolving beacon, yellow
362AA		Stabiliser for rear axle
363AA		Stabiliser for front axle
370CM		air dryer
373AE		antifreeze effective down to -35 degrees
376XH		Without Mattress for lower bunk
376XK		Without Mattress for upper bunk
376XL		No bunks for 'M' , 'C' , 'DK' cabs
380AC		windscreen of laminated glass tinted
380CA		door windows tinted
381AA		cab rear wall without windows
381XC		Without curtain before bunks

381YX		Without all-roand curtain
384CD		Safety belt display, driver's side
386AS		Mechanical lifting roof
387AF		Electric door window lifters for driver and co-driver
388AB		Folding sunshade for driver and co-driver
388AK		sun shade in front of windscreen
389AC		handles left and right (on B-post)
389AD		handles left and right (on A-post)
390AX		storage compartment above windscreen
390CW		pigeon hole on rear wall lhs
390XE		Without additional storage compartment in dashboard
390XX		without oddment box
392AR		kerb mirror, right, heated and electrically adjustable
392CL		EU front mirror on co-driver's side
392CZ		Electrically heated and adjustable rear view mirror, heated wide-angle mirror
392HA		Mirror brackets for body width 2500-2600 mm width 2500 mm
394FM		1 Fire extinguisher, 2 kg, multilingual (English/German/Dutch)
396CC		windscreen washer electric
400AH		mudflap front
401CH		plastic mudguards (full) rear
404AP		spray reducer
405AC		Bonding set, separate
405AK		hazard-warning sign
405AR		hazard-warning lamp
405CP		20 m tyre inflator hose with pressure gauge
407AH		jack 12 t
411AA		1 chock
434CH		Smoking package
434DA		Interior design in Sand
44VCA		Crankcase ventilation closed
451BC		body floor STE 500 - 3 mm
456AK		side boards STE 380 - 2 mm
456CC		Lashing eyes fully recessible in body floor
457EA		side-boards 400 mm
459AA		fold-down side boards
461KA		headboard 700 mm
462FE		ladder stored under tipper body
462XX		without deflector on headboard
463EA		tail board 400 mm
464AB		Oscillating back wall can also be partially folded down and manually operated claw closure
485QH		MEILLER tipper body 3,800x2,350
489MA		Reflective contour marking for tipper body, sides white and rear yellow
490PA		mineral oil for tipper hydraulics

523AC		signs in English
538AE		plastic floor and engine tunnel covering
542DC		International data confirmation
542DM		Supplier declaration
542FX		anti-noise measures are not in accordance with EU standard
542IZ		confirmation for international registration
542NA		Registration as N2 vehicle, (GVW <= 12t)
600AC		Fittings for right-hand traffic
799RK		Tyre load rating increased by 10% municipal allowance
LQW01		chassis in water-based paint
LVS01		chassis graphite black RAL 9011 matt
LVS02		wheels White aluminium acrylic RAL 9006
LVS03		cab Pure white RAL 9010
LVS04		body Pure white RAL 9010
80001		2 wahlweise 215/75R17,5 LENK-NAH TL
90001		4 wahlweise 215/75R17,5 ANTR-NAH TL
90004		1 wahlweise 215/75R17,5 LENK-NAH TL

Weights:

Gross weight: 8800
1st front axle: 3400
2nd front axle: 0
3rd front axle: 0
Leading axle: 0
1st rear axle: 5600
2nd rear axle: 0
Trailing axle: 0