

MEILLER tipper body 3,800 x 2,350

## 485QH



### Description

The MEILLER tipper body 3800 x 2350 is suitable for normal bulk materials (e.g. sand, gravel, coal, leaves) and general cargo.

- Payload range up to approx. 4500 kg
- Weight of entire tipper body in dimensions: 3.80 x 2.35 x 0.40 m clear = approx. 900 kg
- Side walls 2 mm steel plate QStE 380
- Body floor 3 mm steel plate QStE 500

Chassis connection frame:

2 side members, front and rear tipper carriers with rear reinforcement elements and crosshead

- Integrated hydraulics with telescopic cylinder with off setting, tip valve with pneumatic pickup

Steel tipper body:

- Tipper body undercarriage with 2 side members with closely positioned cross members

Welded floor panel with lashing recesses and screwed front wall 700 mm high

- Top crosshead with ball cup
- Front and rear outriggers
- Fold-down side walls with rub rails and noise dampers on lower side wall bearings at the side
- Top-hinged and fold-down rear wall
- Chain for side wall support, safety ropes, side rub rails, grab handles, ladder, locating pins protected against diagonal insertion

MEILLER hydraulic pump:

- Type 254 flange-mounted directly on the PTO

All steel components are sand blasted, primed and painted.

- Robust hook fasteners