



Vehicle description for: TGS 41.480 8x4 BB CH



Illustration can deviate

Vehicle standards

Product family	The new MAN Truck Generation
Model & Variant	TGS 41.480 8x4 BB CH
Vehicle type	Vehicle type Tipper (KI)
Cab	Local transport cab NN
Main wheel distance	3205 mm
Overhang	800 mm
Steering configuration	Left

Vertical Load

	National Registration	Technical Load
Gross weight	41,000 kg	41,000 kg
Front axle	8,000 kg	8,000 kg
Front axle 2	8,000 kg	8,000 kg
Rear axle	13,000 kg	13,000 kg
Rear axle 2	13,000 kg	13,000 kg

Horizontal Load

	National Registration	Technical Load
Gross train weight	0 kg	0 kg



The printed images in this offer are for explanatory purposes and may differ from the actual configuration.
For further product information on the tire selection "selectively", please contact our sales staff.

Vehicle characteristics

Basic characteristics

<input type="checkbox"/>	Chassis	0P2U9
<input type="checkbox"/>	Chassis class, heavy	0P2UC
<input type="checkbox"/>	Destination: Morocco (MA)	0P3HG
<input type="checkbox"/>	Merchant tonnage 41 t	0P8LN
<input type="checkbox"/>	Basic layout of vehicle, all-round rugged	0PGCV
<input type="checkbox"/>	Frame type, medium-high	0P2TQ
<input type="checkbox"/>	Vehicle type Tipper (KI)	0P2UN
<input type="checkbox"/>	Left-hand-drive	0P3AS
<input type="checkbox"/>	Right-hand traffic	0P3F5
<input type="checkbox"/>	Vehicle documents in English	0P2L7
<input type="checkbox"/>	Labelling in English	0P8NM
<input type="checkbox"/>	Cab position 640 mm (distance from frame lower edge to cab floor)	0PHBE

Registration

<input type="checkbox"/>	Vehicle approval, N3 class	0P3JR
<input type="checkbox"/>	Maximum speed limiter, 80 km/h, electronic, engine speed regulation	0P2UG
<input type="checkbox"/>	Maximum vehicle noise level, 80 dB in acc. with UN/ECE-R 51.02	0PINC
<input type="checkbox"/>	Vehicle classification in accordance with regulation (EU) 2018/858	0PKAW

Documents

<input type="checkbox"/>	Without registration documentation, national	0P3B0
<input type="checkbox"/>	Special confirmation, heavy load / municipal operation	0P3CK

Application scope / transport tasks

<input type="checkbox"/>	Construction	0P6WH
<input type="checkbox"/>	Increase of the tyre load capacity by 10% (for communal supplement)	0P0UU
<input type="checkbox"/>	023 Dump tipper	0P2QI
<input type="checkbox"/>	Temperature range, vehicle deployment, warm country	0PHIB
<input type="checkbox"/>	Case hardness of final drive Distribution	0P4F0

Lines, editions and packages

<input type="checkbox"/>	Special request paintwork	0PJTD
--------------------------	---------------------------	-------

Horizontal and vertical loads

<input type="checkbox"/>	41,000 kg permitted gross load, vertical, nat. appr.	0P5RD
<input type="checkbox"/>	41,000 kg permitted gross load, vertical, tech.	0P5UY
<input type="checkbox"/>	41,000 kg permitted gross load, vertical, tech. Plus	0P8IN
<input type="checkbox"/>	8,000 kg permitted load on front axle, nat. appr.	0P5KT
<input type="checkbox"/>	8,000 kg permitted load on front axle, tech.	0P5LN
<input type="checkbox"/>	8,800 kg permitted load on front axle, tech. Plus	0P5LT
<input type="checkbox"/>	8,000 kg permitted load on 2nd front axle NatZu	0P5F1
<input type="checkbox"/>	8,000 kg permitted load on 2nd front axle, tech.	0P5NM
<input type="checkbox"/>	8,800 kg permitted load on 2nd front axle, tech. Plus	0P7T1
<input type="checkbox"/>	13,000 kg permitted load on rear axle NatZu	0P5HC
<input type="checkbox"/>	13,000 kg permitted load on rear axle, tech.	0P5IO



<input type="checkbox"/>	13,000 kg permitted load on rear axle, tech. Plus	0P8BY
<input type="checkbox"/>	13,000 kg permitted load on 2nd rear axle NatZu	0P5FM
<input type="checkbox"/>	13,000 kg permitted load on 2nd rear axle, tech.	0P5M9
<input type="checkbox"/>	13,000 kg permitted load on 2nd rear axle, tech. Plus	0P7TJ
<input type="checkbox"/>	0kN D value	0P8XD

Chassis

Vehicle frame (wheelbase, overhang, ...)

<input type="checkbox"/>	Main wheelbase, 3,205 mm	0P2Z2
<input type="checkbox"/>	Wheelbase between front axles, 1,795 mm	0P3C1
<input type="checkbox"/>	Wheelbase between rear axles, 1,400 mm	0P3BX
<input type="checkbox"/>	Frame overhang, rear, 800 mm	0P3EU
<input type="checkbox"/>	Main frame side member thickness, 9.5 mm	0P0Y7
<input type="checkbox"/>	Vehicle rear, straight end of frame	0P0XT

Exhaust system, air intake

<input type="checkbox"/>	Exhaust silencer, side, right	0P1BH
<input type="checkbox"/>	Exhaust tailpipe, behind cab, right, vertical, with outlet valve	0P1BN
<input type="checkbox"/>	Air intake, behind cab, raised	0P0AY
<input type="checkbox"/>	Pre-separator for engine air intake	0P0BA

Battery cases, batteries, alternator

<input type="checkbox"/>	Battery, 12 V, 175 Ah, 2 units, maintenance free	0P0WA
<input type="checkbox"/>	Alternator, Basic	0P1BV
<input type="checkbox"/>	Medium battery box, 2 batteries	0P0WU
<input type="checkbox"/>	Battery box, left	0P0WO
<input type="checkbox"/>	Main battery switch, mechanical	0P0WF
<input type="checkbox"/>	Safety cut-out	0P1V2
<input type="checkbox"/>	Lockable battery box, with padlock	0P0WL

Tanks and fuel line

<input type="checkbox"/>	Guard plate for tanks	0P1DL
<input type="checkbox"/>	Fuel tank capacity 400 l, right	0P4ED
<input type="checkbox"/>	Fuel tank, right, steel	0P4GN
<input type="checkbox"/>	Tank cross-section, right, medium	0P4HE
<input type="checkbox"/>	AdBlue tank capacity 35 l, left	0P8N3
<input type="checkbox"/>	AdBlue tank, left, plastic	0P4H1
<input type="checkbox"/>	Fuel tank cap, lockable for master key system	0P4H5
<input type="checkbox"/>	Cap for AdBlue tank, lockable	0P4GE

Frame attachments

<input type="checkbox"/>	Without underride protection, front	0P1FM
<input type="checkbox"/>	Without working platform	0P0VH
<input type="checkbox"/>	Without underride protection, side	0P1FG
<input type="checkbox"/>	Final cross member, with hole pattern 160 x 100 mm	0P1SB
<input type="checkbox"/>	Underride protection, rear, round	0P1FD
<input type="checkbox"/>	Wheel chock, one unit, without retaining device, delivered loose	0P6WW



- Without body attachment brackets/thrust plates 0P0X6

Pneumatic brakes, compressed-air generation, brake system

- Air compressor, 1-cylinder, 360 ccm 0P0AF
- Compressed-air treatment, pneumatically controlled 0P0AB
- Steel compressed-air tank 0P0XH
- Electronic brake system (EBS) 0P0BL
- Anti-lock braking system (ABS) 0P0BE
- Full brake assistant 0P0CM
- Without preparation for EBS Full control unit 0PHPM
- MAN EVBec high-performance engine brake, stages possible 0P0BW
- Eco retarder, speed-dependent, stages possible, energy efficient 0P0BR
- Drum brakes on front axle 0P11A
- Drum brakes on 2nd front axle 0P11J
- Drum brakes on rear axle 0P115
- Drum brakes on 2nd rear axle 0P11F
- Parking brake control, next to driver's seat 0P3KH
- Brake cylinder with parking brake for increased gross weight 0P8QF
- Parking brake with spring-type actuator on rear axles (incl. leading axle/ trailing axle) 0PGBL
- MAN EasyStart immobiliser 0P1TF
- Brake lining thickness display, with brake lining wear warning 0P0BG
- Harmonisation of brake lining wear 0P0BI

Lights and acoustic signals on the chassis (rear lights, ...)

- Rear lights 0P2AQ
- Protective cover for rear lights 0P6XS
- Acoust. Reversing warning system when reverse gear selected 0P3CD
- Light function test 0P2AD
- Side marker lights, LED 0P2BJ

Driveline/running gear

Engine, radiator

- Diesel engine MAN D2676 LF07, 353 kW (480 hp) output, 2,300 Nm torque, Euro 5 0P6BL
- Fuel filter, heated, for fuels up to Cleanliness Class 25 0PHIG
- Fuel pre-filter, with oil separator/water trap, heated 0P0AU
- Engine dry-air filter, with safety insert 0P0B8
- Ventilation, crankcase, closed 0P8PM
- Anti-noise skirt, engine 0P2E7
- Fan control for start of cooling with low coolant temperature (e.g. hot country) 0P0K5
- Reduction of dust swirl through radiator fan 0P1YE
- Engine cooler, normal length 0P4XX
- Radiator protection, lower 0P1XE
- Front radiator protection, grille 0P1VP
- Engine oil dipstick and digital oil level gauge 0P0B6
- Warning message for engine coolant level, with advance warning 0P0KA
- Antifreeze, down to -32 °C 0P0AK
- Service product level indicator and intake system vacuum 0P3KT



Gearbox, clutch

<input type="checkbox"/>	MAN TipMatic 12.28 OD, with retarder 35	0P5VX
<input type="checkbox"/>	Gearbox for increased percentage of overrun during driving operation	0PGCL
<input type="checkbox"/>	MAN TipMatic actuation, with drop arm, manual (DNR option, switching strategy option)	0P3KI
<input type="checkbox"/>	MAN Idle Speed Driving gearbox function	0P0ER
<input type="checkbox"/>	MAN TipMatic Efficiency driving program, up to 70,000 kg	0P0FA
<input type="checkbox"/>	MAN TipMatic Offroad gearbox shift strategy, up to 70,000 kg	0P0F4
<input type="checkbox"/>	Single-disc clutch, 430 mm, dry, reinforced (LongLife)	0P0DW
<input type="checkbox"/>	Driveline propshaft, reinforced	0P0E2
<input type="checkbox"/>	Propshaft, 2nd rear axle, reinforced	0PGCF

Wheels, tyres

<input type="checkbox"/>	Required tyre speed index J	0PFW2
<input type="checkbox"/>	Front axle tyres optionally 315/80R22.5 Steering-Road+Offroad TL (156/150 K)	0PEXT
<input type="checkbox"/>	Rim type, front axle, steel, single-part	0P0P0
<input type="checkbox"/>	Rim size, front axle, 10-hole, 9.00x22.5	0P0NI
<input type="checkbox"/>	Wheel nut cover ring, front axle	0P0PR
<input type="checkbox"/>	Tyres 2nd front axle optional 315/80R22.5 steer S+G TL (156/150 K)	0PFIO
<input type="checkbox"/>	Rim type, 2nd front axle, steel, 1-part	0P0PF
<input type="checkbox"/>	Rim size, 2nd front axle, 10-hole, 9.00x22.5	0P0OH
<input type="checkbox"/>	Wheel nut cover ring, 2nd front axle	0P0Q3
<input type="checkbox"/>	Rear axle tyres optionally 315/80R22.5 Drive-Road+Offroad TL (154/150 K)	0PD RX
<input type="checkbox"/>	Rim type, rear axle, steel, single-part	0P0O0
<input type="checkbox"/>	Rim size, rear axle, 10-hole, 9.00x22.5	0P0MU
<input type="checkbox"/>	Tyres for 2nd rear axle optionally 315/80R22.5 Drive-Road+Offroad TL (154/150 K)	0PEA2
<input type="checkbox"/>	Rim type, 2nd rear axle, steel, single-part	0P0PA
<input type="checkbox"/>	Rim size, 2nd rear axle, 10-hole, 9.00x22.5	0P0O7
<input type="checkbox"/>	Tyre inflation hose, 20 m, with pressure gauge	0P1UA
<input type="checkbox"/>	Centring sleeves for rim mounting	0PHZW

Axles

<input type="checkbox"/>	8x4	0P3BI
<input type="checkbox"/>	Steering ratio, standard	0P1JX
<input type="checkbox"/>	Steering oil tank with electrical measuring sensor	0P1JV
<input type="checkbox"/>	Front axle, 9,200 kg, not driven, straight, steered, not liftable	0P5EX
<input type="checkbox"/>	Mudguard, front axle	0P1AT
<input type="checkbox"/>	2nd front axle, 9,200 kg, not driven, straight, steered, not liftable	0P4ZH
<input type="checkbox"/>	Mudguard, 2nd front axle, removable upper shell	0P1B8
<input type="checkbox"/>	Splash guard flaps on mudguard, 2nd front axle	0P1Y2
<input type="checkbox"/>	Rear axle, 13,000 kg, planetary axle with drive shaft, straight, not steered, not liftable	0P4ZM
<input type="checkbox"/>	Twin tyre on rear axle	0P1HN
<input type="checkbox"/>	Transfer mudguard, rear axle	0P1AQ
<input type="checkbox"/>	2nd rear axle, 13,000 kg, planetary axle without drive shaft, straight, not steered, not liftable	0P4Y7
<input type="checkbox"/>	Twin tyre on 2nd rear axle	0P1HW
<input type="checkbox"/>	Transfer mudguard, 2nd rear axle	0P1B6
<input type="checkbox"/>	Axle ratio, i = 6.00	0P0DF
<input type="checkbox"/>	Differential locks on driven rear axles	0P0DI
<input type="checkbox"/>	Without differential locks, front axles	0P0DL



- Emergency steering pump 0P1KO

Axle control system and suspension

- Suspension type for front axles and driven rear axles, leaf/leaf (BB) 0P2YB
- Leaf-spring suspension on front axle, parabolic, 4-leaf, steel 0P1JF
- Leaf-spring suspension on 2nd front axle, parabolic, 4-leaf, steel 0P1JT
- Leaf-spring suspension on rear axle, parabolic, 5-leaf, steel 0P1J2
- Leaf-spring suspension on 2nd rear axle, parabolic, 5-leaf, steel 0P1JL
- Spring load-bearing capacity front axle 9,500 kg 0P5C4
- Spring load-bearing capacity of 2nd front axle, 9,500 kg 0P5DF
- Spring load-bearing capacity of rear axle, 13,000 kg 0P5BV
- Spring load-bearing capacity of 2nd rear axle, 13,000 kg 0P5C7
- Shock absorbers on front axle 0P1M4
- Shock absorbers on 2nd front axle 0P1ME
- Shock absorbers on rear axle 0P1LQ
- Shock absorbers on 2nd rear axle 0P1M9
- Stabiliser, front axle 0P1LD
- Stabiliser, 2nd front axle 0P1LK
- Stabiliser, rear axle 0P1LA
- Stabiliser, 2nd rear axle 0P1LH
- Wishbone, reinforced 0P6ZS

Cab

Cab and cab exterior

- Local transport cab NN 0P2DL
- Cab mount, Basic 0P1V8
- Cab tilt mechanism, manual 0P1V6
- No tilting roof/sliding roof 0P1VY
- Bumper, steel, 3 pieces 0P1SG
- Front step, integrated, with grab option 0P1VE
- Windscreen, composite safety glass, tinted 0P1X0
- Sunblind, in front of windscreen 0P1WK
- Wiper system for windscreen 0P1WG
- Wiper activation, manual 0P1UL
- Step unit, hinged 0P1V0
- Central locking, no remote control 0P1WS
- Vehicle key, 4 units 0P3JU
- No door extension 0P1WV
- Door labelling, according to maximum technically permitted overall vehicle weight 0P2DO
- Door windows, tinted 0P1WO
- Door window, safety glass 0P1WM
- Cab rear wall, no window 0P1VD

Lights and acoustic signals on cab exterior (headlights, horn, ...)

- Front headlights, H7 0P1ZN
- Stone protection guard for front headlights, wide and fine mesh 0PICD
- Daytime driving lights, LED 0P2BP



<input type="checkbox"/>	Fog lights, H7	0P2AH
<input type="checkbox"/>	Headlight beam regulator, manual	0P2AC
<input type="checkbox"/>	Driving-light control, manual	0P1ZF
<input type="checkbox"/>	Contour lights, LED, 2 units	0P2BS
<input type="checkbox"/>	Turn signal lights, sides, bulb	0P1Z6
<input type="checkbox"/>	Horn, two-tone, electrical	0P1W1
<input type="checkbox"/>	Revolving beacons, LED, yellow (individual LEDs light up in cascades, revolving)	0P2BD
<input type="checkbox"/>	2 revolving beacons on cab roof, 1 right and 1 left	0P2B3
<input type="checkbox"/>	Spotlight, 1 unit, cab roof, left	0P1YK
<input type="checkbox"/>	Spotlight, halogen, white	0P1YY
<input type="checkbox"/>	Spotlight/manoeuvring light, only in conjunction with parking lights	0P2C6
<input type="checkbox"/>	Preparation for loading area lighting	0P2A5
<input type="checkbox"/>	Without revolving beacons at the rear of the vehicle	0PJRO

Mirrors and mirror replacements

<input type="checkbox"/>	Exterior rear-view mirror, electrically adjustable	0P2CA
<input type="checkbox"/>	Mirror housing, not painted	0P2CP
<input type="checkbox"/>	Vehicle components, suitable for body width larger than 2,400 mm to 2,600 mm	0P2CT
<input type="checkbox"/>	Kerb mirror, right, electrically adjustable	0P2CG
<input type="checkbox"/>	Front mirror, mechanical adjustment	0P2CJ

Seats

<input type="checkbox"/>	Seat covers, fabric, standard	0P2PQ
<input type="checkbox"/>	Comfort driver's seat, air-sprung	0P2P2
<input type="checkbox"/>	Driver's seat arm rests	0P2OE
<input type="checkbox"/>	Co-driver's seat, not sprung, with storage box	0P2OO
<input type="checkbox"/>	Storage space, in seat bracket of co-driver's seat	0P2Q6
<input type="checkbox"/>	Seat belt indicator, driver's side, acoustic and visual	0P2NB

Driver's workplace

<input type="checkbox"/>	Multi-function steering wheel, adjustable height and angle	0P2GD
<input type="checkbox"/>	Steering wheel, with parking position	0P2GE
<input type="checkbox"/>	Steering lock	0P3JZ
<input type="checkbox"/>	Instrumentation, Basic km/h	0P3L3
<input type="checkbox"/>	Analogue tachograph, CONTINENTAL	0P2KW
<input type="checkbox"/>	Tachograph, calibrated	0P2KG
<input type="checkbox"/>	Stowage compartment, open with two USB sockets, 5 V, charging only, to the right of climate control panel	0PGT7
<input type="checkbox"/>	2 pull-out cup holders in instrument panel	0P2FA
<input type="checkbox"/>	Cigarette lighter	0P2IH
<input type="checkbox"/>	Single DIN slots, 4 units, roof space, front	0P2FJ

Cab air-conditioning system

<input type="checkbox"/>	Air-conditioning system, manual	0P2NU
<input type="checkbox"/>	Pre-separator (cyclone filter) for interior air intake	0P2O7

Bunk area

<input type="checkbox"/>	Without bunk area package	0PKNE
--------------------------	---------------------------	-------

Cab interior



<input type="checkbox"/>	Without interior lighting package	0PKNF
<input type="checkbox"/>	Colour scheme for interior styling, dark	0P2I6
<input type="checkbox"/>	Interior styling analogous to colour scheme	0PGBT
<input type="checkbox"/>	Windscreen roller blind, internal	0P2FE
<input type="checkbox"/>	Interior light, central	0PHA6
<input type="checkbox"/>	Reading light, 2 units, 1 on driver's side and 1 on co-driver's side	0P2IR
<input type="checkbox"/>	Entry lighting	0P2IO
<input type="checkbox"/>	Door interior cladding, washable	0P2IA
<input type="checkbox"/>	Storage, instrument panel in middle section, open	0P2HK
<input type="checkbox"/>	Storage box, centre area, to rear	0P2H9
<input type="checkbox"/>	Storage box, cab rear wall, 2 units, behind driver's and co-driver's sides	0P2F2
<input type="checkbox"/>	Grab handle, above door, internal, 2 units, 1 right and 1 left	0P2G2
<input type="checkbox"/>	Entry handles, standard	0PHPK

Accessories and tools

<input type="checkbox"/>	Compressed-air connection, cab	0P2FL
<input type="checkbox"/>	Jack, 12,000 kg	0P3F8
<input type="checkbox"/>	Vehicle toolkit	0P2TX
<input type="checkbox"/>	No warning triangle	0P3FH

Intelligent Truck

Assistance systems

<input type="checkbox"/>	Electronic Stability Program (ESP)	0P1TN
<input type="checkbox"/>	Anti-slip control (ASR)	0P1T2
<input type="checkbox"/>	Tempomat (cruise control, CC)	0P1TR
<input type="checkbox"/>	Road speed limiter, adjustable, limiter (engine speed regulation)	0P0C3
<input type="checkbox"/>	Without advanced emergency braking system	0P1U5

Infotainment (radio,...)

<input type="checkbox"/>	MMT infotainment system, Starter Basic	0P2M1
<input type="checkbox"/>	MAN loudspeaker system	0P2MF
<input type="checkbox"/>	No navigation map	0P2N2
<input type="checkbox"/>	French additionally for display	0P2JT

Bodies/interfaces

Interfaces to semitrailer (e.g. fifth-wheel coupling, brake connection,...)

<input type="checkbox"/>	Without trailer brake connection behind cab	0P1O3
<input type="checkbox"/>	No fifth-wheel coupling	0P1RJ

Interfaces to trailer (e.g. trailer coupling, brake connections,...)

<input type="checkbox"/>	Towing coupling at final cross member, ROCKINGER SK5	0P1MZ
<input type="checkbox"/>	Towing coupling on final cross member	0P1SH
<input type="checkbox"/>	Without trailer brake connection at end of frame, centre	0P1O0
<input type="checkbox"/>	Without trailer socket at frame end	0P1OW
<input type="checkbox"/>	Without trailer socket for anti-lock brake system (ABS)	0P1O9



Ex works bodies and interfaces to bodies (e.g. tipper indicator...)

<input type="checkbox"/>	Interface for data exch. with body (customer-specific control module) and engine intermediate speed control (ZDR), front area of cab	0P2NA
<input type="checkbox"/>	Interface for vehicle data (FMS)	0P2J3
<input type="checkbox"/>	Tipper indicator, cab (symbols)	0P2M5
<input type="checkbox"/>	Electrical preparation for keypad, body control	0PINX

PTOs

<input type="checkbox"/>	PTO, gearbox-dependent, type NH/4c, without flange, f=0.88/1.14, position approx. 2:30 o'clock	0P4QS
<input type="checkbox"/>	PTO, gearbox-dependent, for short-time operation less than 60 min	0P4VK
<input type="checkbox"/>	PTO, gearbox-dependent, shiftable	0P4X9
<input type="checkbox"/>	Without fan wheel for PTO, gearbox-dependent	0P4VR
<input type="checkbox"/>	Function parameters for PTO; gearbox-dependent, driving operation	0P4WP
<input type="checkbox"/>	Sector-specific parameterisation, general	0P4X0

Towing, recovery and lashing

<input type="checkbox"/>	Central coupling jaw, integrated in bumper/front cross member, with lock pin	0P1MK
--------------------------	--	-------

Paintworks

Paintwork, cab, top

<input type="checkbox"/>	Top coating, cab	0P6YB
--------------------------	------------------	-------

Paintwork, cab, bottom

<input type="checkbox"/>	Textured coating, step units	0P6X9
<input type="checkbox"/>	Textured coating, mudguard, behind cab	0P6YG
<input type="checkbox"/>	Textured coating, bumper, steel	0P6YQ

Paintwork, chassis

<input type="checkbox"/>	Top coating, chassis	0P6YC
<input type="checkbox"/>	Top coating, rims, steel, white-aluminium	0P6YL

Colour

<input type="checkbox"/>	Top coating, cab	DEEP ORANGE RAL 2011	N
<input type="checkbox"/>	Top coating, chassis	GRAPHITE BLACK RAL 9011	W



Technical data: TGS 41.480 8x4 BB CH / L39EAA03

Vehicle type: Vehicle type Tipper (KI)
 Cab: Local transport cab NN
 Drive Type: 8x4

TD018	Statorily permissible gross vehicle weight	41000
TD025	Technically permissible gross vehicle weight	41000
TD031	Statorily permissible gross train weight	0
TD032	Statorily permissible trailer load	0

Lengths		mm
TD071	Total length	9177.0
TD063	Front vehicle overhang	1607.0
TD057	Wheelbase between front axles	1795
TD058	Wheelbase between leading axle and rear axle	0
TD059	Wheelbase between rear axles	1400
TD060	Wheelbase between rear axle and trailing axle	0
TD064	Rear frame overhang	800.0
TD072	Distance from first front axle to body	604.0
TD067	Distance to kingpin from front axle, nominal position	-
TD074	Slew radius, front	-
TD075	Slew radius, rear	-
TD068	Coupling length	8595.0

Widths		mm
TD008	Width included rearview mirror	2981.0
TD001	Width over cab	2240.0

Frame		mm
TD009	Frame width at front	945.0
TD010	Frame width at the rear	765.0
TD078	Frame profile	270 x 85 x 9,5

Heights		mm
TD033	Maximum external height, unladen	3285.0
TD082	Total transport height, unladen	3285.0
TD034	Maximum external height, laden	3211.0
TD035	Frame height at theoretical rear wheelbase, unladen	1136.0
TD036	Frame height at theoretical rear wheelbase, laden	1056.0
TD045	Raising from driving position, front	0.0
TD046	Lowering from driving position, front	0.0
TD047	Raising from driving position, rear	0.0
TD048	Lowering from driving position, rear	0.0
TD051	Height of fifth-wheel coupling above ground, unladen	-
TD052	Height of fifth-wheel coupling above ground, laden	-

Circle dimensions		m
TD055	Track circle diameter	20.4
TD056	Wall-to-wall turning circle diameter	22.2

Weights/loads		kg
TD026	Chassis weight with cab	10666.0
TD027	Chassis weight, front	---
TD028	Chassis weight, rear	---
TD029	Payload	---

The technical data must be considered as an approximation. Some of the values are given in a simplified form. More detailed notes and descriptions can be found in the respective information in the overview. Contents and specifications have been compiled with the greatest possible care. Nevertheless, we do not assume responsibility for the data and values supplied being correct and up to date. Subject to errors and changes. MAN Truck & Bus AG is liable only in cases of intent, gross negligence or culpable breach of significant contractual obligations.